

&gt;&gt;

# PostgreSQL Buffer Manager

---

- PostgreSQL Buffer Manager
- Clock-sweep Replacement Strategy

COMP9315 21T1 ◇ PG Buffers ◇ [0/8]

## ❖ PostgreSQL Buffer Manager

PostgreSQL buffer manager:

- provides a shared pool of memory buffers for all backends
- all access methods get data from disk via buffer manager

Buffers are located in a large region of shared memory.

Definitions: **src/include/storage/buf\*.h**

Functions: **src/backend/storage/buffer/\*.c**

Buffer code is also used by backends who want a private buffer pool

## ❖ PostgreSQL Buffer Manager (cont)

Buffer pool consists of:

### **BufferDescriptors**

- shared fixed array (size **NBuffers**) of **BufferDesc**

### **BufferBlocks**

- shared fixed array (size **NBuffers**) of 8KB frames


**Buffer** = index values in above arrays

- indexes: global buffers **1..NBuffers**; local buffers negative

Size of buffer pool is set in [postgresql.conf](#), e.g.

```
shared_buffers = 16MB      # min 128KB, 16*8KB buffers
```

## ❖ PostgreSQL Buffer Manager (cont)



COMP9315 21T1 ◇ PG Buffers ◇ [3/8]

## ❖ PostgreSQL Buffer Manager (cont)

### **include/storage/buf.h**

- basic buffer manager data types (e.g. **Buffer**)

### **include/storage/bufmgr.h**

- definitions for buffer manager function interface  
(i.e. functions that other parts of the system call to use buffer manager)

### **include/storage/buf\_internals.h**

- definitions for buffer manager internals (e.g. **BufferDesc**)

Code: **backend/storage/buffer/\*.c**

Commentary: **backend/storage/buffer/README**

## ❖ PostgreSQL Buffer Manager (cont)

Definition of buffer descriptors simplified:

```
typedef struct BufferDesc
{
    BufferTag    tag;        // ID of page contained in buffer
    int          buf_id;     // buffer's index number (from 0)

    // state, containing flags, refcount and usagecount
    pg_atomic_uint32 state;

    int          freeNext;   // link in freelist chain
    ...
} BufferDesc;
```

COMP9315 21T1 ◇ PG Buffers ◇ [5/8]

## ❖ Clock-sweep Replacement Strategy

PostgreSQL page replacement strategy: **clock-sweep**

- treat buffer pool as circular list of buffer slots
- **NextVictimBuffer** (NVB) holds index of next possible evictee
- if **Buf[NVB]** page is pinned or "popular", leave it
  - **usage\_count** implements "popularity/recency" measure
  - incremented on each access to buffer (up to small limit)
  - decremented each time considered for eviction
- else if **pin\_count** = 0 and **usage\_count** = 0 then grab this buffer
- increment **NextVictimBuffer** and try again (wrap at end)

## ❖ Clock-sweep Replacement Strategy (cont)

Action of clock-sweep:

	NVB					
	[0]	[1]	[2]	[3]	[4]	[5]
Before Clock Sweep	pin: 1 use: 3	pin: 0 use: 1	pin: 0 use: 2	pin: 0 use: 0	pin: 1 use: 1	pin: 1 use: 2

	NVB					
	[0]	[1]	[2]	[3]	[4]	[5]
After Clock Sweep	pin: 1 use: 2	pin: 0 use: 0	pin: 0 use: 1	pin: 1 use: 0	pin: 1 use: 1	pin: 1 use: 2



## ❖ Clock-sweep Replacement Strategy (cont)

---

For specialised kinds of access (e.g. sequential scan),

- clock-sweep is not the best replacement strategy
- can allocate a private "buffer ring"
- use this buffer ring with alternative replacement strategy

Produced: 22 Feb 2021