

Lab-3

James Holdaway

Question 1

When performing a pull after cloning a repo you will get this return “Already up to date” because there is nothing new in the repo to pull. The only new files and information are locally on your machine.

Question 2

`install.packages()` should be run in the console because it is downloading the package to your device.

Question 3

`library()` should go into the .qmd file because it loads the package for use with our code.

Question 4

No, `palmerpenguins::penguins` does not work initially because the package has not been installed yet.

```
library(palmerpenguins)
```

```
Attaching package: 'palmerpenguins'
```

```
The following objects are masked from 'package:datasets':
```

```
penguins, penguins_raw
```

```
palmerpenguins::penguins
```

```
# A tibble: 344 x 8
  species island bill_length_mm bill_depth_mm flipper_length_mm body_mass_g
  <fct>   <fct>         <dbl>         <dbl>         <int>         <int>
1 Adelie  Torgersen         39.1          18.7          181          3750
2 Adelie  Torgersen         39.5          17.4          186          3800
3 Adelie  Torgersen         40.3           18          195          3250
4 Adelie  Torgersen         NA           NA           NA           NA
5 Adelie  Torgersen         36.7          19.3          193          3450
6 Adelie  Torgersen         39.3          20.6          190          3650
7 Adelie  Torgersen         38.9          17.8          181          3625
8 Adelie  Torgersen         39.2          19.6          195          4675
9 Adelie  Torgersen         34.1          18.1          193          3475
10 Adelie Torgersen         42           20.2          190          4250
# i 334 more rows
# i 2 more variables: sex <fct>, year <int>
```

Now that the package has been loaded the data is accessible.

Question 5

```
palmerpenguins::penguins
```

```
# A tibble: 344 x 8
  species island bill_length_mm bill_depth_mm flipper_length_mm body_mass_g
  <fct>   <fct>         <dbl>         <dbl>         <int>         <int>
1 Adelie  Torgersen         39.1          18.7          181          3750
2 Adelie  Torgersen         39.5          17.4          186          3800
3 Adelie  Torgersen         40.3           18          195          3250
4 Adelie  Torgersen         NA           NA           NA           NA
5 Adelie  Torgersen         36.7          19.3          193          3450
6 Adelie  Torgersen         39.3          20.6          190          3650
7 Adelie  Torgersen         38.9          17.8          181          3625
8 Adelie  Torgersen         39.2          19.6          195          4675
9 Adelie  Torgersen         34.1          18.1          193          3475
10 Adelie Torgersen         42           20.2          190          4250
# i 334 more rows
# i 2 more variables: sex <fct>, year <int>
```

You need to library the package beforehand or R will return something along the lines of “penguin” object not recognized.

Question 6

We can hide warning messages by using the warning chunk option and setting it to false, or you may use the `suppressWarnings(library())` function.

Question 7

You can access the help file for the `arrange` function (`dplyr`) by entering `?arrange` into the console. This function orders the rows of a data frame by the values of selected columns.

Question 8

The screenshot displays a Git commit history interface. At the top, there's a navigation bar with 'Changes' and 'History' tabs, and a search bar. Below this is a table of commits:

Subject	Author	Date (UTC)	SHA
0a7f087fddda2e2ace5b321d029b900ed0c195d0 Copied repo and set up necessary files	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	0a7f087f
ff6b5234e0ab084c952fce077f8067448349d4e5 Filled out all questions except for 8.	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	ff6b5234
origin/main origin/HEAD Initial commit	James Holdaway <jdholdaw@ncsu.edu>	2026-09-15	ca628d44

Below the table, there's a section for the selected commit (SHA: 0a7f087fddda2e2ace5b321d029b900ed0c195d0). It shows the commit message 'Copied repo and set up necessary files' and the parent commit (ff6b5234e0ab084c952fce077f8067448349d4e5). Below this, there's a section for the files changed, showing the .gitignore and Lab-3.Rproj files. The .gitignore file contains the following content:

```
@@ -0,0 +1,4 @@
1 .Rproj.user
2 .Rhistory
3 .RData
4 .Ruserdata
```

The Lab-3.Rproj file contains the following content:

```
@@ -0,0 +1,13 @@
1 Version: 1.0
2
3 RestoreWorkspace: Default
4 SaveWorkspace: Default
5 AlwaysSaveHistory: Default
6
7 EnableCodeIndexing: Yes
8 UseSpacesForTab: Yes
9 NumSpacesForTab: 2
10 Encoding: UTF-8
11
12 RnwWeave: Sweave
13 LaTeX: pdfLaTeX
```

Figure 1: Here is my commit history before this message.