

Lab-3

James Holdaway

Question 1

When performing a pull after cloning a repo you will get this return “Already up to date” because there is nothing new in the repo to pull. The only new files and information are locally on your machine.

Question 2

`install.packages()` should be run in the console because it is downloading the package to your device.

Question 3

`library()` should go into the `.qmd` file because it loads the package for use with our code.

Question 4

No, `palmerpenguins::penguins` does not work initially because the package has not been installed yet.

```
palmerpenguins::penguins
```

Question 5

```
library(palmerpenguins)
```

Attaching package: 'palmerpenguins'

The following objects are masked from 'package:datasets':

```
penguins, penguins_raw
```

```
palmerpenguins::penguins
```

```
# A tibble: 344 x 8
  species island bill_length_mm bill_depth_mm flipper_length_mm body_mass_g
  <fct>   <fct>         <dbl>         <dbl>             <int>         <int>
1 Adelie Torgersen      39.1           18.7             181          3750
2 Adelie Torgersen      39.5           17.4             186          3800
3 Adelie Torgersen      40.3           18              195          3250
4 Adelie Torgersen      NA              NA              NA           NA
5 Adelie Torgersen      36.7           19.3             193          3450
6 Adelie Torgersen      39.3           20.6             190          3650
7 Adelie Torgersen      38.9           17.8             181          3625
8 Adelie Torgersen      39.2           19.6             195          4675
9 Adelie Torgersen      34.1           18.1             193          3475
10 Adelie Torgersen      42            20.2             190          4250
# i 334 more rows
# i 2 more variables: sex <fct>, year <int>
```

You need to library the package beforehand or R will return something along the lines of “penguin” object not recognized. If there was a library call for it earlier in the code than it would have printed.

Question 6

We can hide warning messages by using the warning chunk option and setting it to false, or you may use the `suppressWarnings(library())` function.

```
suppressWarnings(library(dplyr))
```

Question 7

You can access the help file for the arrange function (dplyr) by entering `?arrange` into the console. This function orders the rows of a data frame by the values of selected columns.

```
library(dplyr)
iris2 <- arrange(iris, Petal.Length)
head(iris2)
```

	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
1	4.6	3.6	1.0	0.2	setosa
2	4.3	3.0	1.1	0.1	setosa
3	5.8	4.0	1.2	0.2	setosa
4	5.0	3.2	1.2	0.2	setosa
5	4.7	3.2	1.3	0.2	setosa
6	5.4	3.9	1.3	0.4	setosa

Question 8

Changes History (all commits)

Search

Pull

Subject	Author	Date (UTC)	SHA
origin/main origin/HEAD: update rendering with hidden warning	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	e321cd1f
Debug suppresswarnings	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	45552cf7
Updated rendering + iris2	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	ee38e0bf
Adjusted file path for images to match instructions	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	e165ea6f
Switched format from HTML to PDF and adding lab-3.pdf	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	01de428a
Finalized and ready to be turned in as pdf	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	fd277068
All content in	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	c9a94996

Commits 1-10 of 10

SHA

fd27706878cc298575590e14d8467716c1172441

Author

JamesDHoldaway <jdholdaw@ncsu.edu>

Date (UTC)

2026-09-15 21:12

Subject

Finalized and ready to be turned in as pdf

Parent

c9a949966713a28630df455e7534639e6b3d698

Lab-3.qmd

View file @ fd277068

@@ -8,15 +8,13 @@ editor: visual

8 8 ---

9 9

10 10 ## Question 1

11

12 "Already up to date" because there is nothing new in the repo to pull. The only new files and file updates are on my device currently.

11 When performing a pull after cloning a repo you will get this return "Already up to date" because there is nothing new in the repo to pull. The only new files and information are locally on your machine.

13 12

14 13 ## Question 2

15

16 install.packages() should be ran in the console because it is downloading the package to your device.

14 install.packages() should be run in the console because it is downloading the package to your device.

17 15

18 16 ## Question 3

19 library() should go in the .qmd file because it loads the package for use with our code.

17 library() should go into the .qmd file because it loads the package for use with our code.

20 18

21 19 ## Question 4

22 20 No, palmerpenguins::penguins does not work initially because the package has not been installed yet.

26 24

27 25 palmerpenguins::penguins

28 26

27 Now that the package has been loaded the data is accessible.

29 28

30 29 ## Question 5

31 30 ```{r}

Figure 1: Here is my commit history before this message.