

Lab-3

James Holdaway

Question 1

When performing a pull after cloning a repo you will get this return “Already up to date” because there is nothing new in the repo to pull. The only new files and information are locally on your machine.

Question 2

`install.packages()` should be run in the console because it is downloading the package to your device.

Question 3

`library()` should go into the `.qmd` file because it loads the package for use with our code.

Question 4

No, `palmerpenguins::penguins` does not work initially because the package has not been installed yet.

```
palmerpenguins::penguins
```

Question 5

```
library(palmerpenguins)
```

Attaching package: 'palmerpenguins'

The following objects are masked from 'package:datasets':

```
penguins, penguins_raw
```

```
palmerpenguins::penguins
```

```
# A tibble: 344 x 8
  species island bill_length_mm bill_depth_mm flipper_length_mm body_mass_g
  <fct>   <fct>         <dbl>         <dbl>             <int>         <int>
1 Adelie Torgersen      39.1           18.7             181          3750
2 Adelie Torgersen      39.5           17.4             186          3800
3 Adelie Torgersen      40.3            18             195          3250
4 Adelie Torgersen      NA            NA              NA           NA
5 Adelie Torgersen      36.7           19.3             193          3450
6 Adelie Torgersen      39.3           20.6             190          3650
7 Adelie Torgersen      38.9           17.8             181          3625
8 Adelie Torgersen      39.2           19.6             195          4675
9 Adelie Torgersen      34.1           18.1             193          3475
10 Adelie Torgersen      42            20.2             190          4250
# i 334 more rows
# i 2 more variables: sex <fct>, year <int>
```

You need to library the package beforehand or R will return something along the lines of “penguin” object not recognized. If there was a library call for it earlier in the code than it would have printed.

Question 6

We can hide warning messages by using the warning chunk option and setting it to false, or you may use the `suppressWarnings(library())` function.

```
suppressWarnings(library(dplyr))
```

Question 7

You can access the help file for the arrange function (dplyr) by entering `?arrange` into the console. This function orders the rows of a data frame by the values of selected columns.

```
library(dplyr)
iris2 <- arrange(iris, Petal.Length)
head(iris2)
```

	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width	Species
1	4.6	3.6	1.0	0.2	setosa
2	4.3	3.0	1.1	0.1	setosa
3	5.8	4.0	1.2	0.2	setosa
4	5.0	3.2	1.2	0.2	setosa
5	4.7	3.2	1.3	0.2	setosa
6	5.4	3.9	1.3	0.4	setosa

Question 8

The screenshot displays a Git commit history table and a file diff view. The commit history table shows three commits, with the first commit highlighted. The file diff view shows the changes made in the selected commit, including the .gitignore file and the Lab-3.Rproj file.

Subject	Author	Date (UTC)	SHA
HEAD --> main/HEAD (main) Copied repo and set up necessary files	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	0a7f087f
Filled out all questions except for 8.	JamesDHoldaway <jdholdaw@ncsu.edu>	2026-09-15	ff6b5234
origin/main origin/HEAD Initial commit	James Holdaway <jdholdaw@ncsu.edu>	2026-09-15	ca628d44

SHA 0a7f087f0dda2e2ace5b321d029b900ed0c195d0
Author JamesDHoldaway <jdholdaw@ncsu.edu>
Date (UTC) 2026-09-15 21:00
Subject Copied repo and set up necessary files
Parent ff6b5234e0ab084c952fce077f8067448349d4e5

.gitignore
Lab-3.Rproj

@@ -0,0 +1,4 @@
1 .Rproj.user
2 .Rhistory
3 .RData
4 .Ruserdata

Lab-3.Rproj
@@ -0,0 +1,13 @@
1 Version: 1.0
2
3 RestoreWorkspace: Default
4 SaveWorkspace: Default
5 AlwaysSaveHistory: Default
6
7 EnableCodeIndexing: Yes
8 UseSpacesForTab: Yes
9 NumSpacesForTab: 2
10 Encoding: UTF-8
11
12 RnwWeave: Sweave
13 LaTeX: pdfLaTeX

Figure 1: Here is my commit history before this message.