

Models for Longitudinal Data

Contents

1	Getting Set Up	1
1.1	Setting chunk options and generating R script	1
1.2	Installing Packages	2
1.3	Reading in the data	2
1.4	Exploring the data	2
2	Linear Regression Per Person	7
2.1	Linear regression of cog on age per participant.	8
3	Linear regression per person and group	9
4	Fitting the Model	10
4.1	Installing the Packages	10
4.2	Estimating the fixed effects via bootstrap	11
4.3	Calculating confidence intervals for the fixed effects via Wald, bootstrap and profile likelihood	12
4.4	Get the KR-approximated degrees of freedom	13
4.5	Likelihood ratio tests	13
4.6	Random effects covariance matrix	13
4.7	Predicted random effects	13

1 Getting Set Up

1.1 Setting chunk options and generating R script

```
knitr::opts_chunk$set(warning=FALSE, message=FALSE)
knitr::purl("longitudinal-models.Rmd")
```

```
##
##
## processing file: longitudinal-models.Rmd

## output file: longitudinal-models.R
```

1.2 Installing Packages

```
install.packages('lattice')  
library('lattice')
```


1.3 Reading in the data

```
early.int1 = read.table("earlyint.txt", header=T, sep=",")  
attach(early.int1)
```

1.4 Exploring the data

Spaghetti plot.

```
n = length(unique(id))  
interaction.plot(age, id, cog, xlab="Age in years", ylab="IQ", legend=F)
```




Descriptives.

```
early.mean=tapply(cog,list(age,program),mean) #mean  
early.sd=tapply(cog,list(age,program),sd) #sd  
early.var=tapply(cog,list(age,program),var) #variance  
early.n=table(age,program) #frequency
```


Boxplots.

```
boxplot(cog~age, xlab="Age (in years)", ylab="IQ")
```



Boxplots per program.

```
par(mfrow=c(2,1))
boxplot(cog[program==0]~age[program==0], main="No intervention", xlab="Age (in years)", ylab="IQ")
boxplot(cog[program==1]~age[program==1], main="Intervention", xlab="Age (in years)", ylab="IQ")
```



General function to plot error bars.


```
errbar=function(x,y,height,width,lty=1,col="black"){
  arrows(x,y,x,y+height,angle=90,length=width,lty=lty, col=col)
  arrows(x,y,x,y-height,angle=90,length=width,lty=lty, col=col)
}
```

Plotting mean evolutions.

```
plot(age[id==1],early.mean[,1],type="b",xlim=c(1,2), ylim=c(40,160),xlab="Age (in years)",ylab="IQ",axes=FALSE)
axis(side=1,at=c(1,1.5,2),labels=c(1,1.5,2))
axis(side=2,at=seq(40,160,20))

box()
points(age[id==1],early.mean[,2],type="b",col="red")
errbar(age[id==1]-.005,early.mean[,1],early.sd[,1],.1)
errbar(age[id==1]+.005,early.mean[,2],early.sd[,2],.1,col="red")
```

Mean evolution (with 1 SE intervals)



Correlation between IQ scores at different ages.

```
early.int2 <- reshape(early.int1, timevar = "age", idvar = c("id", "program"), direction = "wide") # re
early.int2
```

##	id	program	cog.1	cog.1.5	cog.2
## 1	1	1	106.98289	98.31060	92.91342
## 2	2	1	108.86019	100.29307	85.29502
## 3	3	1	112.52438	96.76684	83.42649
## 4	4	1	90.24428	85.27380	76.41052
## 5	5	1	105.70738	102.39839	88.78872
## 6	6	1	93.88987	85.09601	76.66209
## 7	7	1	109.93899	109.43202	86.68573
## 8	8	1	106.98599	106.09735	105.92056
## 9	9	1	125.33166	114.01277	105.12163
## 10	10	1	82.49028	97.76043	100.77653
## 11	11	1	105.22740	113.77558	108.48978
## 12	12	1	114.49240	117.93460	122.02861
## 13	13	1	91.73435	86.60655	82.18117
## 14	14	1	95.37839	79.56730	82.49799
## 15	15	1	110.07345	108.65272	87.65045
## 16	16	1	98.01933	94.54154	76.07024
## 17	17	1	87.96931	87.25195	98.98177
## 18	18	1	108.31917	100.51574	98.70037
## 19	19	1	94.18916	74.64264	73.31470
## 20	20	1	120.16253	103.18718	90.92738

## 21	21	1	131.65178	114.16135	95.58954
## 22	22	1	120.85608	98.18288	96.44816
## 23	23	1	116.02689	114.82364	109.35596
## 24	24	1	108.50925	90.67410	95.33989
## 25	25	1	112.12633	116.82108	116.59443
## 26	26	1	80.83364	99.37240	84.50895
## 27	27	1	87.42831	91.92213	93.23212
## 28	28	1	112.40877	91.41400	103.47415
## 29	29	1	123.16009	117.85460	114.91998
## 30	30	1	91.50417	100.18023	77.07159
## 31	31	1	98.81854	92.73035	107.11404
## 32	32	1	102.57830	120.27905	98.31582
## 33	33	1	92.71612	113.93789	79.24296
## 34	34	1	113.13320	100.72077	103.26529
## 35	35	1	83.36287	83.36361	79.02352
## 36	36	1	94.91031	85.72218	78.16092
## 37	37	1	99.20004	108.88909	105.20391
## 38	38	1	109.00945	106.33822	102.16497
## 39	39	1	88.83725	95.32658	105.52882
## 40	40	1	97.11882	85.45274	78.42828
## 41	41	1	97.34675	108.54913	78.15538
## 42	42	1	108.46227	115.06198	105.33598
## 43	43	1	106.51196	103.23088	72.29365
## 44	44	1	93.55798	96.57147	95.85989
## 45	45	1	96.66016	94.09513	98.27780
## 46	46	1	112.22206	113.36683	90.21796
## 47	47	1	115.75380	105.04866	94.08408
## 48	48	1	92.02678	87.41049	94.53681
## 49	49	1	90.05997	78.94745	88.01800
## 50	50	1	118.84066	97.71249	93.61212
## 51	51	1	100.83136	86.38944	98.09643
## 52	52	1	101.98162	108.36219	84.64359
## 53	53	1	113.60019	107.96398	106.56405
## 54	54	1	87.24872	78.63402	105.24226
## 55	55	1	89.91285	105.28723	71.47761
## 56	56	1	97.17166	96.15962	93.83076
## 57	57	1	98.54182	73.69470	94.72776
## 58	58	1	116.51412	105.63534	82.82452
## 59	59	0	124.94527	111.91136	91.24352
## 60	60	0	71.84974	81.08563	83.02724
## 61	61	0	88.45453	79.30242	77.91012
## 62	62	0	101.81687	77.26865	82.05273
## 63	63	0	98.83434	94.90388	90.39131
## 64	64	0	106.62630	111.48140	83.56083
## 65	65	0	90.31671	91.30650	81.15678
## 66	66	0	95.55040	95.36279	94.99702
## 67	67	0	110.57535	97.77947	86.48163
## 68	68	0	95.73969	89.27407	92.22706
## 69	69	0	108.46676	108.50177	81.96456
## 70	70	0	109.57738	89.10167	76.92818
## 71	71	0	114.42217	105.91386	93.90563
## 72	72	0	96.37015	99.40169	90.07637
## 73	73	0	104.56600	109.48258	111.65059
## 74	74	0	99.27624	81.42511	96.03642

```
## 75 75 0 121.96798 97.03722 98.80731
## 76 76 0 110.88300 104.57459 101.48922
## 77 77 0 95.49981 92.58608 89.33631
## 78 78 0 96.03821 86.79500 72.39639
## 79 79 0 115.28714 123.02920 98.05151
## 80 80 0 89.25232 89.57222 91.68889
## 81 81 0 119.21283 99.67131 93.03702
## 82 82 0 98.68876 98.57612 92.32044
## 83 83 0 108.50237 90.58188 80.04558
## 84 84 0 97.63610 95.12270 90.99789
## 85 85 0 98.82146 101.36631 80.64234
## 86 86 0 109.60582 96.96958 81.04709
## 87 87 0 95.09582 106.02006 99.58778
## 88 88 0 98.22010 88.72318 74.19584
## 89 89 0 94.03053 100.83250 89.57231
## 90 90 0 95.94445 91.09095 72.61159
## 91 91 0 104.79640 85.71041 96.40972
## 92 92 0 97.79446 98.93178 88.80250
## 93 93 0 113.70390 95.20994 74.17274
## 94 94 0 111.78680 100.19471 91.77763
## 95 95 0 115.63780 111.71134 92.56601
## 96 96 0 113.99454 109.34016 97.01341
## 97 97 0 129.27171 122.23883 96.33804
## 98 98 0 99.92436 77.48019 70.84332
## 99 99 0 101.59745 93.78219 72.94243
## 100 100 0 119.40051 97.75317 84.70497
## 101 101 0 109.84539 122.96455 91.49998
## 102 102 0 93.98954 72.58405 82.19806
## 103 103 0 103.16078 86.94306 86.77639
```

```
cor(early.int2[,3:5])
```

```
##          cog.1  cog.1.5  cog.2
## cog.1  1.0000000 0.5816070 0.3263912
## cog.1.5 0.5816070 1.0000000 0.4371109
## cog.2  0.3263912 0.4371109 1.0000000
```

2 Linear Regression Per Person


Creating the time variable.

```
early.int1$age0<-early.int1$age-1
```

Displaying the linear regression per person.

```
cf = sapply(early.int1$id, function(x) coef(lm(cog~age0, data=subset(early.int1, id==x))))
Sx<-reorder(early.int1$id, cf[1,])

xyplot(cog ~ age0|Sx, groups=program, data=early.int1, type=c('p','r'), auto.key=T, aspect="xy", par.set
)
```



2.1 Linear regression of cog on age per participant.

Coefficients.


```
lin.reg.coef = by(early.int1, early.int1$id, function(data) coef(lm(cog ~ age0, data=data)))
lin.reg.coef1 = unlist(lin.reg.coef)
names(lin.reg.coef1) = NULL
lin.reg.coef2 = matrix(lin.reg.coef1, length(lin.reg.coef1)/2, 2, byrow = TRUE)
```

R-Squared.

```
lin.reg.r.squared = by(early.int1, early.int1$id, function(data) summary(lm(cog ~ age, data=data))$r.squared)
lin.reg.r.squared1 = as.vector(unlist(lin.reg.r.squared))
```

Histograms.

```
par(mfrow=c(3,1))
hist(lin.reg.coef2[,1], xlab="Intercept", col="lightblue", main="Histogram of individual intercepts")
hist(lin.reg.coef2[,2], xlab="Slope", col="lightblue", main="Histogram of individual slopes")
hist(lin.reg.r.squared1, xlab="R squared", col="lightblue", main="Histogram of individual R squared")
```

3 Linear regression per person and group

Plotting individual regression lines per group.

```
reg.coef = cbind(lin.reg.coef2, early.int1[early.int1$age==1,]$program)
mean.int = tapply(reg.coef[,1], reg.coef[,3], mean)
mean.slope = tapply(reg.coef[,2], reg.coef[,3], mean)

par(mfrow=c(1,2))
plot(age, cog, type="n", xlim=c(1,2), ylim=c(40,160), main="No intervention", xlab="Age-1 (in years)", ylab="Cognitive score",
axis(side=1, at=c(1,1.5,2), labels=c(1,1.5,2))
axis(side=2, at=seq(40,160,20))
box()

for (i in 1:103) {
  if (reg.coef[i,3]==0){
    curve(cbind(1,x)%*%reg.coef[i,1:2], add=T, col="gray")
    curve(cbind(1,x)%*%c(mean.int[1], mean.slope[1]), add=T, lwd=2)
  }
}


plot(age, cog, type="n", xlim=c(1,2), ylim=c(40,160), main="Intervention", xlab="Age-1 (in years)", ylab="Cognitive score",
axis(side=1, at=c(1,1.5,2), labels=c(1,1.5,2))
axis(side=2, at=seq(40,160,20))
```

```

box()

for (i in 1:103){
  if (reg.coef[i,3]==1){
    curve(cbind(1,x)%*%reg.coef[i,1:2], add=T, col="gray")
    curve(cbind(1,x)%*%c(mean.int[2], mean.slope[2]), add=T, lwd=2)
  }
}

```



4 Fitting the Model

4.1 Installing the Packages

```

install.packages("lme4")
install.packages("arm")
install.packages("pbkrtest")

library(lme4)
library(lattice)
library(arm)
library(car)
library(pbkrtest)

```

Creating the time variable.

```
early.int1$age0<-early.int1$age-1
```

Fitting the model with maximum likelihood.

```
early.lmer1 = lmer(cog~1+age0*program+(1 + age0|id), REML = FALSE, data=early.int1)
summary(early.lmer1)
```

```
## Linear mixed model fit by maximum likelihood ['lmerMod']
## Formula: cog ~ 1 + age0 * program + (1 + age0 | id)
## Data: early.int1
##
##      AIC      BIC    logLik deviance df.resid
## 2332.5    2362.4   -1158.3   2316.5     301
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -2.25362 -0.59088  0.02131  0.56850  2.29366
##
## Random effects:
## Groups Name Variance Std.Dev. Corr
## id      (Intercept) 84.02   9.166
##      age0      39.44   6.281   -0.55
## Residual      60.31   7.766
## Number of obs: 309, groups: id, 103
##
## Fixed effects:
##              Estimate Std. Error t value
## (Intercept)  104.3007    1.7274   60.380
## age0         -16.2555    1.8860   -8.619
## program       -0.9646    2.3020   -0.419
## age0:program    6.3187    2.5133    2.514
##
## Correlation of Fixed Effects:
##              (Intr) age0  progrm
## age0         -0.629
## program      -0.750  0.472
## age0:progrm   0.472 -0.750 -0.629
```

4.2 Estimating the fixed effects via bootstrap

```
fixed.boot = bootMer(early.lmer1, fixef, use.u = TRUE, nsim = 250)
fixed.boot
```

```
##
## PARAMETRIC BOOTSTRAP
##
## Call:
## bootMer(x = early.lmer1, FUN = fixef, nsim = 250, use.u = TRUE)
```

```
##
##
## Bootstrap Statistics :
##      original      bias    std. error
## t1* 104.3007437  0.01424596   1.025219
## t2* -16.2554565 -0.07347919   1.606066
## t3*  -0.9646326  0.03266867   1.431340
## t4*   6.3187112  0.09511476   2.274090
```

```
summary(fixed.boot)
```

```
##
## Number of bootstrap replications R = 250
##      original  bootBias bootSE  bootMed
## (Intercept)  104.30074  0.014246 1.0252 104.28389
## age0         -16.25546 -0.073479 1.6061 -16.31605
## program      -0.96463  0.032669 1.4313  -0.99671
## age0:program   6.31871  0.095115 2.2741   6.50525
```

4.3 Calculating confidence intervals for the fixed effects via Wald, bootstrap and profile likelihood

```
confint(early.lmer1,par=5:8,method="Wald",oldNames = FALSE) # Only for fixed effects vc will return NA
```

```
##           2.5 %      97.5 %
## (Intercept) 100.915097 107.686391
## age0        -19.951912 -12.559002
## program     -5.476396   3.547131
## age0:program  1.392761  11.244662
```

```
confint(early.lmer1,method="boot",boot.type="perc",oldNames = FALSE,nsim=500)
```

```
##           2.5 %      97.5 %
## sd_(Intercept)|id      6.6248377 11.1720202
## cor_age0.(Intercept)|id -1.0000000  0.9999961
## sd_age0|id             0.8700550  9.9647573
## sigma                 6.6032140  8.6957184
## (Intercept)          100.7225482 107.7892045
## age0                 -19.9596571 -12.6528151
## program              -5.4528343  3.9271159
## age0:program          0.8768822 11.1150900
```

```
confint(early.lmer1, level = 0.95,method="profile",oldNames = FALSE)
```

```
##           2.5 %      97.5 %
## sd_(Intercept)|id      7.005366 11.406182
## cor_age0.(Intercept)|id -1.000000  1.000000
## sd_age0|id             0.000000  9.975354
## sigma                 6.814978  8.953288
```

```
## (Intercept)          100.883287 107.718200
## age0                 -19.986640 -12.524273
## program              -5.518786   3.589521
## age0:program          1.346481  11.290942
```

4.4 Get the KR-approximated degrees of freedom

```
#early.lmer1.df.KR = get_ddf_Lb(early.lmer1, fixef(early.lmer1))
```

4.5 Likelihood ratio tests

```
early.lmer1.noprogram<-lmer(cog~1+age0+(1 + age0|id), REML = FALSE, data=early.int1)
early.lmer1.intprog<-lmer(cog~1+age0+program+(1 + age0|id), REML = FALSE, data=early.int1)
anova(early.lmer1.noprogram,early.lmer1.intprog,early.lmer1)
```

```
## Data: early.int1
## Models:
## early.lmer1.noprogram: cog ~ 1 + age0 + (1 + age0 | id)
## early.lmer1.intprog: cog ~ 1 + age0 + program + (1 + age0 | id)
## early.lmer1: cog ~ 1 + age0 * program + (1 + age0 | id)
##
```

	npar	AIC	BIC	logLik	deviance	Chisq	Df	Pr(>Chisq)
## early.lmer1.noprogram	6	2336.8	2359.2	-1162.4	2324.8			
## early.lmer1.intprog	7	2336.7	2362.8	-1161.3	2322.7	2.0840	1	0.14885
## early.lmer1	8	2332.5	2362.4	-1158.3	2316.5	6.1345	1	0.01326 *

```
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

4.6 Random effects covariance matrix

```
D.early = unclass(VarCorr(early.lmer1))$id
D.early
```


```
##          (Intercept)          age0
## (Intercept)  84.01946 -31.89378
## age0        -31.89378  39.44496
## attr(,"stddev")
## (Intercept)          age0
##  9.166213   6.280522
## attr(,"correlation")
##          (Intercept)          age0
## (Intercept)  1.0000000 -0.5540135
## age0        -0.5540135  1.0000000
```

4.7 Predicted random effects

```
early.lmer1.re = ranef(early.lmer1)$id
head(early.lmer1.re,10)
```

```
##      (Intercept)      age0
## 1      1.406085 -1.0998501
## 2      1.700819 -3.2167576
## 3      1.996405 -4.4674896
## 4     -11.103349  0.6994181
## 5      1.444739 -1.7280748
## 6     -9.633038 -0.2479249
## 7      4.787570 -3.5798370
## 8      5.221722  1.2096924
## 9     14.723774 -4.3028253
## 10     -7.682855  7.2428573
```

```
plot(early.lmer1.re, main="Random intercept (b0i) versus random slope (b1i)")
```



OLS vs LM Estimates ## Creating the subject specific intercepts and slopes

```
ind.coef=coef(early.lmer1)$id
head(ind.coef)
```

```
##      (Intercept)      age0      program age0:program
## 1      105.70683 -17.35531 -0.9646326      6.318711
```

```
## 2  106.00156 -19.47221 -0.9646326    6.318711
## 3  106.29715 -20.72295 -0.9646326    6.318711
## 4   93.19739 -15.55604 -0.9646326    6.318711
## 5  105.74548 -17.98353 -0.9646326    6.318711
## 6   94.66771 -16.50338 -0.9646326    6.318711
```

```
int.subject=ind.coef[,1]+ind.coef[,3]
slope.subject=ind.coef[,2]+ind.coef[,4]
plot(int.subject,slope.subject, main="Random intercept versus random slope (Including the fixed effects)
```

Random intercept versus random slope (Including the fixed effects)

