Extending AI-Agent Incident Analysis to Multi-Agent Systems

AFACS, an HFACS-based framework, and an audit of public traces

James Le Cuirot
Senior First Officer and Flight Safety Officer · MSc Human Factors in Aviation

Draft, 3 November 2026

Abstract

Ezell, Roberts-Gaal and Chan (2025) proposed a framework for analysing incidents involving AI agents, with system factors, contextual factors and cognitive errors, and listed open challenges for future work. Their framework treats single agents, has no category for deliberate departures from known requirements, and has not been applied to real traces. This report extends it to multi-agent systems using the structure of the Human Factors Analysis and Classification System (HFACS) from aviation. The extension, AFACS, adds a supervision and orchestration tier, a coordination category analogous to crew resource management, and violations coded from behaviour with a graded statement of the evidence (stated, inferred or thin); it also proposes a model-development code that HFACS lacks. A cross-walk maps each of Ezell et al.'s factors onto the AFACS layers. The framework is then tested against the public MAST dataset of multi-agent traces. An audit of that dataset finds that its 1,642 rows hold 1,537 distinct traces, that one group of 100 rows contains only 30 distinct texts with unrelated labels, and that MAST's LLM judge agrees with itself at a mean per-mode Cohen's κ of 0.43 on 30 traces it labelled twice. Audited against the eighteen kinds of information Ezell et al. say investigators need, every framework's logs record what the agents said and did, but none includes the system documentation, artefacts or access needed to reconstruct a failure; sampling settings are logged by one framework and seeds by none, and the only logged model identifier contradicts MAST's metadata for one group of 30 traces. *[Pending: AI pilot: consistency of AFACS coding between models and between runs, and the prevalence of supervision, coordination and violation codes]*.

1 Introduction

When an aircraft accident is investigated, "pilot error" is where the analysis starts. Reason's model of organisational accidents describes how the unsafe act at the sharp end is made likely by latent conditions created earlier and higher up: preconditions in the immediate situation, supervision, and organisational decisions [1, 2]. The Human Factors Analysis and Classification System (HFACS) turned that model into a coding scheme with four tiers, from organisational influences down to unsafe acts [3, 4]. HFACS also keeps Reason's distinction between errors, which are unintended (slips, lapses and mistakes), and violations, which are departures from known rules. The two call for different remedies, and survey evidence suggests they are different kinds of behaviour with different correlates [5].

LLM agents are language models that act over many steps: they plan, call tools, write and run code, and exchange messages. A multi-agent system assigns several such agents roles, such as coder, tester and orchestrator, much as a crew divides duties. Ezell, Roberts-Gaal and Chan [6] have proposed the first framework for analysing incidents involving AI agents in this tradition. It explains incidents through three categories of factor, system factors, contextual factors and cognitive errors, linked in a causal chain, and it sets out what information investigators need to tell them apart. Its authors close with a table of open challenges for future work.

Three features of that framework leave room for extension. It treats a single agent, so it has no place for an orchestrator that supervises other agents, nor for breakdowns between agents. Its agent-level category contains errors only: the paper cites an agent that reasoned about cheating its unit tests before doing so [7], but no category records a deliberate departure from a known requirement. And it is conceptual: it has not been applied to real traces.

This report extends the framework to multi-agent systems using the structure of HFACS, and calls the result AFACS. It takes up five of the thirteen open challenges in Ezell et al.'s Appendix B: *non-exhaustive*

coverage, since multi-agent systems are a domain whose specific factors their taxonomy does not cover; *emerging factors*, by adding violations for the departures they mention but do not categorise; *high-level cognitive errors*, by testing their error categories against HFACS's on real traces; *reconstruction difficulties* and the related problem of *limited data access*, by auditing what openly released logs allow an investigator to reconstruct; and, in part, *expertise shortages*, through a codebook with explicit decision rules and a test of whether AI-assisted coding is consistent. Their remaining challenges (reporting infrastructure, accountability mechanisms, sensitive data, the legal landscape, data retention and voluntary adoption) are institutional and outside the scope of a trace study.

The study uses the public MAST dataset of multi-agent traces [8] and asks four research questions.

- **RQ1, cross-walk.** How do Ezell et al.'s factors map onto the HFACS layers, and what does a multi-agent setting add?
- **RQ2, information adequacy.** Do real multi-agent traces contain the information Ezell et al. say investigators need?
- **RQ3, applicability.** Can the extended framework be applied consistently, and how often do failures involve the added supervision, coordination and violation categories?
- **RQ4, flat labels.** How do MAST's fourteen flat labels map onto the extended framework?

The contributions are: (i) AFACS, an extension of Ezell et al.'s framework to multi-agent systems with a supervision tier, a coordination category and evidence-graded violations, together with an item-by-item cross-walk; (ii) an audit of the MAST dataset documenting duplicates, corrupt and misfiled rows, logging artefacts and the test–retest reliability of its LLM judge; (iii) an audit of MAST's logs against Ezell et al.'s information requirements, showing what public multi-agent traces do and do not let an investigator establish; and (iv) *[Pending: an AI-coded pilot measuring how consistently the framework can be applied, and what it shows that the flat labels do not]*. Human validation with independent coders is planned as a second study, for which a blinded, pre-registered calibration set has already been frozen.

2 Background and Related Work

2.1 Incident analysis for AI agents

Ezell et al. define three categories of factor [6]. System factors are static aspects of an agent's development: training data, feedback, learning methods, the system prompt and scaffolding code. Contextual factors are features of the situation: the information available, the tools, and how the task was defined. Cognitive errors are failures of observation, understanding, decision-making and action execution, which are the most proximate to the incident but arise because of system and contextual factors. The paper also lists eighteen items of information, in three groups (activity logs, system documentation and access, and tool information), that investigators need in order to decide which factors apply (their Table 1). It acknowledges that its treatment of cognitive errors is "necessarily high-level" because the cognitive science of AI agents is nascent, and that its factors are not exhaustive. Shamsujjoha et al. use the Swiss-cheese idea to design layered runtime guardrails for agents [9], and Mylius applies STPA, a system-theoretic hazard analysis, to a frontier-AI scenario [10, 11]. Both look forward, at defences and hazards. Ezell et al. and AFACS look back, at what happened.

2.2 Agent failure taxonomies

MAST was derived bottom-up from 150 traces and refined over three rounds; its authors report human inter-annotator agreement of $\kappa = 0.88$ in the final round, $\kappa = 0.79$ on systems not seen during development, and $\kappa = 0.77$ between an o1-based LLM annotator and human experts [8]. Its discussion draws on organisational safety research, but the taxonomy itself has no causal layers and no error/violation distinction. Other taxonomies classify errors by type, finding that the best LLM locates only 11% of human-annotated errors [12]; by the component that broke [13]; by the agent and step responsible, where the decisive step is found 14.2% of the time [14]; or by the side that should own the fix, with an LLM judge reaching $\kappa = 0.76$ against human labels [15]. These works answer "what broke" and "who and when". AFACS adds "what kind of act" and "what latent conditions".

2.3 HFACS and its reliability

The closest methodological precedent is Wiegmann and Shappell [16]: an aviation psychologist and a commercially rated pilot independently re-coded 319 causal factors from 119 NTSB accident reports into HFACS and agreed at $\kappa = 0.71$. HFACS reliability is contested. Olsen and Shorrock found low agreement, between and within coders, for a modified HFACS used in air traffic control [17]. A review by Cohen, Wiegmann and Shappell found reliability higher with coder training, larger samples and fewer departures from the original framework [18]; that review drew a published critique [19]. LLMs applied to HFACS coding of aviation reports reach far lower exact-match than partial-match agreement [20]. AFACS therefore keeps the original four tiers, and agreement is reported at layer level as well as code level.

2.4 AI behaviours that resemble violations

Specification gaming, in which a system satisfies the letter of its objective while defeating its purpose, is the standard AI-safety term for many behaviours AFACS would code as exceptional violations [21]. ImpossibleBench builds coding tasks in which passing requires breaking the specification, so any pass cannot be accidental [22]. Baker et al. show that reasoning traces can reveal reward hacking, and that models trained against such monitors learn to hide it [7]. In constructed scenarios, frontier models reason explicitly about the constraints they face and choose to circumvent them [23, 24]. OverclaimBench measures false claims of task completion from transcripts alone, with a criterion that "requires no inference about intent" [25], the same behavioural stance as AFACS. At the aggregate level, Hägele et al. find that failures look less like coherent pursuit of unintended goals and more like an incoherent "hot mess" as tasks lengthen [26], a reminder that most failures are likely to be errors.

3 The AFACS Framework and its Cross-Walk (RQ1)

Each failed trace is coded at every layer where the trace gives evidence (multi-label), with a deepest contributing layer and a confidence rating (high, medium or low). Table 1 lists the layers and codes of codebook v1 (`codebook/v1.md`). The codebook is the author's.

3.1 Cross-walk to Ezell et al.

Table 2 condenses the item-by-item mapping in `docs/crosswalk_ezell.md`. In broad terms, Ezell et al.'s system factors correspond to L4, with the system prompt treated as part of the task specification at L3.4; their contextual factors correspond to L2.1, with task definition at L3.4 and resource limits at L4.2; and their cognitive errors correspond to the L1 errors, with memory limits and distraction treated as agent state at L2.2. Their four cognitive functions cut the same ground as HFACS's three error types differently; RQ3 tests which distinctions can be applied consistently.

The mapping also runs the other way. Ezell et al. name model development as a cause, which HFACS has no tier for; HFACS's nearest category, organisational resource management, covers "human resource management (selection, training, staffing)" [16], and AFACS proposes L4.4 by analogy. They name security-related context (malicious inputs, vulnerable tools), which AFACS treats as sub-cases of L2.1. And their list of information requirements gives a standard against which real logs can be audited (RQ2).

3.2 Violations

"Violation" is used in HFACS's sense, applied to behaviour. An investigator never sees inside a pilot's head either: a violation is inferred from evidence that the rule was known and that the action departed from it. AFACS makes the same inference and makes no claim about intent, will or awareness; whether AI agents have intentions is an open question this framework does not try to answer. A failure is coded as a violation only if all three conditions hold: (1) the requirement was in the agent's accessible context; (2) the trace shows the agent represented it, by referencing or acknowledging it, or the deviation is of a kind that cannot plausibly be accidental, such as hardcoding expected test outputs; and (3) the agent proceeded otherwise. If all three hold but the evidence is thin, the code is `L1.V?`; otherwise the failure is an error. Benchmark information the agents never saw cannot satisfy condition (1).

Table 1: AFACS layers and codes (codebook v1). L4.4 is proposed, added from Ezell et al.'s system factors.

Layer	Code	Description
L4 Organisational / design	L4.1	Architecture and role design: role split, missing verifier, no termination logic
	L4.2	Resource provisioning: tools, step or token budgets, context limits
	L4.3	Process: no standard procedure for verification or handover
	L4.4	Model development (proposed): training data, feedback or learning methods
L3 Supervision / orchestration	L3.1	Inadequate supervision: no check on subagent output
	L3.2	Planned inappropriate operation: task beyond an agent's capability or information
	L3.3	Failure to correct a known problem: visible loop or error, no intervention
	L3.4	Deficient specification: ambiguous, contradictory or incomplete task or prompt
L2 Preconditions	L2.1	Environment: tool or API failure, bad or unavailable information
	L2.2	Agent state: context saturation, lost instructions, carried-over error
	L2.3	Coordination: communication breakdown, withheld or ignored input
L1 Unsafe acts: errors	L1.E1	Skill-based: execution slip, e.g. a malformed tool call
	L1.E2	Decision: wrong plan or choice given adequate information
	L1.E3	Perceptual: misread observation, tool output or message
L1 Unsafe acts: violations	L1.V1	Routine: habitual shortcutting across the trace
	L1.V2	Exceptional: one-off departure, e.g. fabricating a result or editing tests
	L1.V?	Indeterminate: the criteria appear to hold but the evidence is thin

The distinction is recorded because the two call for different remedies. An error (the agent could not comply) is addressed by better tools, clearer tasks, verification or more capable models. A violation (the agent registered the requirement and did otherwise) is not a capability problem; it points to incentives, monitoring and what training rewards. In HFACS, routine violations often have organisational roots, such as pressure or tolerated shortcuts; in an AI agent the corresponding latent condition is often training feedback that rewarded the appearance of success, which AFACS records at L4.4.

Every coding records the basis for any violation (Table 3), so that readers can see how strong the evidence is and apply their own view on intent. Stated reasoning is evidence, not proof: a model's written reasoning may not reflect what produced its action, and models trained against monitors can learn to hide it [7]. The absence of incriminating reasoning is therefore no proof of an honest error, which is why the *inferred* grade exists.

3.3 Incidents and failures

Ezell et al. analyse incidents: events that cause or could plausibly cause harm. MAST's traces are failed benchmark tasks in which nobody was harmed. Aviation draws the same line and applies the same causal analysis to both: occurrence reporting covers events where no harm resulted, because their causes are the causes of future accidents. AFACS is applied here to failures on that basis.

4 Data and Audit

The data are MAST's public release (`mcemri/MAST-Data`, revision `95118ac`, licence CC-BY-4.0): 1,642 traces from seven multi-agent frameworks (AG2, MetaGPT, ChatDev, Magentic-One, AppWorld, HyperAgent and OpenManus), eight benchmarks and five LLMs. Each record holds one raw log and 14 binary MAST labels assigned by an LLM judge; the authors' released pipeline uses OpenAI's o1 and truncates traces longer than about one million characters before judging. Before building on the labels, the dataset was audited (`docs/data_audit.md`). Table 4 summarises the exclusions.

Table 2: Condensed cross-walk from Ezell et al.'s factors to AFACS codes. The last three rows have no counterpart in Ezell et al.

Ezell et al. factor	AFACS code	Note
System: training data, feedback, learning methods	L4.4 (proposed)	Latent; feedback that rewards appearing successful is a typical condition behind violations
System: system prompt underspecified or encouraging undesirable behaviour	L3.4	System prompt treated as part of the specification
System: scaffolding not working as intended	L4.1 or L2.1	Design flaw or run-time failure (open question)
Contextual: information inaccessible, missing, poor or malicious	L2.1	
Contextual: tools unusable or failing; tool errors not visible	L2.1 or L4.2	Run-time failure, or provisioning by design
Contextual: unclear or conflicting task; resource limits	L3.4; L4.2	
Cognitive: observation (failure to notice, wrong expectation)	L1.E3	Memory capacity at L2.2
Cognitive: understanding (misinterpretation; conclusions from poor information)	L1.E3; L1.E2	With L2.1 where the information was poor
Cognitive: decision-making (goal priority, non-viable plans, criteria)	L1.E2	Distraction from the goal at L2.2
Cognitive: action execution (incorrect execution; no action; no error monitoring)	L1.E1; L1.E1/E2; L1.E3 or L3.3	L3.3 where a supervising agent should have caught it
(none: single-agent framework)	L3.1–L3.3	Orchestrator fails to check, assigns beyond capability, or leaves a visible problem uncorrected
(none)	L2.3	Coordination between agents, the crew resource management analogue
(mentioned, not categorised)	L1.V1, L1.V2, L1.V?	Violations with an evidence grade (Section 3.2)

Table 3: Evidence grades for violations (codebook v1, field `violation_evidence`).

Grade	Use when	Goes with
stated	The agent's own words (reasoning, plan or message) acknowledge the requirement, and it then departs from it	L1.V1, L1.V2
inferred	Nothing in the agent's words shows it registered the requirement, but the act cannot plausibly be accidental	L1.V1, L1.V2
thin	The criteria seem to hold but the evidence for condition (1) or (2) is weak	L1.V?
none	No violation is coded	

Table 4: Data-quality exclusions applied before sampling.

Reason	Rows	Note
Kept	1,505	
Corrupt source group	96	ChatDev–CodeLlama: 100 rows hold 30 distinct texts
Duplicate text	35	identical trajectory seen earlier; first copy kept
No MAST labels	4	all 14 labels null
Misfiled text	2	"HyperAgent" rows that contain ChatDev logs
Total	1,642	




Figure 1: Test–retest agreement of MAST's LLM judge on 30 byte-identical Magentic-One traces labelled in two runs. Cohen's κ per failure mode; mean 0.43.

Duplicates and judge consistency. The 1,642 rows contain 1,537 distinct trajectory texts. Among labelled rows, 65 groups of byte-identical texts cover 166 rows, and in 59 of these groups the copies carry different MAST labels. Thirty Magentic-One traces appear under two group names and were labelled in separate judge runs. Computing Cohen's κ separately for each of the 14 modes and averaging gives 0.43, with raw agreement of 0.80 and only 4 of 30 pairs carrying identical label sets (Figure 1). Per-mode κ ranges from -0.05 (FM-1.2) to 0.67 (FM-2.6). Pooling all modes into one list inflates the figure to 0.54, because modes that are almost always absent count as agreement; this is why per-code averaging is used throughout. In the ChatDev–CodeLlama group, copies of the same text agree at a mean per-mode κ of -0.04 over 111 pairs, which suggests that text and labels were mismatched upstream; the group is excluded.

MAST's authors report that their few-shot o1 judge agrees with human experts at $\kappa = 0.77$ [8]. The two figures are not directly comparable: they cover different traces and may be computed differently. Even so, repeat runs of the same judge on identical traces agreeing at a mean per-mode κ of 0.43 suggest that individual MAST labels carry substantial run-to-run noise, which matters for any analysis, including RQ4 here, that treats them as a reference.

Metadata errors and logging artefacts. The OpenManus traces are tagged as a programming benchmark but are GAIA questions; the AG2 "GSM" traces are GSM-Plus. Both are corrected. In 29 of the 30 OpenManus logs the task is printed truncated to about 50 characters, although the agents' plans show they received the full text; in the remaining one the task was typed in interactively and never logged. Rendered traces carry a note in both cases. Five traces have an empty task: the harness gave the agents nothing to do. MAST nevertheless labels the MetaGPT example `MetaGPT_ProgramDev2_GPT4o__099` with FM-1.1 Disobey Task Specification and FM-2.2 Fail to Ask for Clarification (Section 7). These artefacts bear directly on Ezell et al.'s reconstruction challenge, and RQ2 examines them systematically.

The human-labelled subset. MAST's separate human-labelled file holds 19 traces (not 21), coded with four different revisions of the taxonomy. Within every round, different traces carry identical three-annotator label vectors, contradicting the original annotation sheets in MAST's repository, so the file is not used.

No ground-truth outcome. MAST records no task success flag, so a "failed" trace here means one the judge flagged with at least one mode. Only 60 traces carry the benchmark's own verdict in the log (AppWorld and the AG2 GSM-Plus subset; 52 fail, 8 pass).

Eligible pool. ChatDev is excluded by design: its traces run from about 60,000 to 500,000 tokens of cleaned text (median 83,893), too long to code or to check reliably. Traces above 30,000 tokens are also




Figure 2: Share of kept traces in which MAST's judge flags each failure mode, by framework. ChatDev is shown for completeness but excluded from the study.

excluded. That leaves 893 MAST-failed and 373 MAST-clean traces across six frameworks: AG2 286 failed, MetaGPT 408, Magentic-One 127, AppWorld 27, OpenManus 27 and HyperAgent 18. Figure 2 shows how often the judge flags each mode by framework. Model is largely confounded with framework: four frameworks ran a single model, and "Claude" carries no version number.

5 Method

Ingest and rendering. Each framework writes a different log format. A parser per format splits each trace into numbered steps, keeps agent text verbatim, and drops only log scaffolding and pure noise (package-installation logs, token counters, repeated web-server warnings). A word-level check confirmed that only scaffolding is lost. Each trace is rendered as a document with numbered steps, and every coder, human or AI, reads the same rendering, so that disagreement concerns the application of the codebook and not what each coder saw. MAST's labels are hidden. Information the agents never saw (benchmark answers, gold patches and the benchmark's own pass/fail verdict) is hidden and replaced by a placeholder, which keeps the step numbering stable and prevents the outcome from colouring the coding.

Information audit (RQ2). For each framework, each of the eighteen items in Ezell et al.'s Table 1 is classified as present, partial, absent or not applicable to benchmark runs. Where a reliable automatic check exists (timestamps, tool calls and outputs, reasoning text, model identifiers, sampling settings, package versions, error messages), the share of traces in which it fires is reported, and the status is a judgement informed by that share. Otherwise the classification rests on reading three sampled traces per framework (the first, middle and last by identifier), with the reason recorded for every judgement. All seven frameworks are audited, ChatDev included. What MAST's dataset records outside the logs (framework, an unversioned model name and the benchmark) is noted separately (`docs/information_audit.md`).

AI pilot (RQ3 and RQ4). Claude codes a sample of MAST-failed traces with codebook v1. The primary annotator is `claude-sonnet-5-5`; a second model, `claude-opus-5-5`, codes the same traces. Each annotation runs through Claude Code's headless mode on the author's Claude subscription, with Claude Code's tools, MCP servers and commands switched off and its default system prompt replaced by the annotator prompt (`prompts/annotator_v1.md`) with the codebook pasted in. The trace is the user message, and the reply is constrained by a JSON schema whose allowed codes are read from the

codebook, so the annotator cannot invent codes and must give step-referenced evidence for each code, a causal summary, and an evidence grade for any violation. Every annotation records the backend, the model requested and the model that served it, the prompt and codebook versions, a hash of the full system prompt, token usage and a session identifier. A refusal is recorded as an error and is not routed to another model. At API list prices the 250-trace run would cost about $14 with `claude-sonnet-5-5`; through the subscription it counts against the plan's usage instead.

The sample is the 250-trace bulk sample: MAST-failed traces outside the frozen calibration set (below), balanced across frameworks (AG2 64, AppWorld 23, HyperAgent 13, Magentic-One 63, MetaGPT 64, OpenManus 23) and across models within each framework. Each trace carries a weight equal to the number of eligible traces it represents, so that overall shares describe the eligible pool rather than the balanced sample; they are reported with Wilson 95% intervals on the Kish effective sample size $n_{\text{eff}} = (\sum w)^2 / \sum w^2$. Model comparisons are limited to MetaGPT and AG2 and are exploratory.

Consistency measures. Consistency is measured between the two models and between two runs of the primary model on the same traces. Agreement uses Cohen's κ [27], read with the Landis and Koch bands [28], for the presence of each layer, for each code (averaged across codes, never pooled), for error versus violation, for the violation evidence grade, for the deepest layer (with a linearly weighted variant on the ordered scale L1 to L4), and for whether a failure was observed; the share of identical full code sets is also reported, because exact matches are much rarer than partial ones in automated HFACS coding [20]. Each headline κ carries a 95% bootstrap interval (2,000 resamples), omitted where either coder gave fewer than three positive or three negative answers, because κ behaves badly for rare or near-universal categories [29]. The natural point of comparison is the 0.43 at which MAST's own judge agrees with itself (Section 4). These measures show whether the framework can be applied *consistently*. They do not show that the codes are *correct*: two runs of a model can agree and both be wrong. Correctness requires independent human coders, which is the purpose of the planned validation.

Expert case studies. The author, a flight safety officer, reviews a small number of the AI's codings with the trace alongside. Reviewing a coding is a different task from coding blind, and these reviews are presented as illustrations of what the framework shows, not as validation.

Planned validation (second study). A calibration set of thirty traces was drawn before this study changed direction and has been frozen for human validation. It holds five traces from each of six frameworks; in four frameworks one of the five is a MAST-clean control in place of a failed trace, giving 26 failed traces and 4 blind controls. A development set of 18 traces and a held-out test set of 12 were fixed before any coding, and the hidden key's SHA-256 fingerprint is committed to the repository. Independent coders will code these traces blind in a purpose-built coding tool, first with the current codebook and then, after any revision, in a second review pass, before seeing any AI coding. The AI pilot does not touch these thirty traces, so that they remain uncontaminated for human coders.

6 Results

6.1 RQ1: cross-walk

Every factor in Ezell et al.'s taxonomy has a place in AFACS (Table 2), most of them at L4, L2.1 or the L1 errors. The extension adds three things with no counterpart in their framework: a supervision tier (L3.1–L3.3), coordination between agents (L2.3), and graded violations. In the other direction, their framework contributes a model-development factor, which AFACS adopts as the proposed L4.4, and named security-related contexts. Whether the added categories matter in practice is an empirical question, taken up in RQ3.

6.2 RQ2: information adequacy

Figure 3 shows, for each framework, the status of each of the eighteen items, and Table 5 counts them. The logs are good records of what the agents said and did: the agents' responses and actions are present in all seven frameworks, and the user's task in six (OpenManus prints it only in part). Everything needed




Figure 3: MAST's logs against the eighteen information items of Ezell et al.'s Table 1, by framework. Colour gives the status; numbers give the share of traces in which an automatic check fires; M marks judgements made by reading sampled traces. Items marked * matter mainly for reconstruction.

to identify or re-run the system that failed is missing. No framework provides system documentation and change logs, system artefacts, or model and system access. System configuration is at best partial: ChatDev logs its sampling settings (temperature 0.2, top-p 1.0) and Magentic-One's installation log reveals its scaffolding package versions, but no framework logs a random seed, and MAST names models without versions. System prompts are logged only by ChatDev. Labelled reasoning appears only in OpenManus and HyperAgent; in the other frameworks the only reasoning visible is what a model chose to write into its messages, which Ezell et al. note may not reflect its actual reasoning. Timestamps are absent from AG2 and Magentic-One.

Only ChatDev records a model identifier inside the log, and it does not always agree with MAST's metadata: one group of 30 traces that MAST labels GPT-4o logs the identifier `ModelType.GPT_45`, so either the metadata or the log is wrong. Without logged identifiers, such discrepancies cannot be detected in the other six frameworks.

What an investigator can establish therefore depends on the software that produced the trace rather than on the failure (Table 5). For AFACS the consequence is uneven observability across layers. Unsafe acts and coordination are well observed, because agent-to-agent messages are logged. Supervision failures are visible as behaviour, for instance an orchestrator that lets an error stand, but without system prompts or role definitions it is often impossible to tell whether the orchestrator was ever instructed to check. Model development (L4.4) cannot be evidenced from these logs at all. These findings are an empirical instance of the reconstruction difficulties Ezell et al. list as an open challenge.

6.3 RQ3: applicability

[Pending: agreement between models and between runs (Table 6); weighted prevalence of supervision (L3.1–L3.3), coordination (L2.3) and violation codes, with violations broken down by evidence grade, overall and by framework].

Table 5: Number of Ezell et al.'s eighteen information items each framework's logs provide. Applicable excludes items that do not arise in these benchmark runs (e.g. tool information for agents that use no tools).

Framework	Traces	Applicable	Present	Partial	Absent
AppWorld	29	18	8	5	5
Magentic-One	165	17	6	6	5
OpenManus	30	17	6	4	7
HyperAgent	28	17	5	5	7
AG2	597	15	2	5	8
ChatDev	226	14	6	5	3
MetaGPT	430	10	2	3	5

Table 6: Consistency of AI coding with AFACS on the bulk sample (shell; values pending). Cohen's κ with 95% bootstrap intervals.

Measure	Sonnet vs Opus	Sonnet run 1 vs run 2
L4 present	–	–
L3 present	–	–
L2 present	–	–
L1 present	–	–
Individual codes (mean per-code κ)	–	–
Violation vs error	–	–
Violation evidence grade	–	–
Deepest layer (weighted)	–	–
Failure observed	–	–
Identical full code set (share of traces)	–	–

6.4 RQ4: MAST's flat labels

Before coding, the framework implies where each MAST mode should fall (Table 7). The central expectation is that FM-1.1 Disobey Task Specification spreads across layers and across errors and violations, because it can describe a misread task, a deficient specification, a registered requirement that was ignored, or, as in the empty-task traces, no task at all.

[Pending: observed distribution of AFACS layers, codes and violation grades within each MAST mode; modes that map to one layer and modes that spread].

7 Case Studies

[Pending: three or four traces from the bulk sample, reviewed by the author, where layered coding changes the account of the failure].

One illustration of the flat-label problem comes from the audit. In `MetaGPT_ProgramDev2_GPT4o__099`

Table 7: Where the framework expects MAST's modes to fall in AFACS, to be tested against the AI pilot.

MAST mode	Expected AFACS location
1.1 Disobey task specification	Spread: L3.4, L1.E2 or L1.E3, L1.V, or a harness defect
1.2 Disobey role specification	L4.1 role design, or L1.E2 / L1.V
1.3 Step repetition	L1 acts, with L3.3 (loop not broken) and L4.1 (no termination logic)
1.4 Loss of conversation history	L2.2 agent state, with L4.2 context limits
1.5 Unaware of termination conditions	L4.1 termination logic, or L1.E2
2.1–2.5 Inter-agent misalignment	Mostly L2.3 coordination; 2.2 also L3.4
2.6 Reasoning–action mismatch	L1.E1 (sound intention, faulty execution), or L1.V
3.1 Premature termination	L1.E2, or L1.V (false claim of completion), with L3.1
3.2 No or incomplete verification	L3.1, L4.3, or L1.V1 (routine skipping)
3.3 Incorrect verification	L3.1, L1.E2 or L1.E3

the task text is empty: the harness passed nothing (step S2). The coder agent writes the placeholder `your_code_here` (S3). The tester writes template tests for a function that does not exist (S4). The reviewer asks for more specific test inputs and never mentions that there is no task and no code (S5), and the exchange repeats once more before the run ends (S6–S7). MAST labels the trace FM-1.1 Disobey Task Specification and FM-2.2 Fail to Ask for Clarification. There was no specification to disobey. Under the violation rule, condition (1) cannot hold, so none of the agents' behaviour here can be coded as a violation. How AFACS should code a defect in the experimental harness itself is an open question in codebook v1.

8 Discussion

The information audit already has an implication for how multi-agent systems are logged. Ezell et al. recommend that developers retain system documentation, exact versions and runtime settings for investigators; MAST's traces, which are among the most widely used public records of multi-agent failure, contain almost none of them. A logging standard for multi-agent research releases, covering at least model identifiers and versions, sampling settings and seeds, system prompts and role definitions, and timestamps, would let later studies reconstruct the failures they analyse. *[Pending: what the extension adds to Ezell et al.'s framework in practice; how consistently the framework can be applied, and what that means for AI-assisted incident analysis]*.

9 Limitations

- **No human validation yet.** The pilot measures consistency, not correctness; agreement between AI runs can coexist with shared error. Human validation is the next study.
- **AI coding AI traces.** The annotator is a language model coding the behaviour of other language models, and may share their blind spots.
- **Behavioural, not intentional.** "Violation" describes what the trace shows. It is not a claim about what a model wanted, and stated reasoning may not reflect what produced an action.
- **Annotation route.** Annotations run through Claude Code's headless mode rather than the bare API. Tools are disabled and the system prompt replaced, but the surrounding harness is Claude Code's, and results with the same prompt through the API may differ slightly.
- **Noisy reference labels.** MAST's labels come from an LLM judge with a test–retest κ of 0.43 on the duplicated traces, a small sample of 30.
- **No ground-truth outcome.** "Failed" means flagged by MAST's judge, except for the 60 traces that carry a benchmark verdict.
- **Failures, not incidents.** Benchmark failures carry no harm; the occurrence-reporting analogy is an argument, not a demonstration.
- **Coverage and confounding.** ChatDev and traces above 30,000 tokens are excluded. Model is confounded with framework and, within AG2, with benchmark, so model comparisons are exploratory.
- **Contested reliability.** HFACS reliability is itself debated [17, 18].

10 Future Work

The next study validates AFACS with independent human coders on the frozen calibration set, measuring agreement between humans and between humans and the AI annotator on the pre-registered held-out traces.

A further phase applies AFACS to a domain evaluation of aviation dispatch and safety decisions under pressure. Each scenario has a ground-truth answer (a minimum equipment list item, a flight-time limitation, weather minima or a fuel decision) and is run in neutral, commercial-pressure, authority-pressure and user-frustration variants. The measure is how often the safe answer survives the pressure, and the

failures are coded with AFACS, with particular attention to error versus violation. It would be built in the UK AI Security Institute's Inspect framework [30] from public regulatory sources only. Related aviation evaluations include Pre-Flight, a benchmark of aviation operational knowledge available in Inspect [31]; PilotBench, which tests trajectory and attitude prediction under safety constraints [32]; and AeroCopilotBench, which evaluates agents on aircraft emergency procedures in an executable cockpit [33]. None of these codes the failures it finds with a human-factors framework.

Use of AI Tools

The data pipeline, tests and figures were built with Claude Code under the author's direction. The AI pilot's annotations are produced by Claude models through Claude Code's headless mode on the author's subscription, as described in Section 5. The framework, the codebook decisions and the expert reviews are the author's. Every study-design decision is recorded with its reason in `src/afacs/design.py`, and the pipeline is open.

Data and Code

MAST dataset: Cemri et al. [8], CC-BY-4.0. Code: MIT licence. Traces are not redistributed because they contain benchmark questions whose maintainers ask that they not be reposted in crawlable form; the pipeline recreates them from the pinned dataset revision.

References

[1] J. Reason, *Human Error*. Cambridge University Press, 1990.

[2] J. Reason, *Managing the Risks of Organizational Accidents*. Ashgate, 1997.

[3] S. A. Shappell and D. A. Wiegmann, "The Human Factors Analysis and Classification System–HFACS," U.S. Department of Transportation, Federal Aviation Administration, Office of Aviation Medicine, Report DOT/FAA/AM-00/7, 2000.

[4] D. A. Wiegmann and S. A. Shappell, *A Human Error Approach to Aviation Accident Analysis: The Human Factors Analysis and Classification System*. Ashgate, 2003.

[5] J. Reason, A. Manstead, S. Stradling, J. Baxter and K. Campbell, "Errors and violations on the roads: a real distinction?" *Ergonomics*, vol. 33, no. 10–11, pp. 1315–1332, 1990.

[6] C. Ezell, X. Roberts-Gaal and A. Chan, "Incident analysis for AI agents," in *Proc. AAAI/ACM Conference on AI, Ethics, and Society (AIES)*, 2025. arXiv:2508.14231.

[7] B. Baker, J. Huizinga, L. Gao, Z. Dou, M. Y. Guan, A. Madry, W. Zaremba, J. Pachocki and D. Farhi, "Monitoring reasoning models for misbehavior and the risks of promoting obfuscation," arXiv:2503.11926, 2025.

[8] M. Cemri, M. Z. Pan, S. Yang, L. A. Agrawal, B. Chopra, R. Tiwari, K. Keutzer, A. Parameswaran, D. Klein, K. Ramchandran, M. Zaharia, J. E. Gonzalez and I. Stoica, "Why do multi-agent LLM systems fail?" in *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. arXiv:2503.13657.

[9] M. Shamsujjoha, Q. Lu, D. Zhao and L. Zhu, "Swiss cheese model for AI safety: A taxonomy and reference architecture for multi-layered guardrails of foundation model based agents," arXiv:2408.02205, 2024.

[10] S. Mylius, "Systematic hazard analysis for frontier AI using STPA," arXiv:2506.01782, 2025.

[11] N. G. Leveson, *Engineering a Safer World: Systems Thinking Applied to Safety*. MIT Press, 2012.

[12] D. Deshpande, V. Gangal, H. Mehta, J. Krishnan, A. Kannappan and R. Qian, "TRAIL: Trace reasoning and agentic issue localization," arXiv:2505.08638, 2025.

[13] K. Zhu et al., "Where LLM agents fail and how they can learn from failures," arXiv:2509.25370, 2025.

[14] S. Zhang et al., "Which agent causes task failures and when? On automated failure attribution of LLM multi-agent systems," in *Proc. ICML*, PMLR vol. 267, pp. 76583–76599, 2025.

[15] H. Raj, V. Gupta, A. Mahmoud, R.-G. Dumitru, D. Yi, A. Sabharwal and Y. He, "Model or harness? An interaction-centric taxonomy for localizing agent failures," arXiv:2607.28802, 2026.

[16] D. A. Wiegmann and S. A. Shappell, "A human error analysis of commercial aviation accidents using the Human Factors Analysis and Classification System (HFACS)," U.S. Department of Transportation, Federal Aviation Administration, Office of Aviation Medicine, Report DOT/FAA/AM-01/3, 2001.

[17] N. S. Olsen and S. T. Shorrock, "Evaluation of the HFACS-ADF safety classification system: Inter-coder consensus and intra-coder consistency," *Accident Analysis & Prevention*, vol. 42, no. 2, pp. 437–444, 2010.

[18] T. N. Cohen, D. A. Wiegmann and S. A. Shappell, "Evaluating the reliability of the Human Factors Analysis and Classification System," *Aerospace Medicine and Human Performance*, vol. 86, no. 8, pp. 728–735, 2015.

[19] B. R. Burnham, "Letter to the Editor re: Evaluating the reliability of the Human Factors Analysis Classification System," *Aerospace Medicine and Human Performance*, vol. 88, no. 6, p. 597, 2017.

[20] A. Ahmadi, S. Sharif and Y. Banad, "Improving aviation safety analysis: Automated HFACS classification using reinforcement learning with group relative policy optimization," arXiv:2508.21201, 2025.

[21] V. Krakovna, J. Uesato, V. Mikulik, M. Rahtz, T. Everitt, R. Kumar, Z. Kenton, J. Leike and S. Legg, "Specification gaming: the flip side of AI ingenuity," DeepMind blog, April 2020.

[22] Z. Zhong, A. Raghunathan and N. Carlini, "ImpossibleBench: Measuring LLMs' propensity of exploiting test cases," arXiv:2510.20270, 2025.

[23] A. Meinke, B. Schoen, J. Scheurer, M. Balesni, R. Shah and M. Hobbhahn, "Frontier models are capable of in-context scheming," arXiv:2412.04984, 2024.

[24] A. Lynch, B. Wright, C. Larson, S. J. Ritchie, S. Mindermann, E. Hubinger, E. Perez and K. Troy, "Agentic misalignment: How LLMs could be insider threats," arXiv:2510.05179, 2025.

[25] N. Smyth et al., "Quantifying overclaiming propensity in frontier LLM agents," arXiv:2609.20812, 2026.

[26] A. Hägele, A. P. Gema, H. Sleight, E. Perez and J. Sohl-Dickstein, "The hot mess of AI: How does misalignment scale with model intelligence and task complexity?" in *Proc. ICLR*, 2026. arXiv:2601.23045.

[27] J. Cohen, "A coefficient of agreement for nominal scales," *Educational and Psychological Measurement*, vol. 20, no. 1, pp. 37–46, 1960.

[28] J. R. Landis and G. G. Koch, "The measurement of observer agreement for categorical data," *Biometrics*, vol. 33, no. 1, pp. 159–174, 1977.

[29] A. R. Feinstein and D. V. Cicchetti, "High agreement but low kappa: I. The problems of two paradoxes," *Journal of Clinical Epidemiology*, vol. 43, no. 6, pp. 543–549, 1990.

[30] UK AI Security Institute, "Inspect AI: Framework for large language model evaluations," software, 2024. `https://inspect.aisi.org.uk/`.

[31] A. Brooker and T. Hughes, "Pre-Flight: A benchmark for evaluating large language models on aviation operational knowledge," arXiv:2607.01829, 2026.

[32] Y. Wu, H. Liu, Z. Li and B. Wang, "PilotBench: A benchmark for general aviation agents with safety constraints," in *Proc. International Joint Conference on Neural Networks (IJCNN)*, 2026. arXiv:2604.08987.

[33] Y. Yuan, Z. Wu, Y. Li, L. Ma and K. Li, "AeroCopilotBench: Safety-gated evaluation of LLM agents on aircraft emergency procedures in an executable cockpit," arXiv:2608.16349, 2026.