

OpenBR – Open Source Biometric Recognition and Beyond

Josh Klontz

www.openbiometrics.org

February 17, 2013

Why Open Source?

Why Open Source?

Reproducible Research

Support a common set of file formats and tools for algorithm design, development, and evaluation.

Why Open Source?

Reproducible Research

Support a common set of file formats and tools for algorithm design, development, and evaluation.

Decrease Time to Market

Provide a well-engineered and consistent framework for deploying new algorithms.

Why Open Source?

Reproducible Research

Support a common set of file formats and tools for algorithm design, development, and evaluation.

Decrease Time to Market

Provide a well-engineered and consistent framework for deploying new algorithms.

Reduce Duplication

Supply state-of-the-art baseline components for algorithm design.

Why Open Source?

Reproducible Research

Support a common set of file formats and tools for algorithm design, development, and evaluation.

Decrease Time to Market

Provide a well-engineered and consistent framework for deploying new algorithms.

Reduce Duplication

Supply state-of-the-art baseline components for algorithm design.

Improve Collaboration

Help foster a community where collaboration takes place at the source code level.

What's in it?

Off-the-shelf algorithms

- Face Recognition
- Gender Classification
- Age Estimation
- Commercial Wrappers

What's in it?

Off-the-shelf algorithms

- Face Recognition
- Gender Classification
- Age Estimation
- Commercial Wrappers

Tools for algorithm evaluation

- Standardized set of file formats
- Automatic plot generation
- Command line interface supporting common biometrics tasks

What's in it?

Off-the-shelf algorithms

- Face Recognition
- Gender Classification
- Age Estimation
- Commercial Wrappers

Tools for algorithm evaluation

- Standardized set of file formats
- Automatic plot generation
- Command line interface supporting common biometrics tasks

Software framework for algorithm development

- C++ plugin API for implementing new algorithms
- Grammar for image processing
- Automatic testing, packaging and deployment

Software Architecture

Qt



Cross-platform application
and UI framework

OpenCV



Image processing library

Eigen



Linear algebra library

CMake



Cross-platform build system

Software Architecture

Qt



Cross-platform application and UI framework

OpenCV



Image processing library

Eigen



Linear algebra library

CMake



Cross-platform build system

br



Command line application for running algorithms and evaluating results.

C API



High-level interface for other programming languages.

C++ Plugin API



Core interface for using and developing algorithms.

Supported Platforms



Supported Platforms

Now



Mac



Soon



iOS



Supported Platforms

Now



Mac



Soon




iOS



Future



NVIDIA®



Algorithm Evaluation




Figure: OpenBR vs COTS face recognition on *MEDS* mugshot database.

Algorithm Evaluation





Figure: OpenBR vs COTS face recognition on *MEDS* mugshot database.

	OpenBR	COTS-A	COTS-B	COTS-C	COTS-D
TAR @ FAR = 0.01	0.77	0.93	<u>0.96</u>	0.86	0.80
Template Size (kB)	<u>0.75</u>	2.8	5.0	36	74
Enrollment Speed	<u>10</u>	N/A	N/A	1.3	1.2
Comparison Speed	<u>3,800,000</u>	N/A	110,000	19,000	2,000



FRVT 2012 (OpenBR = 'K')

pdfs/study_A10/dets.pdf



FRVT 2012 (OpenBR = 'K')

pdfs/study_A10/time_and_size.pdf



Algorithm Example: Face Recognition

```
$ br -algorithm FaceRecognition -compare me.jpg you.jpg
```

Algorithm Example: Face Recognition

```
$ br -algorithm FaceRecognition -compare me.jpg you.jpg
```

FaceRecognition

```
FaceDetection!<FaceRegistration>!<FaceExtraction>+  
<FaceEmbedding>+<FaceQuantization>:UCharL1
```

Algorithm Example: Face Recognition

```
$ br -algorithm FaceRecognition -compare me.jpg you.jpg
```

FaceRecognition

```
FaceDetection!<FaceRegistration>!<FaceExtraction>+  
<FaceEmbedding>+<FaceQuantization>:UCharL1
```

FaceDetection

```
Open+Cvt(Gray)+Cascade(FrontalFace)
```

Algorithm Example: Face Recognition

```
$ br -algorithm FaceRecognition -compare me.jpg you.jpg
```

FaceRecognition

```
FaceDetection!<FaceRegistration>!<FaceExtraction>+  
<FaceEmbedding>+<FaceQuantization>:UCharL1
```

FaceDetection

```
Open+Cvt(Gray)+Cascade(FrontalFace)
```

FaceRegistration

```
ASEFEyes+Affine(88,88,0.25,0.35)+FTE(DFFS)
```

Algorithm Example: Face Recognition

```
$ br -algorithm FaceRecognition -compare me.jpg you.jpg
```

FaceRecognition

FaceDetection!<FaceRegistration>!<FaceExtraction>+
<FaceEmbedding>+<FaceQuantization>:UCharL1

FaceDetection

Open+Cvt(Gray)+Cascade(FrontalFace)

FaceRegistration

ASEFEyes+Affine(88,88,0.25,0.35)+FTE(DFFS)

...

FaceEmbedding

Dup(12)+RndSubspace(0.05,1)+LDA(0.98)+Cat+PCA(768)

Live Coding

Live Coding

```
fill(161, 219, 114);  
for (var x = 40; x < 150; x += 50) {  
  rect(x, 33, 20, 10);  
  rect(x, 45, 20, 15);  
  rect(x, 62, 20, 25);  
}
```

Draw a  shape.



Shapes

line
triangle
rect
ellipse
bezier

Color

background
fill
stroke
strokeWeight


Text

text
textFont
textSize

Flow

if
for
while
function

```
fill(0,0,0);  
rect(80,80, 40,25);  
line(20,20, 180,160);
```



Investing on Principle

<http://www.youtube.com/watch?v=PUv66718DII>

CPU Scaling




Figure: <http://www.extremetech.com/computing/116561-the-death-of-cpu-scaling-from-one-core-to-many-and-why-were-still-stuck>

Evolution of Hardware and Software




Figure: <http://www.extremetech.com/computing/116561-the-death-of-cpu-scaling-from-one-core-to-many-and-why-we-re-still-stuck>

Hardware Realities




Figure: i7 3930k



Figure: GTX 680




Figure: Xeon Phi 5110p

Hardware Realities




Figure: i7 3930k

\$570.00



Figure: GTX 680

\$568.50




Figure: Xeon Phi 5110p

\$2,649

Hardware Realities




Figure: i7 3930k

\$570.00
76.8 GFLOPS



Figure: GTX 680

\$568.50
1665 GFLOPS




Figure: Xeon Phi 5110p

\$2,649
1011 GFLOPS

Hardware Realities




Figure: i7 3930k

\$570.00

76.8 GFLOPS



Figure: GTX 680

\$568.50

1665 GFLOPS




Figure: Xeon Phi 5110p

\$2,649

1011 GFLOPS

Gotcha: Memory Bandwidth

12.8 GFLOPS

48.0 GFLOPS

80 GFLOPS

Hardware Realities




Figure: i7 3930k

\$570.00

76.8 GFLOPS



Figure: GTX 680

\$568.50

1665 GFLOPS




Figure: Xeon Phi 5110p

\$2,649

1011 GFLOPS

Gotcha: Memory Bandwidth

12.8 GFLOPS

48.0 GFLOPS

80 GFLOPS

Gotcha: Code Duplication

Need a separate code base for optimized performance on each device!

Requirements

What we want

- Write once and run everywhere
- Automatically utilize all available hardware
- Run faster on future hardware

Requirements

What we want

- Write once and run everywhere
- Automatically utilize all available hardware
- Run faster on future hardware

What we need

- Virtual machine or just-in-time compiler
- Express computations using induction variables or “kernels”:

```
void example_kernel(int *a, int *b, int i) { a[i] += b[i]; }
```

Requirements

What we want

- Write once and run everywhere
- Automatically utilize all available hardware
- Run faster on future hardware

What we need

- Virtual machine or just-in-time compiler
- Express computations using induction variables or “kernels”:

```
void example_kernel(int *a, int *b, int i) { a[i] += b[i]; }
```

What we're proposing

- LLVM IR and JIT compiler
- Designing for OpenCL 2.0 standard

Perfectly Composable Image Processing Primitives

A grammar for building algorithms from orthogonal primitive kernels with typeless semantics and optimized execution.

Goals

Perfectly Composable Image Processing Primitives

A grammar for building algorithms from orthogonal primitive kernels with typeless semantics and optimized execution.

When we say...

```
Transform *lbpU2 = Transform::make("LBP(1)+U2");
```

Goals

Perfectly Composable Image Processing Primitives

A grammar for building algorithms from orthogonal primitive kernels with typeless semantics and optimized execution.

When we say...

```
Transform *lbp2 = Transform::make("LBP(1)+U2");
```

...we mean

Give me a pointer to a function that computes $LBP_{8,1}^{u2}$ on an image, minimizes main memory transactions by combining kernels, and is optimized for parallel execution on the hardware available.

Goals

Perfectly Composable Image Processing Primitives

A grammar for building algorithms from orthogonal primitive kernels with typeless semantics and optimized execution.

When we say...

```
Transform *lbp2 = Transform::make("LBP(1)+U2");
```

...we mean

Give me a pointer to a function that computes $LBP_{8,1}^{u2}$ on an image, minimizes main memory transactions by combining kernels, and is optimized for parallel execution on the hardware available.

Take-Home Message

Compilation = Source Code + Available Hardware + First Image

The End

Slides

openbiometrics.org/slides.pdf

Source

github.com/biometrics/openbr

E-mail

openbr-dev@googlegroups.com

Thank You!

Welcome to the Parallel Jungle!




Figure: <http://www.drdobbs.com/parallel/welcome-to-the-parallel-jungle/232400273>

Plugin Example: Local Binary Patterns

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>  
class LBP : public Transform {
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
        for (int r=radius; r<src.rows-radius; r++)
            for (int c=radius; c<src.cols-radius; c++) {
                float cval = p[r*src.cols+c];
                dst(r, c) =
                    (p[(r-radius)*src.cols+c-radius] >= cval ? 128 : 0) |
                    (p[(r-radius)*src.cols+c] >= cval ? 64 : 0) |
                    ...;
            }
    }
}
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
        for (int r=radius; r<src.rows-radius; r++)
            for (int c=radius; c<src.cols-radius; c++) {
                float cval = p[r*src.cols+c];
                dst(r, c) =
                    (p[(r-radius)*src.cols+c-radius] >= cval ? 128 : 0) |
                    (p[(r-radius)*src.cols+c] >= cval ? 64 : 0) |
                    ...;
            }
    }
};
```


Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
        for (int r=radius; r<src.rows-radius; r++)
            for (int c=radius; c<src.cols-radius; c++) {
                float cval = p[r*src.cols+c];
                dst(r, c) =
                    (p[(r-radius)*src.cols+c-radius] >= cval ? 128 : 0) |
                    (p[(r-radius)*src.cols+c] >= cval ? 64 : 0) |
                    ...;
            }
    }
};
BR_REGISTER(Transform, LBP)
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
        for (int r=radius; r<src.rows-radius; r++)
            for (int c=radius; c<src.cols-radius; c++) {
                float cval = p[r*src.cols+c];
                dst(r, c) =
                    (p[(r-radius)*src.cols+c-radius] >= cval ? 128 : 0) |
                    (p[(r-radius)*src.cols+c] >= cval ? 64 : 0) |
                    ...;
            }
    }
};
BR_REGISTER(Transform, LBP)
...
Transform *lbp = Transform::make("LBP(1)");
```

Plugin Example: Local Binary Patterns

```
#include <openbr_plugin.h>
class LBP : public Transform {
    BR_PROPERTY(int, radius, 1)
    void project(const Matrix &src, Matrix &dst) const {
        for (int r=radius; r<src.rows-radius; r++)
            for (int c=radius; c<src.cols-radius; c++) {
                float cval = p[r*src.cols+c];
                dst(r, c) =
                    (p[(r-radius)*src.cols+c-radius] >= cval ? 128 : 0) |
                    (p[(r-radius)*src.cols+c] >= cval ? 64 : 0) |
                    ...;
            }
    }
};
BR_REGISTER(Transform, LBP)
...
Transform *lbp = Transform::make("LBP(1)");
Transform *lbp2 = Transform::make("LBP(1)+U2");
```