

# BATBAMBAMBA: Boolean and Arithmetic Languages Oregon Programming Languages Summer School

Ronald Garcia

4 July 2017

# 1 BA: Boolean Arithmetic Language

## Program Static Syntax

$$\begin{aligned}
 t &\in \text{TERM}, \quad n \in \mathbb{N}, \quad b \in \mathbb{B}, \quad p \in \text{PGM} = \text{TERM} \\
 t &::= \text{true} \mid \text{false} \mid \text{if } t \text{ then } t \text{ else } t \\
 &\quad \mid n \mid \text{succ}(t) \mid \text{pred}(t) \mid \text{zero?}(t) \\
 b &::= \text{true} \mid \text{false}
 \end{aligned}$$

## Program Runtime Syntax

$$\begin{aligned}
 E &\in \text{ECTXT}, \quad v \in \text{VALUE}, \quad r \in \text{REDEX} \subseteq \text{PGM}, \quad f \in \text{FAULTY} \subseteq \text{PGM}, \quad \text{err} \in \text{ERROR}, \quad c \in \text{CONFIG} \quad o \in \text{OBS} \\
 v &::= b \mid n \\
 E &::= \square \mid \text{if } E \text{ then } p \text{ else } p \mid \text{succ}(E) \mid \text{pred}(E) \mid \text{zero?}(E) \\
 r &::= \text{if } v \text{ then } p \text{ else } p \mid \text{succ}(v) \mid \text{pred}(v) \mid \text{zero?}(v) \\
 f &::= \text{if } n \text{ then } p \text{ else } p \mid \text{succ}(b) \mid \text{pred}(b) \mid \text{zero?}(b) \\
 \text{err} &::= \text{mismatch} \mid \text{underflow} \\
 c &::= p \mid \text{err} \\
 o &::= v \mid \text{err}
 \end{aligned}$$
 $\rightsquigarrow \subseteq \text{REDEX} \times \text{PGM}$ 

### Notions of Reduction

$$\begin{aligned}
 &\text{if true then } p_2 \text{ else } p_3 \rightsquigarrow p_2 \\
 &\text{if false then } p_2 \text{ else } p_3 \rightsquigarrow p_3 \\
 &\quad \text{pred}(n) \rightsquigarrow n - 1 \quad \text{if } n > 0 \\
 &\quad \text{zero?}(0) \rightsquigarrow \text{true} \\
 &\quad \text{zero?}(n) \rightsquigarrow \text{false} \quad \text{if } n > 0 \\
 &\quad \text{succ}(n) \rightsquigarrow n + 1
 \end{aligned}$$
 $\longrightarrow \subseteq \text{PGM} \times \text{CONFIG}$ 

### Single-step Reduction

$$\begin{aligned}
 &\frac{r \rightsquigarrow p}{E[r] \longrightarrow E[p]} \\
 &\frac{}{E[f] \longrightarrow \text{mismatch}} \\
 &\frac{}{E[\text{pred}(0)] \longrightarrow \text{underflow}}
 \end{aligned}$$
 $\longrightarrow^* \subseteq \text{CONFIG} \times \text{CONFIG}$ 

### Multi-step Reduction

$$\begin{aligned}
 (\text{incl}) \quad &\frac{c_1 \longrightarrow c_2}{c_1 \longrightarrow^* c_2} \quad (\text{refl}) \quad \frac{}{c \longrightarrow^* c} \quad (\text{trans}) \quad \frac{c_1 \longrightarrow^* c_2 \quad c_2 \longrightarrow^* c_3}{c_1 \longrightarrow^* c_3}
 \end{aligned}$$
 $\text{eval}_{BA} : \text{PGM} \rightarrow \text{OBS}$ 

$$\begin{aligned}
 \text{eval}_{BA}(p) &= b \text{ if } p \longrightarrow^* b \\
 \text{eval}_{BA}(p) &= n \text{ if } p \longrightarrow^* n \\
 \text{eval}_{BA}(p) &= \text{mismatch} \text{ if } p \longrightarrow^* \text{mismatch} \\
 \text{eval}_{BA}(p) &= \text{underflow} \text{ if } p \longrightarrow^* \text{underflow}
 \end{aligned}$$

## Safety (AKA Coherence AKA Definedness)

**Proposition 1** (Progress). *For all  $p \in \text{PGM}$  one of the following is true:*

1.  $p \in \text{VALUE}$ ;
2.  $p \longrightarrow p'$  for some  $p' \in \text{PGM}$ ;
3.  $p \longrightarrow \text{err}$  for some  $\text{err} \in \text{ERROR}$ .

**Proposition 2** (Preservation (Vacuous)). *If  $p_1 \longrightarrow p_2$  then  $p_2 \in \text{PGM}$ . (uhh...?!?)*

## TBA: Typed Boolean Arithmetic Language

### Program Static Syntax

$t \in \text{TERM}, \quad n \in \mathbb{N}, \quad b \in \mathbb{B}, \quad \text{Same as BA}$   
 $T \in \text{TYPE}, \quad p \in \text{PGM} = \{t \in \text{TERM} \mid \exists T \in \text{TYPE}. \vdash t : T\}$   
 $T ::= \text{Nat} \mid \text{Bool}$

### Program Runtime Syntax

$E \in \text{ECTXT}, \quad v \in \text{VALUE}, \quad r \in \text{REDEX} \subseteq \text{PGM}, \quad \text{Same grammar as BA (over updated p)}$   
 $err \in \text{ERROR}, \quad c \in \text{CONFIG} \quad o \in \text{OBS}$   
 $v ::= b \mid n$   
 $r ::= \text{if } v \text{ then } p \text{ else } p \mid \text{succ}(v) \mid \text{pred}(v) \mid \text{zero?}(v)$   
 $err ::= \text{underflow}$   
 $c ::= p \mid err$   
 $o ::= v \mid err$

$\rightsquigarrow \subseteq \text{REDEX} \times \text{PGM}$	<b>Same formal schema as BA (over updated p)</b>
$\longrightarrow \subseteq \text{PGM} \times \text{CONFIG}$	<b>Single-step Reduction</b>

$$\frac{r \rightsquigarrow p}{E[r] \longrightarrow E[p]} \qquad \frac{}{E[\text{pred}(0)] \longrightarrow \text{underflow}}$$

$\models \cdot : \cdot \subseteq \text{TERM} \times \text{TYPE} \quad \text{Semantic Typing}$

$\models t : \text{Bool} \quad \text{if and only if} \quad t \longrightarrow^* b \text{ or } t \longrightarrow^* \text{underflow}$   
 $\models t : \text{Nat} \quad \text{if and only if} \quad t \longrightarrow^* n \text{ or } t \longrightarrow^* \text{underflow}$

$\vdash \cdot : \cdot \subseteq \text{TERM} \times \text{TYPE} \quad \text{Syntactic Typing}$

$$\begin{array}{c}
\frac{}{\vdash \text{true} : \text{Bool}} \quad \frac{}{\vdash \text{false} : \text{Bool}} \quad \frac{\vdash t_1 : \text{Bool} \quad \vdash t_2 : T \quad \vdash t_3 : T}{\vdash \text{if } t_1 \text{ then } t_2 \text{ else } t_3 : T} \quad \frac{}{\vdash z : \text{Nat}} \quad \frac{\vdash t : \text{Nat}}{\vdash \text{succ}(t) : \text{Nat}} \\
\frac{\vdash t : \text{Nat}}{\vdash \text{pred}(t) : \text{Nat}} \quad \frac{\vdash t : \text{Nat}}{\vdash \text{zero?}(t) : \text{Bool}}
\end{array}$$

**Evaluator**  $eval_{TBA} : \text{PGM} \rightarrow \text{OBS}$

$eval_{TBA}(p) = b \text{ if } p \longrightarrow^* b$   
 $eval_{TBA}(p) = n \text{ if } p \longrightarrow^* n$   
 $eval_{TBA}(p) = \text{underflow} \text{ if } p \longrightarrow^* \text{underflow}$

### Safety

**Proposition 3** (Progress). *For all  $p \in \text{PGM}$  one of the following is true:*

1.  $p \in \text{VALUE};$
2.  $p \longrightarrow p' \text{ for some } p' \in \text{PGM};$
3.  $p \longrightarrow \text{underflow}.$

**Proposition 4** (Preservation). *If  $\vdash p_1 : T$  and  $p_1 \longrightarrow p_2$  then  $\vdash p_2 : T$ .*

**Proposition 5** (Semantic Type Soundness). *If  $\vdash t : T$  then  $\models t : T$ .*

## **2 MBA: Mixed Boolean and Arithmetic Language**

Missing!

## **3 mMBA: Minimal Mixed Boolean and Arithmetic Language**

Missing!