

01 XML Basics

XML Basics

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 1

01 XML Basics

XML ? What is it ?

The **EX**tensible **MA**rku**P** **L**anguage (**XML**) is a general-purpose specification for creating custom markup languages

(Wikipedia <http://en.wikipedia.org/wiki/XML>)

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 2

01 XML Basics

XML ? What is it ?

XML is a framework for defining other languages:

There is no predefined collection of markup tags; it is possible to define new tags, tailored for our kind of information

Each XML language targets its own application domain

There is a common set of generic tools for processing XML documents

We shall use XML to implement **hierarchical data containers**

When comparing with the **relational data model** XML data containers are organized in a **hierarchical way** rather than in a **tabular way**

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 3

01 XML Basics

Example of XML document

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE recipe SYSTEM "/xml-resources/dtd/recipe.dtd">
<recipe id="117" category="dessert">
  <title>Rhubarb Cobbler</title>
  <author>
    <email>Maggie.Herrick@bbs.mhv.net</email>
  </author>
  <date>Wed, 14 Jun 95</date>
  <description>Rhubarb Cobbler made with bananas</description>
  <ingredients>
    <item>
      <amount unit="cup">2 1/2</amount>
      <type>diced_rhubarb</type>
    </item>
    <item>
      <amount unit="tablespoon">2</amount>
      <type>sugar</type>
    </item>
  </ingredients>
</recipe>

```

XML declaration

Document Type Declaration

Element

Attribute name

Attribute value

Start tag

End tag

Contents of element

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 4

01 XML Basics

Tag names

A name can start with any letter a-z (or A-Z), or an underscore (_)

```
<_This_is_a_very_long_element_name-but_Perfectly_acceptable>
```

The initial letter or underscore can be followed by one or more letters, digits, hyphens, underscores, full stops, combining characters, extender characters, and ignorable characters

```
<Element_12567-2>
```

Spaces and tabs are not allowed in element names; the only punctuation signs allowed are the hyphen (-) and full stop (.)

Not Acceptable: <It is not allowed>

Acceptable: <this-is-OK> <so.is.this>

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 5

01 XML Basics

Elements

An XML document is a text with markup tags and other meta-information

Markup tags denote *elements*

```
<email>Maggie.Herrick@bbs.mhv.net</email>
```

The contents of element

An element start tag with name email

A matching element end tag

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 6

01 XML Basics

Attributes

An *attribute* provides more information about the semantics of an element
 An attribute consists of a *name* and a *value*
 An element can have many attributes with unique names

An attribute with a name base

An attribute with a name unit

An value of attribute enclosed by ' or "

```
<amount unit="cup" base="decimal">2 1/2</amount>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 7

01 XML Basics

Empty elements

An empty element

```
<bottle unit="litre"></bottle>
```

A shorthand notation for empty elements

```
<bottle unit="litre"/>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 8

01 XML Basics

Special characters

Special characters can be escaped using Unicode *character references*:

< and < both yield <
 & and & both yield &

CDATA section is an alternative way of escaping many characters

```
<![CDATA[<start> this is an incorrect element</end>]]>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 9

01 XML Basics

Special elements

Instruction for a processor

Processor for which it is directed

```
<?xml-stylesheet href="book.css" type="text/css?>
```

String containing the instructions

Comment

```
<!-- This is a comment -->
```

Document Type Declaration (DTD, discussed later)

```
<!DOCTYPE name [markup declarations]>
```

Starting instruction

```
<?xml version="1.0"?>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 10

01 XML Basics

Well formed XML

XML document must be **well-formed**:

- start and end tags must match
- element tags must be properly nested
- attributes must be unique

```
<person language="EN">This is my best friend
  <first_name>Alan</first_name>
  <last_name>Smith</last_name>
  I am not sure about email
  <email>al@abc.com</email>
</person>
```

Note, that **mixed contents** elements are well formed

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 11

01 XML Basics

Well formed XML

A well-formed XML document contains one or more elements, and it has just one root (or document) element that contains all other elements

```
<?xml version="1.0">
  <carreg>
    <person>
      <ssno>6546546434</ssno>
      <name>Michael Jones</name>
      <data-of-birth>03-Oct-1967</dateofbirth>
      <address>12 Oak St. Dapto</address>
    </person>
    <car>
      <rego>12345</rego>
      <manufacturer>Mitsubishi</manufacturer>
      <model>Magna</model>
      <made>1994</made>
    </car>
  </carreg>
</carreg>
```

```
<?xml version="1.0">
<carreg>
  <person>
    <ssno>6546546434</ssno>
    <name>Michael Jones</name>
    <data-of-birth>03-Oct-1967</date-of-birth>
    <address>12 Oak St. Dapto</address>
  </person>
  <car>
    <rego>12345</rego>
    <manufacturer>Mitsubishi</manufacturer>
    <model>Magna</model>
    <made>1994</made>
  </car>
</carreg>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 12

01 XML Basics

Well formed XML

Is it enough to be "well-formed" ?

```
<person>
  <name> Alan </name>
  <age> 42 </age>
  <email> al@abc.com </email>
</person>
```

```
<person name="Alan" age="42"
  email="al@abc.com"/>
```

```
<person name="Alan">
  <age> 42 </age>
  <email> al@abc.com </email>
</person>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 13

01 XML Basics

Well formed XML

Is it enough to be "well-formed" ?

```
<hello_message>
  <language>English</language>
  <message_body>Hello world !</message_body>
</hello_message>
```

```
<hello_message language="English">
  Hello world !</hello_message>
```

```
<address format="XLB56" language="French">
  <country>France</country>
  <city>Paris</city>
  <street>Rue Lamande</street>
  <house>25</house>
  <flat>1</flat>
</address>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 14

01 XML Basics

Order of XML elements

Does order matter ?

```
<person>
  <first_name>James</first_name>
  <last_name>Bond</last_name>
</person>
```

```
<person>
  <last_name>Bond</last_name>
  <first_name>james</first_name>
</person>
```

Yes, It does !

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 15

01 XML Basics

XML references

A simple example

```
<state ID="s1">
  <rcode> NSW </rcode>
  <sname> New South Wales </sname>
</state>
```

```
<city ID="c1">
  <ccode> SYD </ccode>
  <cname> Sydney </cname>
  <state-of IDREF="s1"/>
</city>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 16

01 XML Basics

Name conflicts

HTML table, HTML component

```
<table>
  <tr>
    <td>Apples</td>
    <td>Bananas</td>
  </tr>
</table>
```

Coffee table, a piece of furniture

```
<table>
  <category>Coffee</category>
  <width>80</width>
  <length>120</length>
</table>
```

Relational table, a database object

```
<table>
  <tuple>
    <attribute>Name</attribute>
    <value>John Doe</value>
    <attribute>Date of birth</attribute>
    <value>29 February 1980</value>
  </tuple>
</table>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 17

01 XML Basics

Solving name conflicts

HTML table, HTML component

```
<html:table>
  <html:tr>
    <html:td>Apples</html:td>
    <html:td>Bananas</html:td>
  </html:tr>
</html:table>
```

Coffee table, a piece of furniture

```
<fur:table>
  <fur:category>Coffee
  </fur:category>
  <fur:width>80</fur:width>
  <fur:length>120</fur:length>
</fur:table>
```

Relational table, a database object

```
<db:table>
  <db:tuple>
    <db:attribute>Name</db:attribute>
    <db:value>John Doe</db:value>
    <db:attribute>Date of birth</db:attribute>
    <db:value>29 February 1980</db:value>
  </db:tuple>
</db:table>
```

How do we find a unique prefix ?

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 18

01 XML Basics

Creating unique prefixes

HTML table, HTML component

```
<html:table xmlns:html="http://www.w3.org/TR/html4/">
  <html:tr>
    <html:td>Apples</html:td>
    <html:td>Bananas</html:td>
  </html:tr>
</html:table>
```

Coffee table, a piece of furniture

```
<fur:table xmlns:fur="http://www.ikea.com.au/furniture">
  <fur:category>Coffee</fur:category>
  <fur:width>80</fur:width>
  <fur:length>120</fur:length>
</fur:table>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 19

01 XML Basics

Creating unique prefixes

Relational table, a database object

```
<db:table xmlns:db="http://www.ansi.com/sql">
  <db:tupel>
    <db:attribute>Name</db:attribute>
    <db:value>John Doe</db:value>
    <db:attribute>Date of birth</db:attribute>
    <db:value>29 February 1980</db:value>
  </db:tupel>
</db:table>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 20

01 XML Basics

Namespaces

Namespace attribute is always located in the beginning tag of an element

```
<xmltag xmlns:namespace-prefix="namespace-spec">
```

Namespace specification is an Uniform Resource Identifier (URI)

```
<lib:book xmlns:lib="http://www.uow.au/lib">
```

Uniform Resource Identifier identifies an Internet resource

Uniform Resource Identifier is either Uniform Resource Locator (URL)(see above) or Universal Resource Name (URN)(see below)

```
<proc:semaphore urn:dijkstra:p007,692>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 21

01 XML Basics

Default namespace

Default namespace for an element becomes a namespace for all the child elements of that element

```
<table xmlns="http://www.ansi.com/sql">
  <tupel>
    <attribute>Name</attribute>
    <value>John Doe</value>
  </tupel>
</table>
```

It is equivalent to:

```
<db:table xmlns:db="http://www.ansi.com/sql">
  <db:tupel>
    <db:attribute>Name</db:attribute>
    <db:value>John Doe</db:value>
  </db:tupel>
</db:table>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 22

01 XML Basics

Visualization of XML documents

```
<state> NSW
  <city>Wollongong
    <suburb>Figtree</suburb>
    <suburb>Horsley</suburb>
  </city>
  <city>Sydney
    <suburb>Sutherland</suburb>
  </city>
</state>
```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 23

01 XML Basics

Visualization of XML documents

We would like to record information about students, subjects, and enrolments

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 24

01 XML Basics

XML references

Are the hierarchical structures expressive enough ?
We would like to record information about students, subjects, and enrolments

```

<enrolments>
  <subject>
    <code>ITCS206</code>
    <title>Markup languages</title>
    <students>
      <student>
        <number>007</number>
        <name>James Bond</name>
      </student>
      <student>
        <number>777</number>
        <name>Harry Potter</name>
      </student>
    </students>
  </subject>
  ...

```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 25

01 XML Basics

XML References

Are the hierarchical structures expressive enough ?
We would like to record information about students, subjects, and enrolments

```

...
<subject>
  <code>CSCI235</code>
  <title>Databases</title>
  <students>
    <student>
      <number>001</number>
      <name>Janusz Getta</name>
    </student>
    <student>
      <number>777</number>
      <name>Harry Potter</name>
    </student>
  </students>
</subject>
</enrolments>

```

Harry Potter's record is repeated twice !

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 26

01 XML Basics

XML References

Are the hierarchical structures expressive enough ?
We would like to record information about students, subjects, and enrolments

```

<enrolments>
  <subject ID="ITCS206">
    <title>Markup languages</title>
  </subject>
  <subject ID="CSCI253">
    <title>Databases</title>
  </subject>
  <students>
    <student>
      <number>007</number>
      <name>James Bond</name>
      <enrolment IDREF="ITCS206"/>
    </student>
    ...

```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 27

01 XML Basics

XML References

Are the hierarchical structures expressive enough ?
We would like to record information about students, subjects, and enrolments

```

...
<student>
  <number>777</number>
  <name>Harry Potter</name>
  <enrolment IDREF="ITCS206"/>
  <enrolment IDREF="CSCI253"/>
</student>
<student>
  <number>001</number>
  <name>Janusz Getta</name>
  <enrolment IDREF="CSCI253"/>
</student>
</students>
</enrolments>

```

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 28

01 XML Basics

XML References

Diagram illustrating XML references between subjects, students, and enrolments. The diagram shows a hierarchical structure where subjects are referenced by students, and students are referenced by enrolments. The enrolment records use IDREF attributes to reference specific subjects and students.

How to design XML documents ?

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 29

01 XML Basics

References

Elmasri R., Navathe S., Fundamentals of Database Systems, 6th edition, chapter 12 XML: Extensible Markup Language, pp. 420-448
<http://www.uow.edu.au/~jrg/235/HOMEWORK>
 8.1 How to create well formed XML documents ?

© Janusz R. Getta CSC1235/MCS9235/CSCI835 Databases, SCIT, Autumn 2015 30