

## Appendix E: Visualization

---

Visualizations will use the following python libraries:

```
import pandas as pd
import glob
import datetime
import itertools
import matplotlib.pyplot as plt
```

We define several helper functions to assist with reading the cluster files:

```
def read_named_cluster_file(infile_name):
    """ take a file output from COS and return a dictionary,
    where keys are the name of a cluster,
    and values are sets containing names of nodes in the cluster"""
    clusters = dict()
    with open(infile_name, 'r') as fin:
        for i, line in enumerate(fin):
            name = line.split(' ')[0]
            if not clusters.has_key(name):
                clusters[int(name)] = set()
            nodes = line.split(' ')[1:-1]
            for node in nodes:
                clusters[int(name)].add(node)
    return clusters

def get_clusters_with_keyword(date, threshold, keyword):
    """Get clusters from the dataset that include the keyword.
    Get them for the specified date and threshold.

    date : string in yyyyymmdd format
    threshold : integer above 2

    """
    files = pd.DataFrame(glob.glob(date+'/th_%02i'%threshold+'/named*_communities.txt'), columns=['filename'])
    files['clique_size']=files['filename'].apply(lambda x: int(x.split('named')[1].split('.')[0]))
    files.sort('clique_size', ascending=False, inplace=True)
```

```

outlist = []

for index, row in files.iterrows():
    clusters = read_named_cluster_file(row['filename'])
    for index, cluster_set in clusters.iteritems():
        outdict = {}
        if keyword in cluster_set:
            outdict['date'] = date
            outdict['threshold'] = threshold
            outdict['keyword'] = keyword
            outdict['elements'] = cluster_set
            outdict['k-clique'] = row['clique_size']
            outdict['name'] = index
            outdict['id'] = str(date)+'_k'+str(row['clique_size'])+'_t'+str(threshold)
            outdict['size'] = len(cluster_set)
            outlist.append(outdict)
return pd.DataFrame(outlist)

def get_next_clusters(clustersdf, min_likelihood=0):
    """Returns a new clustersdf for the subsequent day
    and a transition matrix between the input and output clustersdf.

    min_likelihood sets a lower bar on the chance that a next-day cluster is the
    same as the previous-day cluster"""

    outlist=[]
    transitions = pd.DataFrame()
    for i, row in clustersdf.iterrows():
        current_date = row['date']
        next_date = dates[dates.index(current_date)+1]

        tr_file = '%s/th_%02i/named%i_communities_transition.csv'%(current_date,
                                                                    row['threshold'],
                                                                    row['k-clique'])

        tr_matrix = pd.read_csv(tr_file, index_col=0)

        shared_elements = tr_matrix.loc[int(row['name'])]
        candidate_names = shared_elements[shared_elements>0].index

        next_clusters_filename = '%s/th_%02i/named%i_communities.txt'%(next_date,
                                                                    row['threshold'],
                                                                    row['k-clique'])

        next_clusters = read_named_cluster_file(next_clusters_filename)

```



```

def __init__(self, contains, uid=None):
    if isinstance(contains, (set, frozenset)): #convenience conversion of set to list.
        contains = list(contains)

    if isinstance(contains, list):
        self.is_leaf = False
        self.contents = []
        for element in contains:
            if isinstance(element, basestring):
                self.contents.append(cluster_drawing(element))
            else:
                self.contents.append(element)
        self.linewidth = 1
    elif isinstance(contains, basestring):
        self.is_leaf = True
        #self.text = contains.encode('ascii', 'ignore')
        self.text = contains
        self.text = contains.decode('utf-8', 'ignore')
        self.linewidth = 0

    self.bottom = 0
    self.center = 0
    self.pts_buffer = 4
    self.uid = uid

def get_list(self):
    if self.is_leaf:
        return [self.text]
    else:
        return [item for x in self.contents for item in x.get_list()] #flat list

def get_set(self):
    return set(self.get_list())

def get_by_name(self, name):
    if self.is_leaf: return None

    if self.uid == name:
        return self
    else:
        for x in self.contents:
            obj = x.get_by_name(name)
            if obj == None:
                continue

```

```

        else:
            return obj
    return None

def get_uids(self):
    if self.is_leaf:
        return []
    else:
        uid_list = [item for x in self.contents for item in x.get_uids()] #flat list
        if self.uid != None:
            uid_list.append(self.uid)
        return uid_list

def score(self):
    """Get the score for the full (recursive) contents"""
    score=0
    this_list = self.get_list()
    for word in set(this_list):
        indices = [i for i, x in enumerate(this_list) if x == word]
        if len(indices)>1:
            score += sum([abs(a-b) for a, b in itertools.combinations(indices, 2)])
    return score

def order(self, scorefunc):
    """Put the contents in an order that minimizes the score of the whole list"""
    if not self.is_leaf:
        best_score = 10000000
        best_order = self.contents
        for permutation in itertools.permutations(self.contents):
            self.contents = permutation
            new_score = scorefunc()
            if new_score < best_score:
                best_score = new_score
                best_order = permutation
        self.contents = best_order

    [element.order(scorefunc) for element in self.contents]

def set_height(self, ax):
    if self.is_leaf:
        #have to mockup the actual image to get the width
        self.image_text = ax.text(0, 0, self.text, **self.text_properties)
        plt.draw()
        extent = self.image_text.get_window_extent()

```

```

        self.height = extent.y1 - extent.y0
    else:
        self.height = (sum([x.set_height(ax) for x in self.contents]) +
                        (len(self.contents)+1)*self.pts_buffer)
    return self.height

def set_width(self, ax):
    if self.is_leaf:
        #have to mockup the actual image to get the width
        self.image_text = ax.text(0, 0, self.text,
                                   transform=None, **self.text_properties)

        plt.draw()
        extent = self.image_text.get_window_extent()
        self.width = extent.x1 - extent.x0 + self.pts_buffer
    else:
        self.width = max([x.set_width(ax) for x in self.contents]) + 2*self.pts_buffer
    return self.width

def set_center(self, x):
    if not self.is_leaf:
        [child.set_center(x) for child in self.contents]
    self.center = x

def set_bottom(self, bottom=0):
    """Sets the bottom of the box.
    recursively sets the bottoms of the contents appropriately"""
    self.bottom = bottom + self.pts_buffer

    if not self.is_leaf:
        cum_height = self.bottom
        for element in self.contents:
            element.set_bottom(cum_height)
            cum_height += element.height + self.pts_buffer

def layout(self, ax):
    if not self.is_leaf:
        [child.layout(ax) for child in self.contents]

    plt.box('off')
    self.set_width(ax)
    self.set_height(ax)
    ax.clear()

def draw(self, ax):

```

```

if not hasattr(self, 'width'):
    print 'Must run `layout` method before drawing, preferably with dummy axis'

if self.is_leaf:
    self.image_text = ax.text(self.center, self.bottom, self.text,
                             transform=None, **self.text_properties)
else:
    [child.draw(ax) for child in self.contents]
    ax.add_patch(plt.Rectangle((self.center-.5*self.width,self.bottom),
                              self.width, self.height,
                              alpha=.1, transform=None))

ax.set_axis_off()

```

We define several functions which intermediate between the visualization object and the clusters as they have been imported:

```

def make_elements(clustersdf, k_min=0, k_max=25, order=False):

    prev_elements = []
    for k, k_group in clustersdf.groupby('k-clique', sort=False):
        if k < k_min: continue
        if k > k_max: continue
        elements = []
        for i, row in k_group.iterrows():
            cluster_elements = row['elements']
            cluster_list = [] #this is what we will eventually pass to the class initialize
            for prev_element in prev_elements:
                prev_set = prev_element.get_set()
                if prev_set <= cluster_elements: #set 'contains'
                    cluster_elements = cluster_elements - prev_set
                    cluster_list = cluster_list + [prev_element]

            cluster_list = cluster_list + list(cluster_elements)
            elements.append(cluster_drawing(cluster_list, row['id']))

        prev_elements = elements

    a = cluster_drawing(elements)
    if order:
        a.order(a.score)
    return a

```

```

def draw_transition(a, b, tr_matrix, ax):
    for a_id in a.get_uids():
        for b_id in b.get_uids():
            try:
                likelihood = tr_matrix.loc[a_id, b_id]
            except KeyError: # if either don't show up in the transition matrix, they don't
                continue
            if likelihood > 0:
                #print a_id, b_id, likelihood
                a_object = a.get_by_name(a_id)
                b_object = b.get_by_name(b_id)

                ax.plot([a_object.center+.5*a_object.width, b_object.center-.5*b_object.width],
                        [a_object.bottom, b_object.bottom],
                        color='b', alpha=likelihood**2, transform=None)

                ax.plot([a_object.center+.5*a_object.width, b_object.center-.5*b_object.width],
                        [a_object.bottom+a_object.height, b_object.bottom+b_object.height],
                        color='b', alpha=likelihood**2, transform=None)

    ax.set_axis_off()

```

Finally, we are ready to make a visualization:



```

fig = plt.figure(figsize=(18,23))
ax = plt.gca()
ax_test = ax.twinx()

prev_elements = None
transition = None
k_min=4

current_df = cu.get_clusters_with_keyword(date='20150618', threshold=5, keyword='charleston')

for i in range(2):

    center = 200*i+200
    bottom = 120
    current_elements = cu.make_elements(current_df, k_min=k_min)
    current_elements.layout(ax_test)
    current_elements.set_bottom(bottom)
    current_elements.set_center(center)
    current_elements.draw(ax)

    if prev_elements != None:
        print i
        cu.draw_transition(prev_elements, current_elements, transition, ax)

    prev_elements = current_elements
    current_df, transition = cu.get_next_clusters(current_df, min_likelihood=.2)
    datestr = dateutil.parser.parse(current_df['date'].iloc[0]).strftime('%B %d %Y')
    ax.text(center, bottom, datestr, va='top', ha='center', transform=None, fontsize=14)

ax.set_axis_off()
ax_test.set_axis_off()

```