

## 3.6. Variables

*There are only two kinds of languages: the ones people complain about and the ones nobody uses.*

– Bjarne Stroustrup

We have touched already some simple syntax like dereferencing variable `A` by `${A}` in `message` command: `message("This is A: ${A}")`. Cache variables was mentioned in CMake stages. Here is an overview of different types of variables with examples.

 [CMake documentation](#)

- [Language: variables](#)

 [Examples on GitHub](#)

- [Repository](#)
- [Latest ZIP](#)
- [3.6.1. Regular variables](#)
  - [3.6.1.1. Regular vs cache](#)
  - [3.6.1.2. Scope of variable](#)
  - [3.6.1.3. New scope](#)
  - [3.6.1.4. Same scope](#)
  - [3.6.1.5. Parent scope](#)
  - [3.6.1.6. From cache](#)
  - [3.6.1.7. Cache unset regular](#)
  - [3.6.1.8. Confusing](#)
  - [3.6.1.9. Names](#)
  - [3.6.1.10. Quotes](#)
  - [3.6.1.11. Dereferencing](#)
  - [3.6.1.12. Nested dereferencing](#)
  - [3.6.1.13. Types of variable](#)
  - [3.6.1.14. Create list](#)
  - [3.6.1.15. Operations with list](#)
  - [3.6.1.16. Recommendation](#)
  - [3.6.1.17. Summary](#)
- [3.6.2. Cache variables](#)

- 3.6.2.1. No scope
- 3.6.2.2. Double set
- 3.6.2.3. -D
- 3.6.2.4. Initial cache
- 3.6.2.5. Force
- 3.6.2.6. Force as a workaround
- 3.6.2.7. Cache type
- 3.6.2.8. Enumerate
- 3.6.2.9. Internal
- 3.6.2.10. Advanced
- 3.6.2.11. Use case
- 3.6.2.12. Option
- 3.6.2.13. Unset
- 3.6.2.14. Recommendation
- 3.6.2.15. Summary
- 3.6.3. Environment variables
  - 3.6.3.1. Read
  - 3.6.3.2. Set
  - 3.6.3.3. Unset
  - 3.6.3.4. Inheriting
  - 3.6.3.5. Configure step
  - 3.6.3.6. No tracking
  - 3.6.3.7. Summary