

- `make()`

make

Renders a table following a given column specification

Parameters

```
make(  
    columns: array,  
    data: array,  
    header,  
    footer,  
    hline: content,  
    toprule: arguments,  
    midrule: arguments,  
    bottomrule: arguments,  
    notes: content,  
    ..args  
)
```

columns array

Default: ()

data array

Default: ()

hline content

Content to be rendered after each row of data. Typically `table.hline(...)` but there's probably some funky uses

Default: **none**

toprule arguments

Default: `toprule`

midrule arguments

Default: `midrule`

bottomrule arguments

Default: `bottomrule`

notes **content**

Default: `note.display-list`

Variables:

- `toprule`
- `lightrule`
- `midrule`
- `bottomrule`

toprule **stroke**

The stroke of the top-rule of a table

lightrule **stroke**

The stroke of rules between rows or columns

midrule **stroke**

The stroke of the rule after the header and before the footer

bottomrule **stroke**

The stroke of the bottom-rule of a table

note

- `clear()`
- `display-numbering()`
- `make()`
- `make-numbering()`
- `set-numbering()`

Variables:

- `state`
- `numbering`
- `display`
- `display-list`

clear

Explicitly empties the stateful array tracking pending notes. Called prior to showing the table to ensure that previous notes that were forgotten about aren't accidentally absorbed into this table.

Parameters

`clear()`

display-numbering

Helper function to display the numbering for a specific table note

Parameters

```
display-numbering(key: int) -> content
```

key `int`

0-indexed position of note inside stateful array

make

This function replicates the behaviour of #footnote: It is called within the table body, and stores the content until the table notes are being rendered. It is not possible to make a hyperlink between the table body's number and the associated note.

Parameters

```
make(body: content)
```

body `content`

Content to be rendered under the table.

make-numbering

Helper functions to render the numbering of a note (either in the table body, or underneath)

Parameters

```
make-numbering() -> content
```

set-numbering

Helper function to update the numbering style of table notes.

Parameters

```
set-numbering(new) -> content
```

state `state`

Stateful array that tracks table notes that are yet to be displayed

numbering `state`

Stateful string that represents the numbering format to be used when rendering table notes. It is assumed that this does not change when there are as-of-yet undisplayed notes that are pending. Defaults of lowercase alphabetical numbering.

display `content`

Renders pending table notes in a grid-like manner (auto, 1fr), after which it empties the list of pending footnotes

display-list `content`

Renders pending table notes in a list-like manner. Each note is boxed.