DHL Group	A300 – 600 NORMAL C/L	REV 2

BEFORE START

COCKPIT PREP	COMPLETE (BOTH)
GEAR PINS and COVERS	REMOVED
SIGNS	SET
NAV SYSTEMS	NAV
FUEL QUANTITY	<<_KG>>
T.O DATA	SET (BOTH)
EFB	ON/SET/AIRPLANE MODE (BOTH)
LDG ELEVATION	_FEET SET
ALTIMETERS	_MB/_FEET (BOTH)
BRK/A-SKID	TESTED/NORM-ON
WINDOWS/DOORS	CLOSED (B0TH)
BEACON	ON
PARKING BRAKE	AS RQRD

AFTER START

PITCH TRIM	_SET
RUDDER TRIM	ZERO
SLATS/FLAPS	__/__ SET
SPOILERS	ARMED
ANTI ICE	AS RQRD
ECAM STATUS	CHECKED

BEFORE TAKE OFF

FLIGHT CONTROLS	CHECKED (BOTH)
FLIGHT INST	FMA/NO FLAG (BOTH)
BRIEFING	CONFIRMED
TRP/T.O SPEEDS	FLEX/V1-VR-V2 (BOTH)
SLATS/FLAPS	__/__ SET (BOTH)
T.O CONFIG	NORMAL FOR T.O
COURIER	ADVISED
T.O RWY	__(BOTH)
TCAS	TA/RA
AUTOBRAKE	MAX
IGNITION	CONT RELIGHT
PACKS	OFF

AFTER TAKE OFF CLIMB

LDG GEAR	UP/NEUTRAL
SLATS/FLAPS	RETRACTED
PACKS	ON
BARO REF	SET STD/PASSING FL_ (BOTH)

APPROACH

BRIEFING	CONFIRMED
ECAM STATUS	CHECKED
SIGNS	ON
ALTIMETERS/DH-DA/MDA	PASSING FL_/_SET (BOTH)
IGNITION	CONT RELIGHT
LDG ELEVATION	_FT SET
ALTIMETERS	SET QNH_/PASSING _ FT (BOTH

LANDING

COURIER	ADVISED
LDG GEAR	DOWN/THREE GREEN
AUTOBRAKE	AS RQRD
ANTI SKID	CHECKED
SLATS/FLAPS	__/__ SET
SPOILERS	ARMED

AFTER LANDING

SLATS/FLAPS	RETRACTED
SPOILERS	DISARMED
PITCH TRIM	1 NOSE UP
APU	AS RQRD
TCAS	AS RQRD
RADAR	OFF

PARKING

APU BLEED	AS RQRD
ENGINES	OFF
DIFF PRESS	CHECKED ZERO
LIGHTS and SIGNS	AS RQRD
TRANSPONDER	2000 SET/STBY
FUEL PUMPS	OFF
WINDOW and PROBE HEAT	OFF
EFB	AS RQRD (BOTH)
PARKING BRAKE and CHOCKS	AS RQRD

SECURING AIRCRAFT

NAV SYSTEMS	OFF
OXYGEN	OFF
APU BLEED	OFF
EMERGENCY EXIT LT	DISARM
APU AND BAT	OFF

