

CHARACTERISTICS OF THE INTERFACE

The characteristics of the switchboard to ensure compatibility with the nominal values of the circuits connected to the switchboard and with the conditions for electrical installation.

This document is included with the accompanying technical documentation for each switchboard.

ČSN EN 61439 – 1 ed. 3; ČSN EN 61439-2 ed. 3

Switchboard manufacturer:	AUTEL montáže, a.s.
Model:	R2-TDI1/13
Name:	20CJJ01GH001F÷5F, 20CJJ01GH001R÷5R
Serial number:	125/26
Order:	26053
Documentation No, of:	D251793302, 18.02.2026

1.	Rated voltage (U_n)	☐ 690 V ☐ 500 V ☐ 400 V ☒ 230 V ☒ 220 V ☐ 100 V ☒ 24 V ☐ 12 V
2.	Rated operational voltage (U_e); ($U_e \geq U_n$)	230V
3.	Rated insulation voltage (U_i); ($U_i \geq U_n$)	500V
4.	Rated impulse withstand voltage (U_{imp})	4 kV
5.	Rated current of the switchboard (I_nA)	13A
6.	Rated current of a circuit (I_{nc})	13A
7.	Main circuit group rated current (I_{ng})	10,4 A
8.	Rated dynamic withstand current (I_{pk})	≤ 17 kA
9.	Rated short-time withstand current (I_{cw})	≤ 10 kA/1s
10.	Rated conditional short-circuit current (I_{cc})	≤ 10 kA
11.	Rated diversity factor (RDF)	0,8
12.	Rated frequency (f_n)	☐ 50 Hz ☒ 60 Hz ☒ DC
13.	Additional requirements dependent on the application of the functional unit (e.g. type of coordination, overload characteristics)	- the supply line for the switchboard will be protected against overloading by a device restricting the current to a value not exceeding I_nA for the switchboard. The switchboard will be installed in a place with excess voltage according to point 4
14.	Degree of macro-environmental pollution	☐ 1 ☐ 2 ☒ 3 ☐ 4

15.	Methods of grounding the network for which the switchboard is designed	☐ TN-C ☒ TN-S ☐ TN-C-S ☐ TN ☒ IT ☐ TT	☐ SELV ☒ PELV ☐ FELV
16.	Internal and/or external installations	☒ inside ☐ outside	
17.	Stable or mobile	☒ stable ☐ mobile	
18.	Degree of protection against contact with hazardous live parts, ingress of solid foreign bodies and water, IP code, including the degree of protection for any distinct positions for removable and withdrawable parts	54/20	
19.	Designed for use by persons skilled in electrical engineering, competent or instructed persons	☒ Electrically skilled persons ☒ Competent persons ☐ Instructed persons	
20.	Classification of electromagnetic compatibility (EMC) Environment A – industry; B – households and light industry	☒ environment A ☐ environment B	
21.	Special operating conditions, if considered	-	
22.	External constructions	☐ uncovered switchboard ☐ switchboard with instruments behind the front wall ☐ covered switchboard ☐ cabinet switchboard ☒ modular cabinet switchboard ☐ console switchboard ☐ distribution board ☐ modular switchboard assembly ☐ wall switchboard for surface mounting ☐ wall flush-mounted switchboard ☒ floor standing switchboard	
23.	Degree of protection against mechanical shock, IK code if applicable	IK05	
24.	Type of construction	☒ fixed parts ☐ removable parts ☐ withdrawable parts	
25.	Type of internal compartment and associated degree(s) of protection, IP code (tab. 104 ČSN EN 61439 – 2 ed. 3)	method 1	
26.	Types of electrical connections of functional units (ČSN EN 61439 – 2 ed. 3) F – fixed connection D – disconnectable connection W – withdrawable connection	F – main power supply circuit F – main output circuit F – auxiliary circuits	
27.	Mounting orientation (ČSN EN 61439 - 2 ed. 3)	☒ vertical ☐ horizontal	
28.	Type of protective device(s) against short circuit	circuit breaker	
29.	Verification for protection against injury from electric current	☒ automatic disconnection from the source ☐ double insulation ☐ protection by small voltage ☐ electrical separation	
30.	Switchboard dimensions (height/width/depth)	2100x4800x800	
31.	Weight	1240	