

Linear methods of classification

Victor Kitov

Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above
- 3 Stochastic gradient descend
- 4 Regularization
- 5 Logistic regression
- 6 Fisher's linear discriminant

Linear discriminant functions

- Classification of two classes ω_1 and ω_2 .
- Linear discriminant function:


$$g(x) = w^T x + w_0$$

- Decision rule:

$$x \rightarrow \begin{cases} \omega_1, & g(x) \geq 0 \\ \omega_2, & g(x) < 0 \end{cases}$$


- Decision boundary $B = \{x : g(x) = 0\}$ is linear.

Example: decision regions



Reminder

- 1 $a = [a^1, \dots, a^D]^T$, $b = [b^1, \dots, b^D]^T$
- 2 Scalar product $\langle a, b \rangle = a^T b = \sum_{d=1}^D a_d b_d$
- 3 $a \perp b$ means that $\langle a, b \rangle = 0$
- 4 Norm $\|a\| = \sqrt{\langle a, a \rangle}$
- 5 Distance $\rho(a, b) = \|a - b\| = \sqrt{\langle a - b, a - b \rangle}$



- $p = \langle a, \frac{b}{\|b\|} \rangle$ - signed projection
- $|p| = \left| \langle a, \frac{b}{\|b\|} \rangle \right|$ - unsigned length

- Comments:

- in 2,4 and 5 most commonly used definitions of scalar product, norm and distance are given
- in general scalar product, norm and distance may have alternative definitions.

Properties

- Consider arbitrary

$$x_A, x_B \in B \Rightarrow \begin{cases} g(x_A) = w^T x_A + w_0 = 0 \\ g(x_B) = w^T x_B + w_0 = 0 \end{cases}$$

so $w^T(x_A - x_B) = 0$ and $w \perp B$.

Distance from origin

- Distance from the origin to B is equal to absolute value of the projection of $x \in B$ on $\frac{w}{\|w\|}$:

$$\left\langle x, \frac{w}{\|w\|} \right\rangle = \frac{\langle x, w \rangle}{\|w\|} = \{w^T x + w_0 = 0\} = -\frac{w_0}{\|w\|}$$

- So $\rho(0, B) = \frac{w_0}{\|w\|}$, and w_0 determines the offset from the origin.

Distance from x to B

Denote x_{\perp} - the projection of x on B , and $r = \langle \frac{w}{\|w\|}, x - x_{\perp} \rangle$ - the signed length of the orthogonal complement of x on B :

$$x = x_{\perp} + r \frac{w}{\|w\|}$$

After multiplication by w and addition of w_0 :


$$w^T x + w_0 = w^T x_{\perp} + w_0 + r \frac{\langle w, w \rangle}{\|w\|}$$

Using $w^T x + w_0 = g(x)$ and $w^T x_{\perp} + w_0 = 0$, we obtain:

$$r = \frac{g(x)}{\|w\|}$$

So from one side of the hyperplane $r > 0 \Leftrightarrow g(x) > 0$, and from the other side of the hyperplane $r < 0 \Leftrightarrow g(x) < 0$.

Illustration



Linear decision rule:

$$\hat{c}(x) = \begin{cases} \omega_1, & g(x) > 0 \\ \omega_2, & g(x) < 0 \end{cases}$$

Decision boundary: $g(x) = 0$, confidence of decision: $|g(x)| / \|w\|$.

Multiple classes classification

- Classification among $\omega_1, \omega_2, \dots, \omega_C$.
- Use C discriminant functions $g_c(x) = w_c^T x + w_{c0}$
- Decision rule:

$$\hat{c}(x) = \arg \max_c g_c(x)$$

- Decision boundary between classes ω_i and ω_j is linear:

$$(w_i - w_j)^T x + (w_{i0} - w_{j0}) = 0$$

- *Decision regions are convex.*

Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above**
- 3 Stochastic gradient descend
- 4 Regularization
- 5 Logistic regression
- 6 Fisher's linear discriminant

Linear discriminant functions

- Consider binary classification of classes ω_1 and ω_2 .
- Denote classes ω_1 and ω_2 with $y = +1$ and $y = -1$.
- Linear discriminant function: $g(x) = w^T x + w_0$,

$$\hat{\omega} = \begin{cases} \omega_1, & g(x) \geq 0 \\ \omega_2, & g(x) < 0 \end{cases}$$

- Decision rule: $y = \text{sign } g(x)$.
- Define constant feature $x_0 \equiv 1$, then $g(x) = w^T x = \langle w, x \rangle$ for $w = [w_0, w_1, \dots, w_D]^T$.
- Define the margin $M(x, y) = g(x)y$
 - $M(x, y) \geq 0 \iff$ object x is correctly classified as y
 - $|M(x, y)|$ - confidence of decision

Weights selection

- Target: minimization of the number of misclassifications Q :

$$Q(w|X) = \sum_n \mathbb{I}[M(x_n, y_n|w) < 0] \rightarrow \min_w$$


- Problem: standard optimization methods are inapplicable, because $Q(w, X)$ is discontinuous.
- Idea: approximate loss function with smooth function \mathcal{L} :

$$\mathbb{I}[M(x_n, y_n|w) < 0] \leq \mathcal{L}(M(x_n, y_n|w))$$

Approximation of the target criteria

We obtain the upper boundary on the empirical risk:

$$\begin{aligned} Q(w|X) &= \sum_n \mathbb{I}[M(x_n, y_n|w) < 0] \\ &\leq \sum_n \mathcal{L}(M(x_n, y_n|w)) = F(w) \end{aligned}$$



$$\begin{aligned} Q(M) &= (1 - M)^2 \\ V(M) &= (1 - M)_+ \\ S(M) &= 2(1 + e^M)^{-1} \\ L(M) &= \log_2(1 + e^{-M}) \\ E(M) &= e^{-M} \end{aligned}$$

Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above
- 3 Stochastic gradient descend**
- 4 Regularization
- 5 Logistic regression
- 6 Fisher's linear discriminant

Optimization

- Optimization task to obtain the weights:

$$F(w) = \sum_{i=1}^N \mathcal{L}(\langle w, x_i \rangle y_i) \rightarrow \min_w$$

- Gradient descend algorithm:

INPUT:

η - parameter, controlling the speed of convergence
stopping rule

ALGORITHM:

initialize w_0 randomly


while stopping rule is not satisfied:

$$w_{n+1} \leftarrow w_n - \eta \frac{\partial F(w_n)}{\partial w}$$

$$n \leftarrow n + 1$$


Gradient descend

- Possible stopping rules:
 - $|w_{n+1} - w_n| < \varepsilon$
 - $|F(w_{n+1}) - F(w_n)| < \varepsilon$
 - $n > n_{max}$
- Suboptimal method of minimization in the direction of the greatest reduction of $F(w)$:



Recommendations for use

- Convergence is faster for normalized features
 - feature normalization solves the problem of «elongated valleys»



Convergence acceleration

Stochastic gradient descend method

set the initial approximation w_0

calculate $\hat{F} = \sum_{i=1}^n \mathcal{L}(M(x_i, y_i | w_0))$

iteratively until convergence \hat{Q}_{approx} :

- 1 select random pair (x_i, y_i)
- 2 recalculate weights: $w_{n+1} \leftarrow w_n - \eta_n \mathcal{L}'(\langle w_n, x_i \rangle y_i) x_i y_i$
- 3 estimate the error: $\varepsilon_i = \mathcal{L}(\langle w_{n+1}, x_i \rangle y_i)$
- 4 recalculate the loss $\hat{F} = (1 - \alpha) \hat{F} + \alpha \varepsilon_i$
- 5 $n \leftarrow n + 1$

Variants for selecting initial weights

- $w_0 = w_1 = \dots = w_D = 0$
- For logistic \mathcal{L} (because the horizontal asymptotes):
 - randomly on the interval $[-\frac{1}{2D}, \frac{1}{2D}]$
- For other functions \mathcal{L} :
 - randomly
- $w_i = \frac{\text{cov}[x^i, y]}{\text{var}[x^i]}$ (these are regression weights, given that x^i are uncorrelated).

Discussion of SGD

Advantages

- Easy to implement
- Works online
- A small subset of learning objects may be sufficient for accurate estimation

Discussion of SGD

Advantages

- Easy to implement
- Works online
- A small subset of learning objects may be sufficient for accurate estimation

Drawbacks

- Suboptimal - converges to local optimum
- Needs selection of η_n :
 - too big: divergence
 - too small: very slow convergence
- Overfitting possible for large D and small N
- When $\mathcal{L}(u)$ has left horizontal asymptotes (e.g. logistic), the algorithm may «get stuck» for large values of $\langle w, x_i \rangle$.

Examples

Quadratic loss: $\mathcal{L}(M) = (M - 1)^2$

Perceptron of Rosenblatt: $\mathcal{L}(M) = [-M]_+$.

Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above
- 3 Stochastic gradient descend
- 4 Regularization**
- 5 Logistic regression
- 6 Fisher's linear discriminant

Regularization for SGD

- L_2 -regularization for upperbound approximation:

$$F^{reg}(w) = F(w) + \lambda \|w\|^2$$

- SGD weights modification: $w \leftarrow w(1 - \eta 2\lambda) - \eta \frac{\partial}{\partial w} F(w)$

Regularization

- Useful technique to control the complexity of the model, can be applied to any algorithm.

$$F^{reg}(w) = F(w) + \lambda R(w)$$

- λ is the parameter controlling strength of regularization = model complexity.
- Examples:

$$R(w) = \|w\|_1 = \sum_{d=1}^D |w^d|$$

$$R(w) = \|w\|_2^2 = \sum_{d=1}^D (w^d)^2$$

$$R(w) = \alpha \|w\|_1 + (1 - \alpha) \|w\|_2, \alpha \in [0, 1]$$

L_1 norm

- $\|w\|_1$ regularizer will do feature selection.
- Consider

$$Q(w) = F(w) + \lambda \sum_{d=1}^D |w_d|$$

- if $\lambda > \sup_w \left| \frac{\partial F(w)}{\partial w_i} \right|$, then it becomes optimal to set $w_i = 0$
- For smaller C more inequalities will become active.

L_2 norm

- $\|w\|_1$ regularizer will do feature selection.
- Consider $R(w) = \|w\|_2^2 = \sum_d w_d^2$

$$Q(w) = F(w) + \lambda \sum_{d=1}^D w_d^2$$

- $\frac{\partial R(w)}{\partial w_i} = 2w_i \rightarrow 0$ when $w_i \rightarrow 0$.

Illustration





Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above
- 3 Stochastic gradient descend
- 4 Regularization
- 5 Logistic regression**
- 6 Fisher's linear discriminant

Binary classification

- Linear classifier:

$$\text{score}(\omega_1|x) = w^T x$$

- +relationship between score and class probability is assumed:

$$p(\omega_1|x) = \sigma(w^T x)$$

where $\sigma(z) = \frac{1}{1+e^{-z}}$ - sigmoid function

Binary classification: estimation

Using the property $1 - \sigma(z) = \sigma(-z)$ obtain that

$$p(y = +1|x) = \sigma(w^T x) \implies p(y = -1|x) = \sigma(-w^T x)$$

So for $y \in \{+1, -1\}$

$$p(y|x) = \sigma(y\langle w, x \rangle)$$

Therefore ML estimation can be written as:

$$\prod_{i=1}^N \sigma(\langle w, x_i \rangle y_i) \rightarrow \max_w$$

Loss function for 2-class logistic regression


For binary classification $p(y|x) = \sigma(\langle w, x \rangle y)$ $w = [\beta'_0, \beta]$,
 $x = [1, x_1, x_2, \dots, x_D]$.

Estimation with ML:

$$\prod_{i=1}^n \sigma(\langle w, x_i \rangle y_i) \rightarrow \max_w$$

which is equivalent to

$$\sum_i^n \ln(1 + e^{-\langle w, x_i \rangle y_i}) \rightarrow \min_w$$



It follows that logistic regression is linear discriminant estimated with loss function $\mathcal{L}(M) = \ln(1 + e^{-M})$.

Multiple classes

Multiple class classification:

$$\begin{cases} \text{score}(\omega_1|x) = w_1^T x \\ \text{score}(\omega_2|x) = w_2^T x \\ \dots \\ \text{score}(\omega_C|x) = w_C^T x \end{cases}$$

+relationship between score and class probability is assumed:

$$p(\omega_c|x) = \text{softmax}(w_c^T x | x_1^T x, \dots, x_C^T x) = \frac{\exp(w_c^T x)}{\sum_i \exp(w_i^T x)}$$

Multiple classes

Weights ambiguity:

w_c , $c = 1, 2, \dots, C$ defined up to shift v :

$$\frac{\exp((w_c - v)^T x)}{\sum_i \exp((w_i - v)^T x)} = \frac{\exp(-v^T x) \exp(w_c^T x)}{\sum_i \exp(-v^T x) \exp(w_i^T x)} = \frac{\exp(w_c^T x)}{\sum_i \exp(w_i^T x)}$$

To remove ambiguity usually $v = w_C$ is subtracted.

Estimation with ML:

$$\begin{cases} \prod_{n=1}^N \text{softmax}(w_{y_n}^T x_n | x_1^T x, \dots, x_C^T x) \rightarrow \max_{w_1, \dots, w_{C-1}} \\ w_C = \mathbf{0} \end{cases}$$

Table of contents

- 1 Geometric foundations of linear classification
- 2 Estimation of error rate from above
- 3 Stochastic gradient descend
- 4 Regularization
- 5 Logistic regression
- 6 Fisher's linear discriminant**

Problem statement

- Standard linear classification decision rule

$$\hat{c} = \begin{cases} 1, & w^T x \geq -w_0 \\ 2, & w^T x < -w_0 \end{cases}$$

is equivalent to

- 1 dimensionality reduction to 1-dimensional space (defined by w)
 - 2 making classification in this space
- Idea of Fisher's LDA: find direction, giving most discriminative projections.

Possible realization


- Classification between ω_1 and ω_2 .
- Define $C_1 = \{i : x_i \in \omega_1\}$, $C_2 = \{i : x_i \in \omega_2\}$ and

$$m_1 = \frac{1}{N_1} \sum_{n \in C_1} x_n, \quad m_2 = \frac{1}{N_1} \sum_{n \in C_2} x_n$$

$$\mu_1 = w^T m_1, \quad \mu_2 = w^T m_2$$

Naive solution:

$$\begin{cases} (\mu_1 - \mu_2)^2 \rightarrow \max_w \\ \|w\| = 1 \end{cases}$$




Fisher's LDA

- Define projected within class variances:

$$s_1 = \sum_{n \in C_1} (w^T x_n - w^T m_1)^2, \quad s_2 = \sum_{n \in C_2} (w^T x_n - w^T m_2)^2$$

- Fisher's LDA criterion: $\frac{(\mu_1 - \mu_2)^2}{s_1^2 + s_2^2} \rightarrow \max_w$



Equivalent representation

$$\begin{aligned}
 \frac{(\mu_1 - \mu_2)^2}{s_1^2 + s_2^2} &= \frac{(w^T m_1 - w^T m_2)^2}{\sum_{n \in C_1} (w^T x_n - w^T m_1)^2 + \sum_{n \in C_2} (w^T x_n - w^T m_2)^2} \\
 &= \frac{[w^T (m_1 - m_2)]^2}{\sum_{n \in C_1} [w^T (x_n - m_1)]^2 + \sum_{n \in C_2} [w^T (x_n - m_2)]^2} \\
 &= \frac{w^T (m_1 - m_2)(m_1 - m_2)^T w}{w^T \left[\sum_{n \in C_1} (x_n - m_1)(x_n - m_1)^T + \sum_{n \in C_2} (x_n - m_2)(x_n - m_2)^T \right] w} \\
 &= \frac{w^T S_B w}{w^T S_W w}
 \end{aligned}$$

$$S_B = (m_1 - m_2)(m_1 - m_2)^T,$$

$$S_W = \sum_{n \in C_1} (x_n - m_1)(x_n - m_1)^T + \sum_{n \in C_2} (x_n - m_2)(x_n - m_2)^T$$

Fisher's LDA solution

$$Q(w) = \frac{w^T S_B w}{w^T S_W w} \rightarrow \max_w$$

Using property that $\frac{d}{dw} (w^T A w) = 2Aw$ for any $A \in \mathbb{R}^{K \times K}$, $A^T = A$

$$\frac{dQ(w)}{dw} \propto 2S_B w [w^T S_W w] - 2 [w^T S_B w] S_W w = 0$$

which is equivalent to

$$[w^T S_W w] S_B w = [w^T S_B w] S_W w$$

So

$$w \propto S_W^{-1} S_B w \propto S_W^{-1} (m_1 - m_2)$$