

APP CRS	Rwy Idg	11570
284°	THRE	13
	Apt Elev	13

RNAV (RNP) Y RWY 28R
SAN FRANCISCO INTL (SFO)



GPS required. RF required. For inoperative ALSF, increase RNP 0.10* all Cats visibility to RVR 4500 and RNP 0.30# all Cats visibility to 1½ mile. For uncompensated Baro-VNAV systems, procedure NA below 2°C (36°F) or above 54°C (130°F).


*Missed Approach requires minimum climb of 250 feet per NM to 2000.
#Missed Approach requires minimum climb of 325 feet per NM to 2500.

ALSF-2

MISSED APPROACH: Climb to 3000 on track 284° to VIKYU and hold.

ATIS 113.7 115.8 118.85 135.45	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8	CLNC DEL 118.2
--------------------------------------	-------------------------------	------------------------------------	------------------	-------------------



3000	VIKYU	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 68)					
↑ tr 284°							
		RW28R	FABLA	JOSUF	DONNG	GUTTS	BATKE
		284°	730	1263	1800	284°	3000
		2.1 NM	1.7 NM	1.7 NM	5.2 NM	4.4 NM	GP 3.00° TCH 55
CATEGORY	A	B	C	D			
RNP 0.10 DA*	299/40		286 (300-¾)				
RNP 0.30 DA#	415/45		402 (500-¾)				
AUTHORIZATION REQUIRED							

SW-2, 03 APR 2014 to 01 MAY 2014

SW-2, 03 APR 2014 to 01 MAY 2014