

## Title

**txt** — Prints string and values of scalar expressions or macros in dynamic document. By default, the command writes a text paragraph. The primary purpose of the command is writing dynamic text to interpret analysis results in the dynamic document. This command belongs to [Weaver](#) package, but it also supports the [MarkDoc](#) package. The syntax for both packages is similar, but the **txt** command behaves differently based on which package is in use. If Weaver log is on, **txt** functions for Weaver package only. This document only describes the **txt** command in Weaver package. For using the command in [MarkDoc](#) package [see the MarkDoc documentation on GitHub wiki](#)

## Syntax

Prints dynamic text on the Weaver log or smcl log. The **code** subcommand prints the output "as is" in the dynamic document.

```
txt [code] [display_directive [display_directive [...]]]
```

where the *display\_directive* is

```
Weaver Markup
"double-quoted string "
`"compound double-quoted string "`
[%fmt] [=] exp
_skip(#)
_column(#)
_newline[(#)]
_dup(#)
'
''
```

## Description

**txt** prints dynamic text i.e. strings and values of scalar expressions or macros in the Weaver or the smcl log-file. **txt** also prints output from the user-written Stata programs. Any of the supported markup languages can be used to alter the string and scalar expressions. This command is to some extent similar to **display** command in Stata. For example, it can be used to carry out a mathematical calculation by typing **txt 1+1**. It also supports many of the display directives as well.

Note that in contrast to the [display](#) command that prints the [scalar](#) unformatted, the **txt** command uses the default **%10.2f** format for displaying the scalar. This feature helps the users avoid specifying the format for every scalar, due to popularity of this format. However, specifying the format expression can overrule the default format. For example:

```
. scalar num = 10.123
. txt "The value of the scalar is " %5.1f num
```

The example above will print the scalar with only 1 decimal number. This feature only supports scalar interpretation and does not affect the [macro](#) contents.

## Display directives

The supported *display\_directive* s are used in do-files and programs to produce formatted output. The directives are

<a href="#">Weaver Markup</a>	A simplified markup language for annotating the content of the HTML log
"double-quoted string "	displays the string without the quotes
`"compound double-quoted string "`	display the string without the outer quotes; allows embedded quotes
[% <i>fmt</i> ] [=] <b>exp</b>	allows results to be formatted; see <a href="#">[U] 12.5 Formats: Controlling how data are displayed</a> .
_ <b>skip</b> (#)	skips # columns
_ <b>column</b> (#)	skips to the #th column
_ <b>newline</b>	goes to a new line
_ <b>newline</b> (#)	skips # lines
_ <b>dup</b> (#)	repeats the next directive # times
,	displays one blank between two directives

,,

places no blanks between two directives

## Mathematical notations

The **txt** command can be used for writing mathematical notations in Weaver package, both in HTML and LaTeX log files. Writing mathematical notations in the HTML log is made possible by including **MathJax** engine, a JavaScript-based engine for rendering LaTeX notations in HTML format. To do so, notations should begin with `"\"` and end with `"\"` for rendering notations within the text and double dollar sign `"$"` or alternatively, the `"\[` and `"\"` for rendering notations in a separate line. For more information in this regard, see [mathematical notations](#) documentation.

When Weaver package is running, the **code** subcommand appends the dynamic text to the

## Examples

As a hand calculator:

```
. txt 2 * 2
```

As might be used in do-files and programs:

```
. sysuse auto
. summarize price
. txt "mean of Price variable is " r(mean) " and SD is " %9.3f r(sd)
```

If the text only includes string and macro, the double quotations can be ignored. The **txt** command will interpret all of the *display\_directives* and scalars as string (so it's not recommended):

```
. local n 9.9
. txt Not recommended, but you may also print the value of `n' without double quote
```

## Author

**E. F. Haghish**

Center for Medical Biometry and Medical Informatics  
University of Freiburg, Germany

and

Department of Mathematics and Computer Science  
University of Southern Denmark  
haghish@imbi.uni-freiburg.de

[Weaver Homepage](#)

Package Updates on [Twitter](#)

---

This help file was dynamically produced by [MarkDoc Literate Programming package](#)