



Incident report analysis

Summary	The organization experienced a DoS attack, which compromised the internal network for two hours. The organization's network services stopped responding due to an incoming flood of ICMP packets. Normal internal network traffic could not access any network resources. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services. The company's cybersecurity team then investigated the security event. They found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. This vulnerability allowed the malicious attacker to overwhelm the company's network through a denial of service (DoS) attack. To address this security event, the network security team implemented: 1. A new firewall rule to limit the rate of incoming ICMP packets 2. Source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets 3. Network monitoring software to detect abnormal traffic patterns 4. An IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics
Identify	The company's cybersecurity team investigated the security event. They found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. This vulnerability allowed the malicious attacker to overwhelm the company's network through a denial of service (DoS) attack, which compromised the internal network for two hours.

Protect	To address this security event, the network security team implemented: 1. A new firewall rule to limit the rate of incoming ICMP packets 2. An IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics
Detect	To detect new DoS attacks in the future, the team will use a network monitoring software to detect abnormal traffic patterns, a IDS/IPS system to monitor and filter out some ICMP traffic based on suspicious characteristics, source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and a SIEM tool to monitor for possible future attacks.
Respond	The incident management team responded by blocking incoming ICMP packets and stopping all non-critical network services offline. For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. Then, the team will analyze network logs to check for suspicious and abnormal activity. The team informed upper management of this event and they will contact customers and appropriate legal authorities, if applicable.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. Critical network services should be restored first. Once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: