

Bachelor Thesis

Comparison of Hamming- and Variation of Information-Loss
based structured learning on the Multicut Problem

Jan Lammel

19. Februar 2016

Table of Contents

1 Introduction

2 Theory

3 Experiments and Results

4 Conclusion

Segmentation




Motivation Variation of Information



- Hamming Loss strongly dependend on exact path of segmentation
- But: Path of segmentation often not unique

- Idea VOI: Consider labels of segmentation and penanlize area-dependend

Region Adjacency Graph (RAG)



- Image partitioned into **Superpixel** (SP) via SLIC [2]
- Each Superpixel $\hat{=}$ **Node** in RAG
- Nodes of adjacent SP are linked by an **Edge**

Multicut Problem (MP)

$$\begin{aligned} \min_y \quad & \sum_{y_e \in E} \langle w, \beta_e \rangle \cdot y_e \\ \text{s.t.} \quad & y - \sum_{y_i \in P(y)} y_i \leq 0 \quad \forall y \in E \end{aligned}$$

- w : Weights to be learned
- β_e : Features of edge e
- y_e : Activity of edge e
- Constraint to enforce consistency

Stochastic Gradient with RF Feature

- Varying configurations:
 - Domain Feature Space
 - Constraint on RF Feature
 - Subgradient Descent with/without RF Feature
- Results:
 - Decrease of VOI Loss leads to decline of Hamming Loss in Trainingsset
 - Rate of decrease sensible to configuration,
besides strong fluctuations due to stochastic process
 - Loss decrease on Trainingset \propto Loss increase on Testset
 \Rightarrow Overfit of training data


Stochastic Gradient without RF Feature

- Varying configurations:
 - Domain Feature Space
 - Constraint on N^4 Feature
- Results:
 - VOI Loss decrease on Trainingset of approximately 4%
 - Change of Loss on Testset within 1σ range of error

Cross Validation Measurement 10


- Cross validation to minimize measurement errors
 - Results on Testset:
 - $\mathcal{L}_H: \frac{\text{StochGrad}}{\text{SubGrad}} = 0.989 \pm 0.005$
 - $\mathcal{L}_{VOI}: \frac{\text{StochGrad}}{\text{SubGrad}} = 1.0025 \pm 0.0084$
- No significant change

Explanation by SLIC I




- Ground Truth Edge
- Ground Truth Area
- Structure
- Background

Explanation by SLIC I




- Ground Truth Edge
- Ground Truth Area
- Structure
- Super Pixel Edges
- Background

Explanation by SLIC I



Structure
 Super Pixel- &
Ground Truth Edges

Explanation by SLIC I



Conclusion


- Stochastic Gradient with RF Feature leads to Overfit of training data
- No significant change without RF Feature
 - Bad Ground Truth compensated by SLIC
 - SLIC provides just important edges
 - Difficulty of exact segmentation path is gone
 - Examination on Pixel-level would be interesting


- [1] Sebastian Nowozin, Christoph H. Lampert, *Structured Learning and Prediction in Computer Vision*, 2011.
- [2] Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Süsstrunk, *SLIC Superpixels Compared to State-of-the-art Superpixel Methods*, 2011
- [3] D. Martin, C. Fowlkes, D. Tal and J. Malik, *A Database of Human Segmented Natural Images and its Application to Evaluating Segmentation Algorithms and Measuring Ecological Statistics*, Proc. 8th Int'l Conf. Computer Vision, July 2001
- [4] Yaroslav Ganin and Victor Lempitsky, *N^4 -Fields: Neural Network Nearest Neighbor Fields for Image Transforms*, Skolkovo Institute of Science and Technology, 2014
- [5] Piotr Dollár and C. Lawrence Zitnick, *Structured Forests for Fast Edge Detection*, ICCV 2013
- [6] Ullrich Köthe, *Vision with Generic Algorithms*, Image Processing and Analysis Library, Version 1.10.0
- [7] Thorsten Beier, *Inferno*, <https://github.com/DerThorsten/inferno>
- [8] P. Arbeláez, M. Maire, C. Fowlkes and J. Malik, *Contour Detection and Hierarchical Image Segmentation*, IEEE TPAMI, Vol. 33, No. 5, pp. 898–916, May 2011
- [9] Saining Xie and Zhuowen Tu, *Holistically-Nested Edge Detection*, CoRR, abs/1504.06375, 2015
- [10] Bjoern Andres, Joerg H. Kappes, Thorsten Beier, Ullrich Köthe and Fred A. Hamprecht, *Probabilistic Image Segmentation with Closedness Constraints* ICCV, Proceedings, (2011), 2611 - 2618
- [11] Jörg Hendrik Kappes, Markus Speth, Björn Andres, Gerhard Reinelt, Christoph Schnörr, *Globally Optimal Image Partitioning by Multicuts*, EMMCVPR, Springer, 2011
- [12] Jörg Hendrik Kappes, Markus Speth, Gerhard Reinelt, Christoph Schnörr, *Higher-order Segmentation via Multicuts*, 2013
- [13] Kappes, J.; Swoboda, P.; Savchynskyy, B.; Hazan, T. and Schnörr, C., *Probabilistic Correlation Clustering and Image Partitioning Using Perturbed Multicuts*, In Proc. SSVM, Springer, LNCS , 2015


- [14] Margret Keuper, Evgeny Levinkov, Nicolas Bonneel, Guillaume Lavoué, Thomas Brox, Bjoern Andres, *Efficient Decomposition of Image and Mesh Graphs by Lifted Multicuts*, eprint arXiv:1505.06973, 05/2015
- [15] Sebastian Nowozin and Christoph H. Lampert, *Global Connectivity Potentials for Random Field Models*, IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2009)
- [16] S. Beucher and F. Meyer, *Mathematical Morphology in Image Processing*, Marcel Dekker, 1992, ch. 12
- [17] Jordi Pont-Tuset and Pablo Arbelaez and Jonathan T. Barron and Ferran Marqués and Jitendra Malik, *Multiscale Combinatorial Grouping for Image Segmentation and Object Proposal Generation*, CoRR, abs/1503.00848, 2015


Questions











Algorithm 1 Get Gradient Descent Direction

```
1: procedure GETGRADIENTDESCENTDIRECTION(#Perturbs, σ, w)
2:   σ: Noise standard deviation
3:   w: Current Weight Wector
4:
5:    $\Delta x = 0$ 
6:   for n = 1...#Perturbs do
7:     Generate Noise  $\in \mathcal{N}(0, \sigma^2)$  und add to w
8:     Calculate Loss on current Training Sample
9:      $\Delta x = \Delta x + \text{Noise} * \text{Loss}$ 
10:     $\Delta x = -\Delta x / \#Perturbs$ 
11:   return  $\Delta x$ 
```

Algorithm 2 Line Search and update Weights

```
1: procedure LINESEARCHANDTAKESTEP( $\eta$ , It,  $w$ ,  $\Delta x$ ,  $\Delta w_{\text{prev}}$ )
2:    $\eta$ : Stepwidth
3:   It: Current Iteration
4:    $w$ : Current weight vector
5:    $\Delta x$ : Gradient Descent Direction
6:    $\Delta w_{\text{prev}}$ : Step of previous iteration
7:
8:    $\eta_{\text{eff}} = \eta / \text{It}$ 
9:
10:  for  $n = \{0.1, 0.5, 1.0, 5.0, 10.0\}$  do
11:    Varied Weight Vector  $w_{\text{var}} = w + \eta_{\text{eff}} \cdot \Delta x \cdot n + m \cdot w_{\text{prev}}$ 
12:    Calculate mean Loss  $\mathcal{L}$  on entire Training Set
13:    from  $w_{\text{var}}$ 
14:    if  $\mathcal{L} < \mathcal{L}_{\text{best}}$  then
15:       $\mathcal{L}_{\text{best}} = \mathcal{L}$ 
16:      Save  $w_{\text{best}} = w_{\text{var}}$ 
17:      Break
18:    Memorize  $\mathcal{L}$  and associated varied weight vector
19:   $w = w_{\text{var}}$ , where regarding Loss is minimal
20:  return  $w$ 
```

$$\mathcal{L}_i(y_i, y_i^*) = \begin{cases} \mathbb{I}[y_i \neq y_i^*] \cdot \alpha_{\text{over}} & \text{if } y_i^* = 0 \\ \mathbb{I}[y_i \neq y_i^*] \cdot \alpha_{\text{under}} & \text{if } y_i^* = 1 \end{cases} \quad \forall y_i \in E$$

$$\mathcal{L}_H(y, y^*) = \sum_{y_i \in E} \mathcal{L}_i(y_i, y_i^*)$$

$$\mathcal{L}_{\text{VOI}}(y, y^*) = H_y + H_{y^*} - 2 \cdot I(y, y^*)$$

$$H_y = \mathbb{E}[\hat{I}(y)] = - \sum_{l \in y} p(l) \cdot \log_e(p(l))$$

$$I(y, y^*) = \sum_{l_1 \in y} \sum_{l_2 \in y^*} p(l_1, l_2) \cdot \log_e \left(\frac{p(l_1, l_2)}{p(l_1)p(l_2)} \right)$$