

Part 1:

```

*** Booting Zephyr OS build zephyr-v20701 ***
MAIN STARTED
Network interface found: 0x2000089c
PAN ID set to: 0x1234
Channel set to: 15
Interface is up
Network configuration initialized successfully
Socket created successfully: 0
Receiver address set to: fd00::2
Sent: temp=20
[00:00:00.328,918] «[0m<inf> ieee802154_nrf5: nRF5 802154 radio initialized.[0m
[00:00:00.353,820] «[0m<inf> net_config: Simple Sender 802.15.4.[0m
[00:00:00.459,838] «[0m<inf> net_config: IPv6 address: fd00::1.[0m
Sent: temp=21
Sent: temp=22
Sent: temp=23
Sent: temp=24
Sent: temp=25
Sent: temp=26
Sent: temp=27
Sent: temp=28
Sent: temp=29
Sent: temp=30
Sent: temp=31
Sent: temp=32
Sent: temp=33
Sent: temp=34
Sent: temp=35
Sent: temp=36
Sent: temp=37
Sent: temp=38
Sent: temp=39
Sent: temp=40
Sent: temp=41
Sent: temp=42
Sent: temp=43
Sent: temp=44
Sent: temp=45
[]

```

```

Sent: temp=45
*** Booting Zephyr OS build zephyr-v20701 ***
MAIN STARTED
Network interface found: 0x2000089c
PAN ID set to: 0x1234
Channel set to: 15
Interface is up
Network configuration initialized successfully
Socket created successfully: 0
Socket bound to port: 12345
Waiting for data...
[00:00:00.337,951] «[0m<inf> ieee802154_nrf5: nRF5 802154 radio initialized.[0m
[00:00:00.362,884] «[0m<inf> net_config: Simple Receiver 802.15.4.[0m
[00:00:00.468,841] «[0m<inf> net_config: IPv6 address: fd00::2.[0m
Received: temp=21
Waiting for data...
Received: temp=22
Waiting for data...
Received: temp=23
Waiting for data...
Received: temp=24
Waiting for data...
Received: temp=25
Waiting for data...
Received: temp=26
Waiting for data...
Received: temp=27
Waiting for data...
Received: temp=28

```

Part 2 & 3:

Server:

```
Waiting for CoAP request...
Received 13 bytes
RX MID=10599
GET /sensor -> temp=27
Sent CoAP response: temp=27
RESP MID=10599
Waiting for CoAP request...
Received 20 bytes
RX MID=10600
POST /action -> action_state=1
Sent CoAP response: action=on
RESP MID=10600
Waiting for CoAP request...
Received 13 bytes
RX MID=10601
GET /sensor -> temp=28
Sent CoAP response: temp=28
RESP MID=10601
Waiting for CoAP request...
Received 20 bytes
RX MID=10602
POST /action -> action_state=0
Sent CoAP response: action=off
RESP MID=10602
Waiting for CoAP request...
Received 13 bytes
RX MID=10603
GET /sensor -> temp=29
Sent CoAP response: temp=29
RESP MID=10603
Waiting for CoAP request...
```

Client:

```
Sending CoAP request to server...
REQ MID=10599
sendto successful, bytes=13
Waiting for CoAP response...
Received 12 bytes
Received ACK for message ID: 10599
ACK MID=10599
RTT=14 ms MID=10599
Received payload: temp=27
Button was pressed, action_state will be toggled!
Sending CoAP request to server...
REQ MID=10600
sendto successful, bytes=20
Waiting for CoAP response...
Received 14 bytes
Received ACK for message ID: 10600
ACK MID=10600
RTT=15 ms MID=10600
Received payload: action=on
Sending CoAP request to server...
REQ MID=10601
sendto successful, bytes=13
Waiting for CoAP response...
Received 12 bytes
Received ACK for message ID: 10601
ACK MID=10601
RTT=14 ms MID=10601
Received payload: temp=28
Button was pressed, action_state will be toggled!
Sending CoAP request to server...
REQ MID=10602
sendto successful, bytes=20
Waiting for CoAP response...
Received 15 bytes
Received ACK for message ID: 10602
ACK MID=10602
RTT=15 ms MID=10602
Received payload: action=off
Sending CoAP request to server...
REQ MID=10603
sendto successful, bytes=13
Waiting for CoAP response...
Received 12 bytes
Received ACK for message ID: 10603
```