

Recorded documentation issues — not yet fixed

A register of every wrong, unverified or inconsistent fact found in this documentation while executing `PLAN_gio.md`, with the exact file and line. **Nothing in this file has been changed in the docs** — these were deliberately recorded, not fixed, because each needs either a decision from the documentation owner or confirmation from the SalesPlay API team. Written so that whoever picks an item up can go straight to the file.

Recorded: 2026-09-16 (line numbers as of that date). Source of truth for these entries: `PLAN_gio.md` §11.

Summary

Ref	Problem	Where	Size	Who can resolve it
11.1	Placeholder example values ("string", 0) in generated reference pages	49 of 53 pages under <code>docs/API-reference/</code> (root cause: <code>api_spec.yaml</code> has example: on 122 of 792 string fields)	1,071 occurrences	Docs team, using real API captures (backlog G1)
11.2	Two orphaned pages that contradict the current pages	<code>docs/API-reference/Webhooks.md</code> , <code>docs/guides/authentication.md</code>	2 files, 647 lines	Docs owner — delete (backlog S7, S8)
11.3	Wrong or unverified facts in the guides	9 entries, listed with file and line below	9	API team to confirm; docs team to edit
11.3b	Guide code samples that call endpoints the API does not have	<code>product.md</code> , <code>categories.md</code> , <code>order-integration.md</code> , <code>receipt.md</code> , <code>webhooks-guide.md</code> , <code>oauth.md</code> , <code>personal-access-tokens.md</code>	15 method+path combinations, /webhookss ×38	API team to confirm the real paths; then rewrite the samples
11.4	Inconsistent field names across endpoints, not called out anywhere	<code>api_spec.yaml</code> and the generated pages	5 name pairs	Docs team — add the callout (<code>DOCS_IMPROVEMENT_PLAN.md</code> fix 1.5); API team if the names are to be unified

Why these matter more than usual now: the site is optimised for AI assistants (see `PLAN_gio.md`), which means assistants will repeat these pages *more* confidently. A wrong path or field in the docs becomes a wrong path or field in a developer's code.

Endpoints affected — by API category

Every issue in this register, listed by the API category (sidebar group) and the exact endpoint (method + path) it touches. Refs point to the detailed sections below. "all" = every operation in that category.

API category	Endpoint	Issues
Webhooks	GET /webhooks	11.1 placeholders (9) · 11.2 contradicted by orphaned <code>Webhooks.md</code> · 11.3b guide uses <code>/webhookss</code> and <code>/id</code> · 11.4 <code>created_at</code> / <code>updated_at</code>
	POST /webhooks	11.1 (8) · 11.2 · 11.3b · 11.4
	DELETE /webhooks	11.1 (5) · 11.2 · 11.3b
	<i>(does not exist)</i> PUT /webhooks	11.3 guide documents it — API returns <code>405</code>
Categories	GET /category	11.1 (12) · 11.3b guide calls <code>GET /categories</code> , <code>GET /categories/{id}</code> · 11.4 <code>created_at</code> and <code>updated_date</code> on the same response
	POST /category	11.1 (11) · 11.3b guide calls <code>POST /categories</code> , <code>PUT /categories/{id}</code> · 11.4
	DELETE /category	11.1 (7) · 11.3b guide calls <code>DELETE /categories/{id}</code>
Sub Categories	GET /sub_category	11.1 (8) · 11.4 <code>created_at</code> + <code>updated_date</code>
	POST /sub_category	11.1 (11) · 11.4
	DELETE /sub_category	11.1 (8)
Measurements	GET /measurements	11.1 (12) · 11.4 <code>created_at</code> + <code>updated_date</code>
	POST /measurements	11.1 (11) · 11.4 response has <code>updated_at</code> while the list has <code>updated_date</code>
	DELETE /measurements	11.1 (4)
Taxes	GET /taxes	11.1 (18) · 11.4
	POST /taxes	11.1 (15) · 11.4
	DELETE /taxes	— (clean)
Customers	GET /customers	11.1 (41) · 11.4 <code>created_at</code> / <code>updated_at</code>
	POST /customers	11.1 (76)
	DELETE /customers	11.1 (6)
Employee	GET /employee	11.1 (17)
Suppliers	GET /suppliers	11.1 (16) · 11.4
	POST /suppliers	11.1 (35) · 11.4
	DELETE /suppliers	11.1 (4)
Products	GET /products	11.1 (9) · 11.3 <code>limit</code> "Maximum: 100" unverified (251 accepted) · 11.3b guide calls <code>GET /products/{id}</code> · 11.4 <code>created_date</code> / <code>updated_date</code> , <code>shop_id</code>

API category	Endpoint	Issues
	POST /products	11.1 (96) · 11.3b guide calls PUT /products/{id} · 11.4 request uses store_id (only place in the API) and created_at / updated_at ; response uses product_id
	(does not exist) DELETE /products	11.3b guide documents DELETE /products/{id} — no such endpoint in the spec
Product Image	POST /product_image	— (clean)
	DELETE /product_image	11.1 (4) · 11.4 product_id
Receipts	GET /receipts	11.1 (19) · 11.3 date-format wording · 11.3b guide calls GET /receipts/{id} · 11.4 shop_id , product_id
	GET /void_receipts	11.1 (52) · 11.3b guide calls GET /receipts/void?... (wrong path, query string) · 11.4
	GET /credit_note_and_refund	11.1 (66) · 11.4
	POST /credit_note_and_refund	11.1 (34) · 11.4
Orders	GET /orders	11.1 (40) · 11.3b guide calls GET /orders/{id} · 11.4 shop_id , product_id
Shops	GET /shops	11.1 (12) · 11.4 updated_date only (no created_*), request filter shop_ids
Payment Types	GET /payment_types	11.1 (32) · 11.4 created_date / updated_date , shop_id
	POST /payment_types	11.1 (15)
	DELETE /payment_types	11.1 (8)
Order Types	GET /order_types	11.1 (12) · 11.4 created_at + updated_date
	POST /order_types	11.1 (11)
	DELETE /order_types	11.1 (7)
Modifiers	GET /modifiers	11.1 (35) · 11.4 created_date / updated_date
	DELETE /modifiers	11.1 (7)
Inventory	GET /inventory	11.1 (20) · 11.4 shop_id / shop_ids , product_id
	POST /inventory	— (clean) · 11.4 shop_id , product_id
GRN	GET /grn	11.1 (49) · 11.4 shop_id / shop_ids , product_id
	POST /grn	11.1 (42) · 11.4
Purchase Orders	GET /purchase_orders	11.1 (30) · 11.4 shop_id / shop_ids , product_id
Online Orders	POST /online_orders	11.1 (138 — the worst page) · 11.4 shop_id
	GET /online_order_status	11.1 (11) · 11.3 description says "path parameter" — the id goes in the JSON body

API category	Endpoint	Issues
	POST /cancel_online_order	11.1 (8)
Shifts	GET /shifts	11.1 (23) · 11.4 created_at , shop_id
	GET /drawer_transaction	11.1 (25) · 11.4 shop_id / shop_ids
Timecards	GET /timecards	11.1 (21) · 11.4 shop_id / shop_ids
POS Devices	GET /pos_devices	11.1 (15) · 11.4 shop_id
Merchant	GET /merchant	— (clean) · 11.4 created_at
Not in the spec	POST /oauth/token	11.3b used by oauth.md , personal-access-tokens.md , authentication.md (4×) — exists in the Postman collection, never verified, absent from api_spec.yaml
All list endpoints (24 GET s that take limit)	GET /category ... GET /void_receipts	11.3 pagination: default 10 documented, no maximum verified; only GET /products declares maximum: 100
All endpoints	every operation	11.3 rate limit "300 / 300 s" unverified (360 requests in 54 s all 200) · 11.3 error body in errors-guide.md doesn't match the real {"errors":{...}} envelope · 11.3 X-Request-ID header does not exist

Numbers in parentheses after 11.1 are the count of "string" / 0 placeholders on that endpoint's page.

Clean pages (no placeholder issue): DELETE /taxes , POST /product_image , POST /inventory , GET /merchant .

Suggested order

- 11.3b — the largest and most damaging: a developer following the product or category guide today writes code against endpoints that return 404 / 405 . Needs one answer from the API team ("do /products/{id} and PUT exist, or is POST <collection> the only create/update?") and then a rewrite of the samples.
- 11.3 — nine one-line facts; most are already confirmed wrong in DOCS_BACKLOG.md and only need the edit.
- 11.2 — two deletions.
- 11.1 — mechanical once real values are captured; one example: per spec field, then python gen_api_docs.py .
- 11.4 — a callout box on the affected pages; no API change needed.

Checked 2026-09-16 against the current files. Line numbers are as of that date.

11.1 Placeholder examples in generated reference pages (audit A4)

Where: 49 of the 53 generated pages under docs/API-reference/<group>/*.md — 1,071 occurrences of "string" and 13 pages with 0 as a number placeholder, in the *Example request* and *Response JSON* blocks. Per endpoint (count = placeholders on that page):

API category	Endpoint	Page	Count
Online Orders	POST /online_orders	online-orders/place-online-order.md	138
Products	POST /products	products/create-product.md	96
Customers	POST /customers	customers/create-customer.md	76
Receipts	GET /credit_note_and_refund	receipts/get-credit-notes.md	66
Receipts	GET /void_receipts	receipts/get-void-receipts.md	52
GRN	GET /grn	grn/get-grn.md	49
GRN	POST /grn	grn/create-grn.md	42
Customers	GET /customers	customers/get-customers.md	41
Orders	GET /orders	orders/get-orders.md	40
Modifiers	GET /modifiers	modifiers/get-modifiers.md	35
Suppliers	POST /suppliers	suppliers/create-supplier.md	35
Receipts	POST /credit_note_and_refund	receipts/create-credit-note.md	34
Payment Types	GET /payment_types	payment-types/get-payment-types.md	32
Purchase Orders	GET /purchase_orders	purchase-orders/get-purchase-orders.md	30
Shifts	GET /drawer_transaction	shifts/get-drawer-transactions.md	25
Shifts	GET /shifts	shifts/get-shifts.md	23
Timecards	GET /timecards	timecards/get-timecards.md	21
Inventory	GET /inventory	inventory/get-inventory.md	20
Receipts	GET /receipts	receipts/get-receipts.md	19
Taxes	GET /taxes	taxes/get-taxes.md	18
Employee	GET /employee	employee/get-employees.md	17
Suppliers	GET /suppliers	suppliers/get-suppliers.md	16
Payment Types	POST /payment_types	payment-types/create-payment-type.md	15
POS Devices	GET /pos_devices	pos-devices/get-pos-devices.md	15
Taxes	POST /taxes	taxes/create-tax.md	15
Categories	GET /category	categories/get-categories.md	12
Measurements	GET /measurements	measurements/get-measurements.md	12
Order Types	GET /order_types	order-types/get-order-types.md	12
Shops	GET /shops	shops/get-shops.md	12
Categories	POST /category	categories/create-category.md	11
Measurements	POST /measurements	measurements/create-measurement.md	11

API category	Endpoint	Page	Count
Online Orders	GET /online_order_status	online-orders/get-online-order-status.md	11
Order Types	POST /order_types	order-types/create-order-type.md	11
Sub Categories	POST /sub_category	sub-categories/create-sub-category.md	11
Products	GET /products	products/get-products.md	9
Webhooks	GET /webhooks	webhooks/get-webhook.md	9
Online Orders	POST /cancel_online_order	online-orders/cancel-online-order.md	8
Payment Types	DELETE /payment_types	payment-types/delete-payment-type.md	8
Sub Categories	GET /sub_category	sub-categories/get-sub-categories.md	8
Sub Categories	DELETE /sub_category	sub-categories/delete-sub-category.md	8
Webhooks	POST /webhooks	webhooks/create-webhook.md	8
Categories	DELETE /category	categories/delete-category.md	7
Modifiers	DELETE /modifiers	modifiers/delete-modifier.md	7
Order Types	DELETE /order_types	order-types/delete-order-type.md	7
Customers	DELETE /customers	customers/delete-customer.md	6
Webhooks	DELETE /webhooks	webhooks/delete-webhook.md	5
Measurements	DELETE /measurements	measurements/delete-measurement.md	4
Product Image	DELETE /product_image	product-image/delete-image.md	4
Suppliers	DELETE /suppliers	suppliers/delete-supplier.md	4

Clean (no placeholders): DELETE /taxes , POST /product_image , POST /inventory , GET /merchant .

Example, docs/API-reference/products/get-products.md lines 48, 54, 66, 72, 101, 107: "product_ids": "string" , "cursor": "string" .

Root cause: the pages are generated by gen_api_docs.py from api_spec.yaml ; where a field has no example: value the generator prints the type name. The spec has 122 example: lines against 792 type: string fields.

Why it matters for AI assistants: an assistant copies the example verbatim; a developer sends "limit": 0 or "product_ids": "string" and receives INVALID_VALUE , then blames the documentation. The fix is tracked as DOCS_BACKLOG.md G1 (add example: to every spec field from real captures).

11.2 Orphaned duplicate pages that contradict the current pages (audit A9)

File	Size	Not linked from	Contradicts	How
docs/API-reference/Webhooks.md ("Webhook API Suite")	420 lines	sidebars.js (only API-reference/webhooks/* are listed) — reachable by URL and by search only	docs/API-reference/webhooks/get-webhook.md , create-webhook.md , delete-webhook.md , overview.md	Documents the parameters as query-string (### Query Parameters , line 27; GET .../webhooks?id=wh_abc123 , lines 39–102), whereas the current pages state the verified behaviour: <i>parameters are read from the JSON body, even on GET; query-string parameters are ignored</i> (get-webhook.md lines 24–25). Uses created_at in its response.
docs/guides/authentication.md ("Get Your Credentials" / "Authentication")	227 lines	sidebars.js — reachable by URL and by search only	docs/guides/personal-access-tokens.md and docs/guides/oauth.md	Same content as both current pages merged, but a separate older copy; any correction made to the current pages (header format, token refresh at POST /oauth/token , lines 143–151) is not reflected here. The file also starts with a UTF-8 BOM.

Why it matters for AI assistants: two pages on the same site giving different answers; the assistant picks one at random and cites it. Tracked as DOCS_BACKLOG.md S7 and S8 (delete both).

11.3 Wrong or unverified facts in the guides (audit A10)

Fact as written	API category / endpoint(s)	File and line	Status	Correct fact (to be confirmed)
"Every API response (success or failure) includes an <code>X-Request-ID</code> header. Log this ID..."	All categories — every endpoint	<code>docs/guides/errors-guide.md</code> line 63 (Debugging Tips)	Wrong — the live API sends no such header (verified 2026-09-14, <code>DOCS_BACKLOG.md</code> E1)	Remove; if the API team provides a correlation header, document that one
"Log Request IDs: Store the <code>X-Request-ID</code> for every SalesPlay interaction..."	All categories — every endpoint	<code>docs/guides/going-live.md</code> line 36	Wrong — same	Same
"### 4. Update a Webhook (PUT)" with <code>curl -X PUT .../webhookss/WEBHOOK_ID</code> and five language samples	Webhooks — <code>PUT /webhooks</code> (does not exist; <code>GET/POST/DELETE /webhooks</code> are the real ones)	<code>docs/guides/webhooks-guide.md</code> lines 243–321	Wrong — <code>PUT /webhooks</code> returns 405 (<code>DOCS_BACKLOG.md</code> W1). Note also the typo <code>webhookss</code> in the URL (line 251)	"To change a webhook, delete it and create it again" — unless the API team confirms an update method
"Per Account: 300 requests / 300 seconds"	All categories — every endpoint (tested with <code>GET /merchant</code>)	<code>docs/API-reference/rate-limits.md</code> line 17; repeated in <code>docs/guides/errors-guide.md</code> line 50	Unverified — the page itself notes (line 20) that 360 requests in 54 seconds all returned <code>200</code> ; no <code>429</code> or <code>Retry-After</code> has ever been observed	Ask the API team for the real limit and the <code>429</code> behaviour; until then label the figure "published policy, not observed"
"check that the Personal Access Token you are using has the required scope (e.g., <code>orders.manage</code>)" "	All categories — authentication on every endpoint	<code>docs/guides/errors-guide.md</code> line 66	Wrong — Personal Access Tokens have no scopes; OAuth apps have permissions named like <code>RECEIPTS_READ</code> (<code>DOCS_BACKLOG.md</code> E2)	Rewrite the tip around OAuth app permissions
Date format described only as "(Y-m-d H:i:s) 24 hours format"	All list endpoints with date filters: <code>GET /receipts</code> , <code>/void_receipts</code> , <code>/credit_note_and_refund</code> ,	field tables in all generated pages (e.g. <code>get-products.md</code> lines 44–47) and <code>docs/API-</code>	Incomplete — verified accepted formats are <code>YYYY-MM-DD HH:MM:SS</code> and <code>YYYY-MM-DD</code> ;	State the two accepted formats and the rejection

Fact as written	API category / endpoint(s)	File and line	Status	Correct fact (to be confirmed)
	/orders , /category , /sub_category , /measurements , /taxes , /customers , /employee , /suppliers , /products , /shops , /payment_types , /order_types , /modifiers , /grn , /online_order_status , /shifts , /drawer_transaction , /timecards , /purchase_orders , /pos_devices ; plus every created_at / updated_at field in requests	reference/date-time- format.md	ISO-8601 is rejected with Invalid date Format. (DOCS_BACKLOG.md D1)	
"The request to get the order status should include the order reference ID as a path parameter."	Online Orders — GET /online_order_status	api_spec.yaml → GET /online_order_status description (rendered on docs/API- reference/online- orders/get-online-order- status.md under the intro paragraph)	Wrong — the endpoint takes system_unique_ids in the JSON body like every other endpoint; there is no path parameter	Replace with "Send the system unique IDs in the JSON body" — found 2026- 09-16 while regenerating the pages
Error payload shown as { "code": "validation_failed", "message": "...", "request_id": "req_..." }	All categories — every endpoint (400 / 401 / 429 responses)	docs/guides/errors- guide.md lines 33–43 (Handling Error Responses)	Wrong — the live API returns { "errors": { "code", "details", "field" } } with codes like UNAUTHORIZED , INVALID_VALUE (verified; this is what all 53 reference pages show)	Replace with the verified body; ties in with the x- Request-ID row
"Test in sandbox environments before deploying to production. Support for development, staging, and production endpoints."	All categories — base URL of every endpoint	was docs/Introduction.md (Key Features card) — removed in Step 6; the same claim remains in docs/guides/going- live.md line 45 ("Once your testing in the sandbox environment is complete")	Unverified — no sandbox base URL is documented anywhere; the only known host is the production API	Confirm with the API team whether a sandbox exists; if so document its base URL, if not remove the

Fact as written	API category / endpoint(s)	File and line	Status	Correct fact (to be confirmed)
				sentence in going-live
Pagination "default limit 10", old "max 250"	24 list endpoints that accept <code>limit</code> (all <code>GET</code> list operations); only <code>GET /products</code> declares <code>maximum: 100</code>	<code>docs/API-reference/pagination.md</code> ; <code>limit</code> rows on generated pages ("Maximum: 100")	Unverified — 251 and 500 were accepted in testing (<code>DOCS_BACKLOG.md</code> P2)	Confirm the real ceiling with the API team

11.3b Guide code samples that call endpoints the API does not have (found 2026-09-16, Step 5)

The six-language code samples in four guides were written REST-style and do not match `api_spec.yaml` (which has no `PUT` , no `/ {id}` paths, and uses `POST <collection>` as create-or-update with the ID in the JSON body). Every method+path used by the guides was compared with the spec:

Guide	Section	Code calls	In the spec	Notes
docs/guides/product.md	Get Products (single)	GET /products/{id}	GET /products with product_ids in the JSON body	no /{id} path exists
	Edit Product	PUT /products/{id}	POST /products (updates when product_code exists)	PUT is not in the spec (cf. PUT /webhooks → 405)
	Delete Product	DELETE /products/{id}	—	there is no delete-product endpoint in the spec
docs/guides/categories.md	all four sections	POST/GET/PUT/DELETE /categories[{id}]	POST/GET/DELETE /category (singular; ID in body)	path is wrong in every sample
docs/guides/order-integration.md	Get Orders (single)	GET /orders/{id}	GET /orders with order_numbers in the body	
docs/guides/receipt.md	Get Receipts (single)	GET /receipts/{id}	GET /receipts with receipt_numbers in the body	
	Get Void Receipts	GET /receipts/void?{query}	GET /void_receipts with a JSON body	path and parameter style both wrong
docs/guides/webhooks-guide.md	all sections	.../v1.0/webhookss (38 occurrences), .../webhookss/WEBHOOK_ID	/webhooks with id in the body	typo plus /{id} style
docs/guides/oauth.md , personal-access-tokens.md	token request / refresh	POST /oauth/token (4×)	not in api_spec.yaml	may well exist — unverified, not in the spec

Consequence for Step 5: the "send X to URL" sentence was added only to the four sections whose method+path is in the spec (POST /products , GET /products , GET /orders , GET /receipts), so the documentation does not restate a wrong path. Resolving this table (rewrite the samples against the spec, or confirm with the API team that these REST paths exist) is the largest single item in Phase 0.

11.4 Inconsistent field names not called out anywhere (audit A12)

Counted in api_spec.yaml (the source the reference pages are generated from). Exact endpoints:

Concept	Name used	API category → endpoint (request / response)
Creation timestamp	created_at	Responses: Categories GET /category , POST /category · Sub Categories GET /sub_category , POST /sub_category · Measurements GET /measurements , POST /measurements · Taxes GET /taxes , POST /taxes · Customers GET /customers · Suppliers GET /suppliers , POST /suppliers · Order Types GET /order_types · Shifts GET /shifts · Webhooks GET /webhooks , POST /webhooks · Merchant GET /merchant . Requests: POST /category , POST /sub_category , POST /measurements , POST /taxes , POST /suppliers , POST /products ; created_at_min/max filters on every list endpoint
	created_date	Responses: Products GET /products · Payment Types GET /payment_types · Modifiers GET /modifiers
Update timestamp	updated_at	Responses: Customers GET /customers · Webhooks GET /webhooks , POST /webhooks · Measurements POST /measurements (but its GET says updated_date) . Request: POST /products ; updated_at_min/max filters on GET /products , /suppliers , /shops , /payment_types , /modifiers
	updated_date	Responses: Categories GET /category · Sub Categories GET /sub_category · Measurements GET /measurements · Order Types GET /order_types · Products GET /products · Payment Types GET /payment_types · Modifiers GET /modifiers · Shops GET /shops
Shop identifier	shop_id	Responses: GET /products , /payment_types , /pos_devices , /receipts , /void_receipts , /credit_note_and_refund , /orders , /shifts , /drawer_transaction , /timecards , /grn , /inventory , /purchase_orders . Requests: POST /products (in shops[]) , POST /online_orders , POST /grn , POST /inventory , POST /credit_note_and_refund ; filter on GET /receipts , /void_receipts , /credit_note_and_refund , /orders
	shop_ids (filter)	Requests: GET /shops , /inventory , /grn , /purchase_orders , /drawer_transaction , /timecards
	store_id	Request: Products POST /products → variants[].shops[].store_id Only (api_spec.yaml line ≈1945; create-product.md line 70 and examples). Every other endpoint says shop_id
Product identifier	id	list responses: GET /products (and all other list endpoints use id for their own record)
	product_id	Responses: Products POST /products · Receipts GET /receipts , /void_receipts , /credit_note_and_refund (line items) · Orders GET /orders · GRN GET /grn · Inventory GET /inventory · Purchase Orders GET /purchase_orders . Requests: POST /credit_note_and_refund , POST /grn , POST /inventory , DELETE /product_image (as product_code)

So the same record can show created_at on one endpoint and created_date on another (e.g. POST /measurements → updated_at ; GET /measurements → updated_date ; GET /category carries created_at **and** updated_date on the same object), and a product is created with store_id but every other endpoint says shop_id .

Why it matters for AI assistants: an assistant "normalises" the names and invents created_at on a list response or shop_id on create-product; the developer's code then reads an undefined field. Already noted as problem F in DOCS_IMPROVEMENT_PLAN.md (\$2) with fix 1.5 (a callout on the overview and each affected page) — that callout is **not** added by this plan.