

Business Requirements Document —

Notifications

Platform: Zebu Helpdesk — Staff Portal (Flutter, Android/iOS) **Module:** Notifications (Inbox) **Document Version:** 1.0 (Initial Edition) **Date:** August 2026 **Status:** In Progress (case-by-case) **Classification:** Internal Use Only

Document Control

Field	Value
Document Title	Notifications — Business Requirements Document
Module Scope	The agent's notification Inbox : the notification feed grouped per ticket/task, filter tabs, live search, per-card open / mark-read / delete swipe actions, and the bulk mark-all-read / delete-all menu. This document specifies functional behaviour only — visual styling (colours, themes, animation) is out of scope.
Audience	Quality Assurance, Product Management, Engineering
Source Truth	Flutter source at <code>lib/features/notifications/notifications_screen.dart</code> , <code>lib/models/app_notification.dart</code>

6. Functional Requirements

6.1 NT-001 — Inbox list, filter tabs, and search

Field	Value
Description	The Inbox lists the agent's notifications collapsed into one card per ticket/task, with filter tabs, a live search, infinite scroll, and loading / empty states.
Acceptance Criteria	- The app bar title reads Inbox; when there are conversations it shows a count below as "N conversation(s)" - Filter tabs are shown in this order: All, Unread, Tickets, Tasks, Mentions; the Unread tab carries the live unread count as a badge - Selecting a tab filters the feed client-side: Unread → objects with any unread activity, Tickets → ticket objects, Tasks → task objects, Mentions → objects with a "mention" event, All → everything - A search box with the placeholder Search notifications filters live (debounced ~250 ms) by object id, activity label, or actor name (case-insensitive) - The feed loads pages progressively and keeps pulling pages when a filter hides most of a page (until a screenful of cards or no more) - While the first page loads, a loading skeleton is shown; on error (with no data) an error view with retry is shown - When there are no matching notifications, an empty state reading No notifications with the hint You are all caught up. is shown - The feed supports pull-to-refresh
Priority	High

6.2 NT-002 — Grouped notification card

Field	Value
Description	Each card collapses all of the agent's notifications for a single ticket/task, showing the latest activity and how many were collapsed.
Acceptance Criteria	- Each card shows the object reference (Ticket #N or Task #N), the latest activity message, and the latest activity's relative time - A card with any unread activity is visually marked as unread (an unread rail and emphasised text) - When more than one activity is collapsed, an "N updates" pill is shown - An event chip is shown for the latest activity's type, mapped as: message→Reply, note→Note, assigned→Assigned, transfer→Transferred, status→Status, mention→Mention, overdue→Overdue, new_unassigned→Unassigned - The actor's name is shown when present
Priority	Medium

6.3 NT-003 — Opening a notification

Field	Value
Description	Tapping a card marks the whole object's notifications read and opens the ticket or task.
Acceptance Criteria	- Tapping a card marks all of the agent's notifications for that object as read (server-side) and refreshes the unread count - The app then navigates to the object — the task detail for a task card, the ticket detail for a ticket card - On returning from the detail, the feed refreshes so the card's unread state is cleared - If the mark-read call fails, navigation still proceeds
Priority	High

6.4 NT-004 — Swipe actions (mark read / delete)

Field	Value
Description	Cards can be swiped to mark all of the object's notifications read or to delete them.
Acceptance Criteria	- Swiping a card right marks all of that object's notifications read in place (the card is not removed); this direction is available only when the card has unread activity - Swiping a card left deletes all of that object's notifications; the card is removed immediately (optimistically) and the deletes are sent to the server - If a delete fails, the rows are restored and an error toast is shown - After a mark-read or delete, the unread count is refreshed
Priority	Medium

6.5 NT-005 — Inbox bulk menu

Field	Value
Description	An overflow menu marks the whole inbox read or deletes all notifications.

Field	Value
Acceptance Criteria	- The app-bar overflow menu offers Mark all read and Delete all (destructive) - Mark all read marks every notification read and refreshes the feed and unread count - Delete all first shows a confirmation reading Delete all notifications? with the message This cannot be undone. and a Delete all confirm; on confirm it deletes everything and refreshes - Failures show an error toast
Priority	Medium

Document in progress — additional cases added after individual approval.