

Business Requirements Document — Settings (Server)

Platform: Zebu Helpdesk — Staff Portal (Flutter, Android/iOS) **Module:** Settings (Server) **Document Version:** 1.0 (Initial Edition)
Date: August 2026 **Status:** In Progress (case-by-case) **Classification:** Internal Use Only

Document Control

Field	Value
Document Title	Server Settings — Business Requirements Document
Module Scope	The Server Settings screen, which re-points the app at a different helpdesk backend: the base-URL field with validation, the connectivity status, and the test / save / reset actions. This document specifies functional behaviour only — visual styling (colours, themes, animation) is out of scope.
Audience	Quality Assurance, Product Management, Engineering
Source Truth	Flutter source at <code>lib/features/settings/server_settings_screen.dart</code> , <code>lib/core/network/server_config.dart</code> , <code>lib/core/config.dart</code>

6. Functional Requirements

6.1 ST-001 — Server URL field and status

Field	Value
Description	The screen shows the current helpdesk base URL for editing, validates it, previews the resolved API dispatcher, and shows the device's connectivity.
Acceptance Criteria	- The app bar title reads Server settings - A live status row shows Device online or Device offline reflecting current connectivity - A Helpdesk base URL field is pre-filled with the currently saved server (hint https://ticket.example.com) - The URL is validated: empty → Enter a server URL; unparseable/host-less → Enter a valid URL (e.g. https://host:port); a scheme other than http/https → URL must start with http:// or https:// - Below the field, the resolved API dispatcher URL for the entered (or current) base URL is shown - A note explains that changing the server signs the agent out and requires signing in again against the new backend
Priority	High

6.2 ST-002 — Test connection

Field	Value
Description	A test action checks whether the entered server is reachable.

Field	Value
Acceptance Criteria	- A Test connection button validates the URL first, then pings the entered server (forcing a fresh check) - While testing, a busy indicator is shown - On success a toast reads Server is reachable; on failure a toast reads Could not reach {url}
Priority	Medium

6.3 ST-003 — Save server

Field	Value
Description	Saving persists the new server and re-points the app at it.
Acceptance Criteria	- A Save server button validates the URL first, then persists it (the value survives app restarts) - Saving rebuilds the API client so every subsequent request targets the new server - On success a toast reads Server updated. Sign in again to continue. - The Test/Save/Reset actions are disabled while a test or save is in flight
Priority	High

6.4 ST-004 — Reset to default

Field	Value
Description	A reset action restores the default server.
Acceptance Criteria	- A Reset to default action restores the built-in default server, rebuilds the API client, and repopulates the field with the default value - On reset a toast reads Reset to default server
Priority	Low

Document in progress — additional cases added after individual approval.