

Business Requirements Document — Tasks

Platform: Zebu Helpdesk — Staff Portal (Flutter, Android/iOS) **Module:** Tasks **Document Version:** 1.0 (Initial Edition) **Date:** August 2026 **Status:** In Progress (case-by-case) **Classification:** Internal Use Only

Document Control

Field	Value
Document Title	Tasks — Business Requirements Document
Module Scope	The Tasks surfaces of the Staff Portal: the Tasks list (filter tabs, search, filter/sort, multi-select bulk actions, export, layout toggle, scroll pagination), the Task detail screen (collapsing header with progress and blocked state, Conversation / Details / Activity tabs, the reply/note composer, subtasks, dependencies, and the : action set — close/reopen, assign, transfer, priority, collaborators, tags), and the Create task screen (including creating a task linked to a ticket). This document specifies functional behaviour only — visual styling (colours, themes, animation) is out of scope.
Audience	Quality Assurance, Product Management, Engineering
Source Truth	Flutter source at <code>lib/features/tasks/tasks_list_screen.dart</code> , <code>lib/features/tasks/task_detail_screen.dart</code> , <code>lib/features/tasks/create_task_screen.dart</code> , <code>lib/features/tasks/widgets/{task_row,task_card}.dart</code> , <code>lib/widgets/{entity_list_row,message_composer}.dart</code>

6. Functional Requirements

6.1 TS-001 — Tasks list: filter tabs with per-tab counts

Field	Value
Description	The Tasks list is organised into seven filter tabs shown as a row of chips, each carrying a live count. Selecting a chip switches the list to that view; the tabs are also swipeable as pages. The app bar shows the title "Tasks" and the active view's total count.
Acceptance Criteria	- Exactly seven tabs are shown, in this left-to-right order: Open, All, Overdue, Completed, Created by me, Collaborator, My Tasks - Each tab shows a count badge; the count is computed with the same query the list runs for that view (so a badge can't disagree with the list); a tab whose count fails to load shows no badge - The My Tasks and Collaborator views are additionally scoped to open tasks only (matching the web nav's open-only counts) - Tapping a chip makes it the active view, moves the pager to it, and re-fetches; the seven views are also swipeable, and a settled swipe adopts the swiped-to view - Swiping is disabled while in multi-select mode (TS-007) - The app bar title reads Tasks with the active view's total count shown below it as "N total" - Opening the Tasks tab from another screen's request (e.g. a dashboard tile) preselects the requested view
Priority	High

6.2 TS-002 — Live search over the fetched rows

Field	Value
Description	A search box narrows the visible rows as the user types, applied client-side to the rows already fetched for the active view; it does not trigger a new server fetch.
Acceptance Criteria	- The search box shows the placeholder Search tasks with a search icon - Typing filters the visible rows live, debounced (~300 ms); submitting applies immediately - A row matches when the typed text is contained in any of: task number, title, assignee, or department name - The match is case-insensitive; #, commas, spaces and the ₹ symbol are stripped from both the query and the compared values before matching - Clearing the search box restores the full fetched set for the current view/filter - When the query matches no rows, the empty state (TS-006) is shown - Search does not trigger a server re-fetch
Priority	High

6.3 TS-003 — Filter & sort sheet

Field	Value
Description	A filter button opens a sheet to set a create-date range, sort order, and facet filters (Department, Priority, Agent, Tag). Applying re-queries the list.
Acceptance Criteria	- The filter button indicates an active state when any create-date range or facet filter is set (sort alone does not count) - The sheet offers a date range, a sort selector, and facet pickers for Department, Priority, Agent, Tag - The sort options are exactly: Most Recently Updated, Most Recently Created, Due Date, Task Number, Longest Thread; default is Most Recently Created - Sort order is ascending for Due Date (soonest first) and descending for the others; Longest Thread is ordered by the server - On Apply, the selections are applied and the list re-fetches; cancelling changes nothing - Facet filters and the date range are also enforced on the fetched rows (kept only when the row's department/priority/agent name matches the selected facet and its created date falls inside the range) - The filter/sort sheet's own behaviour (date presets, sort chips, chip-vs-searchable-dropdown facets, Apply/Reset draft) is specified in the Global BRD, GL-005
Priority	High

6.4 TS-004 — Task list row content

Field	Value
Description	Each row summarises one task: number, title, status, assignee, relative created time, meaningful priority, department, due date, progress, and a blocked flag.
Acceptance Criteria	- Every row shows: the task #number, the title, the status, the assignee name (or Unassigned when absent), and the created time as a relative string with a tooltip of the full created date-time - A priority chip is shown only for meaningful priorities (a "Normal"/empty priority is suppressed) - Meta chips are shown for the department (when present) and the due date (when present); the due-date chip is marked danger when the task is overdue - The progress percentage is shown when greater than 0 - A blocked task (an open dependency) is flagged with a "Blocked" indicator - Tapping a row opens that task's detail screen (TS-011)

Field	Value
Priority	High

6.5 TS-005 — Comfortable / compact layout toggle

Field	Value
Description	An app-bar action toggles the list between a comfortable (card) layout and a compact (dense) layout.
Acceptance Criteria	- An app-bar toggle switches between Comfortable view and Compact view; its tooltip names the layout it will switch to - The choice applies immediately to the visible list
Priority	Low

6.6 TS-006 — Scroll pagination and empty state

Field	Value
Description	The list fetches tasks page by page and appends more as the user scrolls; a skeleton shows during first load and an empty state shows when there are no matching rows.
Acceptance Criteria	- The first load shows a loading skeleton - Scrolling fetches and appends further pages until the server has no more - When the active view/filter/search yields no rows, an empty state reads No tasks with the hint Try a different filter or search. - Changing view, date range, sort, or facet filters re-fetches from the first page
Priority	Medium

6.7 TS-007 — Multi-select mode

Field	Value
Description	Long-pressing a row enters multi-select mode for bulk actions.
Acceptance Criteria	- Long-pressing any row toggles its selection and enters selection mode - In selection mode, tapping a row toggles its selection instead of opening it - A selection bar offers select all / deselect all for the currently visible rows - The app bar switches to a selection app bar showing the selected count and a cancel control that clears the selection and exits - Page swiping between tabs is disabled while in selection mode - Exiting selection mode returns to the normal app bar
Priority	Medium

6.8 TS-008 — Bulk actions on selected tasks

Field	Value
Description	From the selection app bar the user can act on all selected tasks: mark complete, reopen, assign to an agent, set priority, or transfer department.

Field	Value
Acceptance Criteria	- The selection app bar's primary action is Mark complete (closes every selected task) - An overflow menu offers: Reopen, Assign to agent..., Set priority..., and Transfer department... - The value-based actions first prompt for the target (agent / priority / department) then apply it to every selected task - Bulk operations run per task; on completion a toast reports the count, e.g. "Completed 5 tasks" or "Assigned 4 tasks · 1 failed" - After a bulk action the selection is cleared, the list refreshes, and the per-tab counts reload - (There is no bulk delete for tasks.)
Priority	Medium

6.9 TS-009 — Export the visible tasks

Field	Value
Description	An export action downloads the active view's tasks (narrowed by the active search) as PDF or Excel.
Acceptance Criteria	- An export menu in the app bar offers PDF and Excel - Export gathers the active view's rows (paged from the server, capped at 2000) and applies the active search/date/facet narrowing - The exported columns are exactly: #, Title, Status, Priority, Department, Assignee, Progress, Created, Due - On success a toast reports the count and format, e.g. "Exported 20 tasks as Excel" - When there are no rows to export, a toast reads No tasks to export - On failure, the server error is shown as a toast (or "Saved file but could not open it automatically" when only the open step failed)
Priority	Medium

6.10 TS-010 — Opening a task / cross-tab filter request

Field	Value
Description	Tapping a row opens the task detail; the row's data is passed along so the detail can show a due date its own endpoint omits. The list also honours a view-filter requested from another screen.
Acceptance Criteria	- Tapping a row (outside selection mode) navigates to the task detail for that task, passing the list row as seed data - A view request arriving from another tab while the list is already open jumps the list to the requested view and clears the request - A task mutated elsewhere causes the list to refetch so the row is not stale
Priority	High

6.11 TS-011 — Task detail: load, loading, and error states

Field	Value
Description	Opening a task loads its record, conversation thread, activity events, subtasks, and dependencies. Because the detail endpoint omits the due date, it is grafted from the list row passed in. A loading view is shown during the fetch and an error view with retry on failure.

Field	Value
Acceptance Criteria	- On open, the screen fetches the task, its thread, activity events, subtasks, and dependencies - When the detail response lacks a due date but the seed row (same task) has one, the seed's due date and overdue flag are used - While loading, a loading view is shown under an app bar titled Task - On failure (or missing task), an error view with retry is shown - After sending a message, the data refreshes in place without the full-screen loader
Priority	High

6.12 TS-012 — Task detail header (title, status, progress, blocked)

Field	Value
Description	A collapsing header shows the task's title and status chips, a progress bar, and a blocked banner when applicable; the app bar always shows the task number and reveals the title once the header scrolls away.
Acceptance Criteria	- The app bar shows #number at all times - The collapsing header shows the title, a status chip, a priority chip (when set), and an Overdue chip when overdue - A progress bar with a "Progress: N%" line is shown when progress is greater than 0 - When the task is blocked, a banner reading Blocked by an open dependency is shown - Once the header scrolls behind the app bar, the title also appears as a second line in the app bar
Priority	Medium

6.13 TS-013 — Task detail tabs

Field	Value
Description	The detail body is organised into three tabs: Conversation, Details, Activity. A progress bar shows while an action runs.
Acceptance Criteria	- Three tabs are shown in this order: Conversation, Details, Activity, selectable by tap or swipe - A linear progress indicator is shown while a task action is in flight - The reply/note composer is shown only on the Conversation tab (TS-016) and hides the instant the user swipes or taps away
Priority	High

6.14 TS-014 — Conversation tab

Field	Value
Description	The Conversation tab shows the task thread as chat bubbles, distinguishing staff replies/notes from incoming messages, grouping consecutive messages from one sender, and dividing the thread by day. The newest message is kept in view.

Field	Value
Acceptance Criteria	- Each thread entry is shown as a bubble; staff entries (replies and internal notes) sit on one side and incoming messages on the other with the sender's avatar - An internal note and an agent reply each carry a distinguishing role label; a plain incoming message carries none - Consecutive entries from the same sender on the same side and day are grouped so name/avatar shows once per run - A day separator is shown when the day changes, labelled Today, Yesterday, or the date - Each bubble shows the message body, any attachments, and a relative timestamp; an empty entry shows (no content) - Attachments open in the shared attachment viewer, and links / inline images in the body are tappable (see Global BRD, GL-001 and GL-002) - The conversation auto-scrolls to the newest entry on open and when a new entry arrives - An empty thread shows No messages yet
Priority	High

6.15 TS-015 — Message bubble actions (Reply / Copy)

Field	Value
Description	Long-pressing a message bubble opens an action sheet to reply to (quote) that message or copy its text.
Acceptance Criteria	- Long-pressing a bubble opens a sheet with Reply and Copy text - Reply loads that entry into the composer as a quote and shows a "Replying to <sender>" banner with a cancel control - Copy text copies the message's plain text and confirms with "Copied"; it is disabled when the message has no text
Priority	Low

6.16 TS-016 — Reply / internal-note composer

Field	Value
Description	On the Conversation tab an agent with reply permission gets a composer to post a public reply or an internal note, with rich text, attachments, emoji, saved-reply/FAQ insertion, and a full-screen editor.
Acceptance Criteria	- The composer is shown only on the Conversation tab and only when the agent has reply permission on the task's department (TS-026); otherwise no composer is shown - A toggle switches between public reply and internal note; the placeholder (reply mode reads "Reply to this task...") and send icon reflect the mode - A + menu offers Camera, Photo, File, Saved replies, and Insert FAQ; an emoji picker is available; attachments are shown as removable chips - An expand control opens a full-screen editor sharing the same draft - Send posts a reply (with alert) or an internal note; on success the thread refreshes in place and the Tasks list is signalled to refresh - Send is disabled when the draft is empty and no attachment is attached; a send shows a busy indicator - On send failure an error toast is shown and the draft (and attachments) are kept
Priority	High

6.17 TS-017 — Details tab: attributes, information, custom fields

Field	Value
Description	The Details tab lists the task's attributes, read-only information, and any custom fields. Editable attribute rows open the matching picker when the agent has permission.
Acceptance Criteria	- An Attributes section shows Status, Priority, Department, and Assignee; each is tappable to edit only with the matching permission (status→close/reopen, priority→edit, department→transfer, assignee→assign), otherwise read-only - An empty editable row shows a placeholder prompt (e.g. "Set priority", "Assign") - An Information section shows read-only Number, Created, Updated, and Due - A Custom fields section is shown only when the task has custom field values, listing each name/value
Priority	High

6.18 TS-018 — Subtasks

Field	Value
Description	The Details tab lists the task's subtasks and lets an agent with create permission add one.
Acceptance Criteria	- A Subtasks section lists the task's subtasks as cards (number, title, status, assignee, progress); an empty list shows No subtasks - Tapping a subtask opens its own task detail - An Add subtask action is shown only when the agent has create permission; it opens a sheet with Title and Description fields - Both fields are required — an empty one shows Title and description are required and blocks creation - On success the subtask is created (inheriting the parent's department), the sheet closes, and the task reloads
Priority	Medium

6.19 TS-019 — Dependencies

Field	Value
Description	The Details tab lists the task's dependencies (blocking tasks) and lets an agent with edit permission add or remove them. A dependency that is still open blocks the task.
Acceptance Criteria	- A Dependencies section lists each dependency as a card showing the blocking task's number and title (or "Dependency #id" when the blocker isn't expanded) and whether it is Required or Optional; an open blocker is indicated as blocking - An empty list shows No dependencies - An Add dependency action (edit permission only) opens a dialog to enter a Blocking task id; a non-numeric/invalid value shows Enter a valid task id - Each dependency can be removed (edit permission only) - Adding or removing a dependency reloads the task (so the blocked state and progress update)
Priority	Medium

6.20 TS-020 — Activity tab

Field	Value
Description	The Activity tab shows the task's event history as a timeline, newest first.

Field	Value
Acceptance Criteria	- Events are shown as a vertical timeline ordered newest first (the server's oldest→newest order reversed, keeping same-second events in correct relative order and "Created" last) - Each event shows its description (or state) and a line combining the actor (when present) and the relative time - An empty history shows No activity
Priority	Low

6.21 TS-021 — Action menu, permission-gated

Field	Value
Description	An overflow (:) menu surfaces the task actions the agent may perform; actions the agent cannot perform on this task's department are hidden.
Acceptance Criteria	- The : menu lists: Close (when the task is open) or Reopen (when closed) — gated by close permission; Assign (assign permission); Transfer dept (transfer permission); Set priority (edit permission); Collaborators (always available); and Tags (edit permission) - Group dividers appear only around non-empty groups - When permissions are not yet loaded, actions default to hidden
Priority	High

6.22 TS-022 — Status: close / reopen

Field	Value
Description	A task's status is binary — Open or Completed — driven by close/reopen. It can be changed from the : menu or the Details-tab Status row via a deliberate picker.
Acceptance Criteria	- From the : menu, Close closes an open task ("Task closed") and Reopen reopens a closed one ("Task reopened"); both reload - The Details-tab Status row opens a picker offering Open and Completed with the current one selected; choosing the other applies the matching close/reopen; choosing the current one (or dismissing) changes nothing - Status changes require close permission
Priority	High

6.23 TS-023 — Assign / transfer / set priority

Field	Value
Description	Assignment, department transfer, and priority changes are made from pickers.
Acceptance Criteria	- Assign opens an agent picker and assigns the task on choose (toast "Assigned", reload) - Transfer dept opens a department picker (pre-selecting the current department) and transfers on choose (toast "Transferred", reload) - Set priority opens a task-priority picker (pre-selecting the current priority) and applies on choose (toast "Priority updated", reload) - Each requires its matching permission (assign / transfer / edit)
Priority	Medium

6.24 TS-024 — Collaborators

Field	Value
Description	Manage the task's collaborators.
Acceptance Criteria	- The Collaborators dialog lists current collaborators (name + email) or No collaborators when empty - Add collaborator opens a user picker and adds the chosen user; each collaborator can be removed - Add/remove are enforced server-side; the action is available to all agents
Priority	Low

6.25 TS-025 — Tags

Field	Value
Description	Manage the task's tags.
Acceptance Criteria	- The Tags dialog lists the task's tags or No tags when empty - Add tag opens a picker from the shared tag list; each tag can be removed - Tag management requires edit permission
Priority	Low

6.26 TS-026 — Per-agent permission gating

Field	Value
Description	Every mutating task affordance is gated by the same per-department permission the corresponding server endpoint enforces, so an agent never sees an action they cannot perform.
Acceptance Criteria	- Action visibility/editability is derived from the agent's per-department task permissions (task.edit, task.create, task.assign, task.transfer, task.close, task.reply) - Close/reopen and the status row require close permission; add-subtask requires create; add/remove dependency, priority, and tags require edit; assign requires assign; transfer requires transfer; the composer requires reply - When permissions are not yet loaded, actions default to hidden (the server would reject them regardless) - Details-tab rows and section actions honour the same gates as the : menu (a non-permitted attribute row is read-only; a non-reply agent gets no composer; add-subtask/add-dependency hidden without their permissions)
Priority	High

6.27 TS-027 — Create task: structure and required fields

Field	Value
Description	The Create task screen collects a new task across grouped sections. Department, title, and description are required; the submit button stays disabled until all three are present and names what is still missing. A task may also be created linked to a ticket.

Field	Value
Acceptance Criteria	- The screen is titled New task and is organised into sections: Task details, Attachments, and Properties - The three required fields are Department, Title, and Description - The Create task button is disabled until all three are provided; while disabled, a hint lists what is missing, e.g. Add department, title to continue - When opened from a ticket, an informational banner reads This task will be linked to ticket #<number> (or a generic variant) and the created task is linked to that ticket - While saving, the form is not interactive and a progress indicator is shown
Priority	High

6.28 TS-028 — Create task: title, description, canned/FAQ, attachments

Field	Value
Description	The Task details section holds the title and a rich description with saved-reply/FAQ insertion; the Attachments section adds files.
Acceptance Criteria	- Title is a required single-line field (placeholder Title; inline server error under it when returned) - Description is a required rich-text field with placeholder Describe the task... (inline error Description is required when empty on submit) - Saved-reply and FAQ actions insert their content into the description at the cursor - Attachments adds files via Camera / Photo / File; added files are shown as removable chips with name and size
Priority	High

6.29 TS-029 — Create task: properties

Field	Value
Description	The Properties section sets the department (required), priority, due date, and an optional parent task.
Acceptance Criteria	- Department opens a department picker; until chosen it shows Required · tap to choose; after a failed submit with no department it shows an inline error - Priority opens a task-priority picker - Due date opens a date then time picker (from yesterday up to 3 years out; defaults to 5 pm when no time is chosen) and can be cleared - Parent task opens a searchable task picker (search by number or title); the chosen parent is shown as "#number · title" and can be cleared
Priority	Medium

6.30 TS-030 — Create task: submit, validation, and result

Field	Value
Description	Submitting validates the required fields, creates the task, and opens the new task.

Field	Value
Acceptance Criteria	- On submit, the title and description are validated and a missing department is surfaced on its own row (scrolling it into view) - On a valid form the task is created with the department, title, rich description, and any priority, due date, parent task, and (when applicable) the linked ticket, plus attachments - On success a toast reads Task #<number> created and the new task's detail screen replaces the create screen - On an API error with field errors, each is shown inline against its field (title, description, dept_id); a general error is shown as an error banner at the top of the form
Priority	High

Document in progress — additional cases added after individual approval.