

07 – Tuple/Set



Ex. No. : 7.1

Date: 18.05.24

Register No.: 231901012

Name: Janany M

Binary String

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No

Program:

```
a = input()
try:
    c = int(a)
    print("Yes")
except:
    print("No")
```



	Input	Expected	Got	
✓	01010101010	Yes	Yes	✓
✓	REC123	No	No	✓
✓	010101 10101	No	No	✓



DNA Sequence

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string **s** that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

Input: s = "AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT"

Output: ["AAAAACCCCC", "CCCCCAAAAA"]

Example 2:

Input: s = "AAAAAAAAAAAAA"

Output: ["AAAAAAAAAAAA"]

For example:

Input	Result
AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT	AAAAACCCCC CCCCCAAAAA



Program:

```
def findRepeatedSequences(s):  
    sequences = { }  
    result = []  
    for i in range(len(s) - 9):  
        seq = s[i:i+10]  
        sequences[seq] = sequences.get(seq, 0) + 1  
        if sequences[seq] == 2:  
            result.append(seq)  
    return result  
s1 = input()  
for i in findRepeatedSequences(s1):  
    print(i)
```

	Input	Expected	Got	
✓	AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCC CCCCAAAAA	AAAAACCCC CCCCAAAAA	✓
✓	AAAAAAAAAAAAA	AAAAAAAAA	AAAAAAAAA	✓




American keyboard

Given an array of strings words, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".



-
-
- **Example 1:**
- **Input:** words = ["Hello","Alaska","Dad","Peace"]
- **Output:** ["Alaska","Dad"]
- **Example 2:**
- **Input:** words = ["omk"]
- **Output:** []
- **Example 3:**
- **Input:** words = ["adsdf","sfd"]
- **Output:** ["adsdf","sfd"]
-

- **For example:**

Input	Result
4 Hello	Alaska Dad



Input	Result
Alaska Dad Peace	

Program:

```
def findWords(words):

    row1 = set('qwertyuiop')

    row2 = set('asdfghjkl')

    row3 = set('zxcvbnm')


    result = []

    for word in words:

        w = set(word.lower())

        if w.issubset(row1) or w.issubset(row2) or w.issubset(row3):

            result.append(word)

    if len(result) == 0:

        print("No words")

    else:

        for i in result:

            print(i)


a = int(input())

arr = [input() for i in range(a)]

findWords(arr)
```



	Input	Expected	Got	
✓	4 Hello Alaska Dad Peace	Alaska Dad	Alaska Dad	✓
✓	1 omk	No words	No words	✓
✓	2 adsfd afd	adsfd afd	adsfd afd	✓



Print repeated no

Given an array of integers `nums` containing `n + 1` integers where each integer is in the range `[1, n]` inclusive. There is only **one repeated number** in `nums`, return *this repeated number*. Solve the problem using [set](#).

Example 1:

Input: `nums = [1,3,4,2,2]`

Output: 2

Example 2:

Input: `nums = [3,1,3,4,2]`

Output: 3

For example:

Input	Result
1 3 4 4 2	4

Program:

```
n=input().split(" ")
n = list(n)
for i in range(len(n)):
    for j in range(i+1,len(n)):
        if n[i] == n[j]:
            print(n[i])
            exit(0)
```



	Input	Expected	Got	
✓	1 3 4 4 2	4	4	✓
✓	1 2 2 3 4 5 6 7	2	2	✓



Check Pair

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to **K**.

Examples:

Input: t = (5, 6, 5, 7, 7, 8), K = 13

Output: 2

Explanation:

Pairs with sum K(= 13) are {(5, 8), (6, 7), (6, 7)}.

Therefore, distinct pairs with sum K(= 13) are { (5, 8), (6, 7) }.

Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0

Program:

```
def count_distinct_pairs(t, K):  
    distinct_pairs = set()  
    for i in range(len(t)):  
        for j in range(i + 1, len(t)):  
            if t[i] + t[j] == K:
```



```

        distinct_pairs.add((min(t[i], t[j]), max(t[i], t[j])))
    return len(distinct_pairs)

t_input = input()
t = tuple(map(int, t_input.split(',')))
K = int(input())
print(count_distinct_pairs(t, K))

```

	Input	Expected	Got	
✓	5,6,5,7,7,8 13	2	2	✓
✓	1,2,1,2,5 3	1	1	✓
✓	1,2 0	0	0	✓

