


Chapter 5

Divide and Conquer



Slides by Kevin Wayne.
Copyright © 2005 Pearson-Addison Wesley.
All rights reserved.

Divide-and-Conquer

Divide-and-conquer.

- Break up problem into several parts.
- Solve each part recursively.
- Combine solutions to sub-problems into overall solution.

Most common usage.

- Break up problem of size n into **two** equal parts of size $\frac{1}{2}n$ in linear time.
- Solve two parts recursively.
- Combine two solutions into overall solution in **linear time**.

Consequence.

- Divide-and-conquer: $\Theta(n \log n)$

5.1 Mergesort

Sorting

Sorting. Given n elements, rearrange in ascending order.

Obvious sorting applications.

- List files in a directory.
- Organize an MP3 library.
- List names in a phone book.
- Display Google PageRank results.

Problems become easier once sorted.

- Find the median.
- Find the closest pair.
- Binary search in a database.
- Identify statistical outliers.
- Find duplicates in a mailing list.

Non-obvious sorting applications.

- Data compression.
- Computer graphics.
- Interval scheduling.
- Computational biology.
- Minimum spanning tree.
- Supply chain management.
- Simulate a system of particles.
- Book recommendations on Amazon.
- Load balancing on a parallel computer.
- ...

Mergesort

Mergesort.

- Divide array into two halves.
- Recursively sort each half.
- Merge two halves to make sorted whole.



Jon von Neumann (1945)

A	L	G	O	R	I	T	H	M	S
---	---	---	---	---	---	---	---	---	---

A	L	G	O	R	I	T	H	M	S
---	---	---	---	---	---	---	---	---	---

divide

A	G	L	O	R	H	I	M	S	T
---	---	---	---	---	---	---	---	---	---

sort

A	G	H	I	L	M	O	R	S	T
---	---	---	---	---	---	---	---	---	---

merge

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.

smallest



A	G	L	O	R
---	---	---	---	---

smallest



H	I	M	S	T
---	---	---	---	---

A									
---	--	--	--	--	--	--	--	--	--


auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.




auxiliary array

Merging

Merging. Combine two pre-sorted lists into a sorted whole.

How to merge efficiently?

- Keep track of smallest element in each sorted half.
- Insert smallest of two elements into auxiliary array.
- Repeat until done.



A Useful Recurrence Relation

Def. $T(n)$ = number of comparisons to mergesort an input of size n .

Mergesort recurrence.


$$T(n) \leq \begin{cases} 0 & \text{if } n=1 \\ \underbrace{T(\lceil n/2 \rceil)}_{\text{solve left half}} + \underbrace{T(\lfloor n/2 \rfloor)}_{\text{solve right half}} + \underbrace{n}_{\text{merging}} & \text{otherwise} \end{cases}$$

Solution. $T(n) = O(n \log_2 n)$.

Assorted proofs. We describe several ways to prove this recurrence. Initially we assume n is a power of 2 and replace \leq with $=$.

Proof by Recursion Tree

$$T(n) = \begin{cases} 0 & \text{if } n=1 \\ \underbrace{2T(n/2)}_{\text{sorting both halves}} + \underbrace{n}_{\text{merging}} & \text{otherwise} \end{cases}$$



Proof by Telescoping

Claim. If $T(n)$ satisfies this recurrence, then $T(n) = n \log_2 n$.

↑
assumes n is a power of 2

$$T(n) = \begin{cases} 0 & \text{if } n = 1 \\ \underbrace{2T(n/2)}_{\text{sorting both halves}} + \underbrace{n}_{\text{merging}} & \text{otherwise} \end{cases}$$

Pf. For $n > 1$:

$$\begin{aligned} \frac{T(n)}{n} &= \frac{2T(n/2)}{n} + 1 \\ &= \frac{T(n/2)}{n/2} + 1 \\ &= \frac{T(n/4)}{n/4} + 1 + 1 \\ &\dots \\ &= \frac{T(n/n)}{n/n} + \underbrace{1 + \dots + 1}_{\log_2 n} \\ &= \log_2 n \end{aligned}$$

Proof by Induction

Claim. If $T(n)$ satisfies this recurrence, then $T(n) = n \log_2 n$.

↑
assumes n is a power of 2

$$T(n) = \begin{cases} 0 & \text{if } n = 1 \\ \underbrace{2T(n/2)}_{\text{sorting both halves}} + \underbrace{n}_{\text{merging}} & \text{otherwise} \end{cases}$$

Pf. (by induction on n)

- Base case: $n = 1$.
- Inductive hypothesis: $T(n) = n \log_2 n$.
- Goal: show that $T(2n) = 2n \log_2 (2n)$.

$$\begin{aligned} T(2n) &= 2T(n) + 2n \\ &= 2n \log_2 n + 2n \\ &= 2n(\log_2(2n) - 1) + 2n \\ &= 2n \log_2(2n) \end{aligned}$$

Analysis of Mergesort Recurrence

Claim. If $T(n)$ satisfies the following recurrence, then $T(n) \leq n \lceil \log_2 n \rceil$.

$$T(n) \leq \begin{cases} 0 & \text{if } n=1 \\ \underbrace{T(\lceil n/2 \rceil)}_{\text{solve left half}} + \underbrace{T(\lfloor n/2 \rfloor)}_{\text{solve right half}} + \underbrace{n}_{\text{merging}} & \text{otherwise} \end{cases}$$

Pf. (by induction on n)

- Base case: $n = 1$.
- Define $n_1 = \lfloor n / 2 \rfloor$, $n_2 = \lceil n / 2 \rceil$.
- Induction step: assume true for $1, 2, \dots, n-1$.

$$\begin{aligned} T(n) &\leq T(n_1) + T(n_2) + n \\ &\leq n_1 \lceil \log_2 n_1 \rceil + n_2 \lceil \log_2 n_2 \rceil + n \\ &\leq n_1 \lceil \log_2 n_2 \rceil + n_2 \lceil \log_2 n_2 \rceil + n \\ &= n \lceil \log_2 n_2 \rceil + n \\ &\leq n(\lceil \log_2 n \rceil - 1) + n \\ &= n \lceil \log_2 n \rceil \end{aligned}$$

$$\begin{aligned} n_2 &= \lceil n / 2 \rceil \\ &\leq \lceil 2^{\lceil \log_2 n \rceil} / 2 \rceil \\ &= 2^{\lceil \log_2 n \rceil} / 2 \\ &\Rightarrow \log_2 n_2 \leq \lceil \log_2 n \rceil - 1 \end{aligned}$$

5.3 Counting Inversions

Counting Inversions


Music site tries to match your song preferences with others.

- You rank n songs.
- Music site consults database to find people with **similar** tastes.

Similarity metric: number of inversions between two rankings.

- My rank: $1, 2, \dots, n$.
- Your rank: a_1, a_2, \dots, a_n .
- Songs i and j **inverted** if $i < j$, but $a_i > a_j$.

Songs					
	A	B	C	D	E
Me	1	2	3	4	5
You	1	3	4	2	5



Inversions
3-2, 4-2

Brute force: check all $\Theta(n^2)$ pairs i and j .

Applications

Applications.

- Voting theory.
- Collaborative filtering.
- Measuring the "sortedness" of an array.
- Sensitivity analysis of Google's ranking function.
- Rank aggregation for meta-searching on the Web.
- Nonparametric statistics (e.g., Kendall's Tau distance).

Counting Inversions: Divide-and-Conquer

Divide-and-conquer.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Counting Inversions: Divide-and-Conquer

Divide-and-conquer.

- **Divide**: separate list into two pieces.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Divide: $O(1)$.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Counting Inversions: Divide-and-Conquer

Divide-and-conquer.

- Divide: separate list into two pieces.
- **Conquer**: recursively count inversions in each half.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Divide: $O(1)$.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Conquer: $2T(n / 2)$

5 blue-blue inversions

8 green-green inversions

5-4, 5-2, 4-2, 8-2, 10-2

6-3, 9-3, 9-7, 12-3, 12-7, 12-11, 11-3, 11-7

Counting Inversions: Divide-and-Conquer

Divide-and-conquer.

- Divide: separate list into two pieces.
- Conquer: recursively count inversions in each half.
- **Combine**: count inversions where a_i and a_j are in different halves, and return sum of three quantities.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

Divide: $O(1)$.

1	5	4	8	10	2	6	9	12	11	3	7
---	---	---	---	----	---	---	---	----	----	---	---

5 blue-blue inversions

8 green-green inversions

Conquer: $2T(n / 2)$

9 blue-green inversions

5-3, 4-3, 8-6, 8-3, 8-7, 10-6, 10-9, 10-3, 10-7

Combine: ???

Total = $5 + 8 + 9 = 22$.

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.

$i = 6$



3	7	10	14	18	19
---	---	----	----	----	----



2	11	16	17	23	25
---	----	----	----	----	----

two sorted halves

--	--	--	--	--	--	--	--	--	--	--	--

auxiliary array

Total:

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.

$i = 6$



3	7	10	14	18	19
---	---	----	----	----	----



2	11	16	17	23	25
---	----	----	----	----	----

two sorted halves

6

2											
---	--	--	--	--	--	--	--	--	--	--	--

auxiliary array

Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.

$i = 6$



3	7	10	14	18	19
---	---	----	----	----	----



2	11	16	17	23	25
---	----	----	----	----	----

two sorted halves

6

2											
---	--	--	--	--	--	--	--	--	--	--	--

auxiliary array

Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.

$i = 6$



two sorted halves

6




auxiliary array

Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6

Merge and Count

Merge and count step.


- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.



Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6 + 3

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6 + 3

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6 + 3

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: 6 + 3

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2 + 0$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2 + 0$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.




Total: $6 + 3 + 2 + 2 + 0 + 0$

Merge and Count

Merge and count step.

- Given two sorted halves, count number of inversions where a_i and a_j are in different halves.
- Combine two sorted halves into sorted whole.



Total: $6 + 3 + 2 + 2 + 0 + 0 = 13$

Counting Inversions: Implementation

```
Sort-and-Count(L) {  
    if list L has one element  
        return 0 and the list L  
  
    Divide the list into two halves A and B  
    (rA, A) ← Sort-and-Count(A)  
    (rB, B) ← Sort-and-Count(B)  
    (r , L) ← Merge-and-Count(A, B)  
  
    return r = rA + rB + r and the sorted list L  
}
```

$$T(n) \leq T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + O(n) \Rightarrow T(n) = O(n \log n)$$

5.4 Closest Pair of Points

Closest Pair of Points

Closest pair. Given n points in the plane, find a pair with smallest Euclidean distance between them.

Fundamental geometric primitive.

- Graphics, computer vision, geographic information systems, molecular modeling, air traffic control.
- Special case of nearest neighbor, Euclidean MST, Voronoi.

↖ fast closest pair inspired fast algorithms for these problems

Brute force. Check all pairs of points p and q with $\Theta(n^2)$ comparisons.

1-D version. $O(n \log n)$ easy if points are on a line.


Assumption. No two points have same x coordinate.

↑
to make presentation cleaner

Closest Pair of Points

Algorithm.


- **Divide:** draw vertical line L so that roughly $\frac{1}{2}n$ points on each side.



Closest Pair of Points

Algorithm.


- Divide: draw vertical line L so that roughly $\frac{1}{2}n$ points on each side.
- **Conquer**: find closest pair in each side recursively.



Closest Pair of Points


Algorithm.

- Divide: draw vertical line L so that roughly $\frac{1}{2}n$ points on each side.
- Conquer: find closest pair in each side recursively.
- **Combine**: find closest pair with one point in each side. ← seems like $\Theta(n^2)$
- Return best of 3 solutions.



Closest Pair of Points


Find closest pair with one point in each side, **assuming that distance $< \delta$** .



Closest Pair of Points

Find closest pair with one point in each side, **assuming that distance $< \delta$** .


- Observation: only need to consider points within δ of line L .



Closest Pair of Points

Find closest pair with one point in each side, **assuming that distance $< \delta$** .


- Observation: only need to consider points within δ of line L .
- Sort points in 2δ -strip by their y coordinate.



Closest Pair of Points

Find closest pair with one point in each side, **assuming that distance $< \delta$** .

- Observation: only need to consider points within δ of line L .
- Sort points in 2δ -strip by their y coordinate.
- Only check distances of those within 11 positions in sorted list!




Closest Pair of Points

Def. Let s_i be the point in the 2δ -strip, with the i^{th} smallest y-coordinate.

Claim. If $|i - j| \geq 12$, then the distance between s_i and s_j is at least δ .

Pf.

- No two points lie in same $\frac{1}{2}\delta$ -by- $\frac{1}{2}\delta$ box.
- Two points at least 2 rows apart have distance $\geq 2(\frac{1}{2}\delta)$. ▪



Fact. Still true if replace 12 with 8. Why?

Closest Pair Algorithm

```
Closest-Pair( $p_1, \dots, p_n$ ) {  
    Compute separation line  $L$  such that half the points  
    are on one side and half on the other side.  $O(n \log n)$   
  
     $\delta_1 = \text{Closest-Pair}(\text{left half})$   
     $\delta_2 = \text{Closest-Pair}(\text{right half})$   $2T(n / 2)$   
     $\delta = \min(\delta_1, \delta_2)$   
  
    Delete all points further than  $\delta$  from separation line  $L$   $O(n)$   
  
    Sort remaining points by y-coordinate.  $O(n \log n)$   
  
    Scan points in y-order and compare distance between  
    each point and next 11 neighbors. If any of these  
    distances is less than  $\delta$ , update  $\delta$ .  $O(n)$   
  
    return  $\delta$ .  
}
```

Closest Pair of Points: Analysis

Running time.

$$T(n) \leq 2T(n/2) + O(n \log n) \Rightarrow T(n) = O(n \log^2 n)$$

Q. Can we achieve $O(n \log n)$?

A. Yes. Don't sort points from scratch each time.

- Sort all the points twice before recursive call, once by x coordinate and once by y coordinate
- Reuse the sorted sequences when needed (linear time)

$$T(n) \leq 2T(n/2) + O(n) \Rightarrow T(n) = O(n \log n)$$

5.5 Integer Multiplication

Integer Arithmetic

Add. Given two n -digit integers a and b , compute $a + b$.

- $O(n)$ bit operations.

Multiply. Given two n -digit integers a and b , compute $a \times b$.

- Brute force solution: $\Theta(n^2)$ bit operations.

	1	1	0	1	0	1	0	1
+	0	1	1	1	1	1	0	1
	1	0	1	0	1	0	0	1

Add

[illegible]

Divide-and-Conquer Multiplication: Warmup

To multiply two n -digit integers:

- Multiply four $\frac{1}{2}n$ -digit integers.
- Add two $\frac{1}{2}n$ -digit integers, and shift to obtain result.

$$\begin{array}{ccccccc} x = & 1 & 0 & 0 & 0 & 1 & 1 & 0 & 1 \\ & \underbrace{}_{x_1} & & \underbrace{}_{x_0} \end{array}$$

$$x = 2^{n/2} \cdot x_1 + x_0$$

$$y = 2^{n/2} \cdot y_1 + y_0$$

$$xy = (2^{n/2} \cdot x_1 + x_0)(2^{n/2} \cdot y_1 + y_0) = 2^n \cdot x_1 y_1 + 2^{n/2} \cdot (x_1 y_0 + x_0 y_1) + x_0 y_0$$

$$T(n) = \underbrace{4T(n/2)}_{\text{recursive calls}} + \underbrace{\Theta(n)}_{\text{add, shift}} \Rightarrow T(n) = \Theta(n^2)$$

↑
assumes n is a power of 2

Karatsuba Multiplication

To multiply two n -digit integers:

- Add two $\frac{1}{2}n$ digit integers.
- Multiply **three** $\frac{1}{2}n$ -digit integers.
- Add, subtract, and shift $\frac{1}{2}n$ -digit integers to obtain result.

$$\begin{aligned}x &= 2^{n/2} \cdot x_1 + x_0 \\y &= 2^{n/2} \cdot y_1 + y_0 \\xy &= 2^n \cdot x_1 y_1 + 2^{n/2} \cdot (x_1 y_0 + x_0 y_1) + x_0 y_0 \\&= \underbrace{2^n \cdot x_1 y_1}_A + \underbrace{2^{n/2} \cdot ((x_1 + x_0)(y_1 + y_0) - x_1 y_1 - x_0 y_0)}_B + \underbrace{x_0 y_0}_C\end{aligned}$$


Theorem. [Karatsuba-Ofman, 1962] Can multiply two n -digit integers in $O(n^{1.585})$ bit operations.

$$\begin{aligned}T(n) &\leq \underbrace{T(\lfloor n/2 \rfloor) + T(\lceil n/2 \rceil) + T(1 + \lceil n/2 \rceil)}_{\text{recursive calls}} + \underbrace{\Theta(n)}_{\text{add, subtract, shift}} \\&\Rightarrow T(n) = O(n^{\log_2 3}) = O(n^{1.585})\end{aligned}$$

Karatsuba: Recursion Tree

$$T(n) = \begin{cases} 1 & \text{if } n = 1 \\ 3T(n/2) + n & \text{otherwise} \end{cases}$$

$$T(n) = \sum_{k=0}^{\log_2 n} n \left(\frac{3}{2}\right)^k = \frac{\left(\frac{3}{2}\right)^{1+\log_2 n} - 1}{\frac{3}{2} - 1} n = 3n^{\log_2 3} - 2n$$



Matrix Multiplication

Matrix Multiplication

Matrix multiplication. Given two n-by-n matrices A and B, compute $C = AB$.

$$c_{ij} = \sum_{k=1}^n a_{ik} b_{kj}$$

$$\begin{bmatrix} c_{11} & c_{12} & \cdots & c_{1n} \\ c_{21} & c_{22} & \cdots & c_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ c_{n1} & c_{n2} & \cdots & c_{nn} \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} & a_{n2} & \cdots & a_{nn} \end{bmatrix} \times \begin{bmatrix} b_{11} & b_{12} & \cdots & b_{1n} \\ b_{21} & b_{22} & \cdots & b_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ b_{n1} & b_{n2} & \cdots & b_{nn} \end{bmatrix}$$

Brute force. $\Theta(n^3)$ arithmetic operations.

Fundamental question. Can we improve upon brute force?

Matrix Multiplication: Warmup

Divide-and-conquer.

- Divide: partition A and B into $\frac{1}{2}n$ -by- $\frac{1}{2}n$ blocks.
- Conquer: multiply 8 $\frac{1}{2}n$ -by- $\frac{1}{2}n$ recursively.
- Combine: add appropriate products using 4 matrix additions.

$$\begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix} \times \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$$

$$\begin{aligned} C_{11} &= (A_{11} \times B_{11}) + (A_{12} \times B_{21}) \\ C_{12} &= (A_{11} \times B_{12}) + (A_{12} \times B_{22}) \\ C_{21} &= (A_{21} \times B_{11}) + (A_{22} \times B_{21}) \\ C_{22} &= (A_{21} \times B_{12}) + (A_{22} \times B_{22}) \end{aligned}$$

$$T(n) = \underbrace{8T(n/2)}_{\text{recursive calls}} + \underbrace{\Theta(n^2)}_{\text{add, form submatrices}} \Rightarrow T(n) = \Theta(n^3)$$

Matrix Multiplication: Key Idea

Key idea. multiply 2-by-2 block matrices with only **7** multiplications.

$$\begin{bmatrix} C_{11} & C_{12} \\ C_{21} & C_{22} \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix} \times \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$$

$$C_{11} = P_5 + P_4 - P_2 + P_6$$

$$C_{12} = P_1 + P_2$$

$$C_{21} = P_3 + P_4$$

$$C_{22} = P_5 + P_1 - P_3 - P_7$$

$$P_1 = A_{11} \times (B_{12} - B_{22})$$

$$P_2 = (A_{11} + A_{12}) \times B_{22}$$

$$P_3 = (A_{21} + A_{22}) \times B_{11}$$

$$P_4 = A_{22} \times (B_{21} - B_{11})$$

$$P_5 = (A_{11} + A_{22}) \times (B_{11} + B_{22})$$

$$P_6 = (A_{12} - A_{22}) \times (B_{21} + B_{22})$$

$$P_7 = (A_{11} - A_{21}) \times (B_{11} + B_{12})$$

- 7 multiplications.
- 18 = 10 + 8 additions (or subtractions).

Fast Matrix Multiplication

Fast matrix multiplication. (Strassen, 1969)

- Divide: partition A and B into $\frac{1}{2}n$ -by- $\frac{1}{2}n$ blocks.
- Compute: 14 $\frac{1}{2}n$ -by- $\frac{1}{2}n$ matrices via 10 matrix additions.
- Conquer: multiply 7 $\frac{1}{2}n$ -by- $\frac{1}{2}n$ matrices recursively.
- Combine: 7 products into 4 terms using 8 matrix additions.

Analysis.

- Assume n is a power of 2.
- $T(n)$ = # arithmetic operations.

$$T(n) = \underbrace{7T(n/2)}_{\text{recursive calls}} + \underbrace{\Theta(n^2)}_{\text{add, subtract}} \Rightarrow T(n) = \Theta(n^{\log_2 7}) = O(n^{2.81})$$

Fast Matrix Multiplication in Practice

Common misperception: "Strassen is only a theoretical curiosity."

- Advanced Computation Group at Apple Computer reports 8x speedup on G4 Velocity Engine when $n \sim 2,500$.
- Range of instances where it's useful is a subject of controversy.

Remark. Can "Strassenize" $Ax=b$, determinant, eigenvalues, and other matrix ops.

Fast Matrix Multiplication in Theory

Q. Multiply two 2-by-2 matrices with only 7 scalar multiplications?

A. Yes! [Strassen, 1969]

$$\Theta(n^{\log_2 7}) = O(n^{2.81})$$

Q. Multiply two 2-by-2 matrices with only 6 scalar multiplications?

A. Impossible. [Hopcroft and Kerr, 1971]

$$\Theta(n^{\log_2 6}) = O(n^{2.59})$$

Q. Two 3-by-3 matrices with only 21 scalar multiplications?

A. Also impossible.

$$\Theta(n^{\log_3 21}) = O(n^{2.77})$$

Q. Two 70-by-70 matrices with only 143,640 scalar multiplications?

A. Yes! [Pan, 1980]

$$\Theta(n^{\log_{70} 143640}) = O(n^{2.80})$$

Fast Matrix Multiplication in Theory

Decimal wars.

- December, 1979: $O(n^{2.521813})$.
- January, 1980: $O(n^{2.521801})$.
- ...
- 1987: $O(n^{2.375477})$.
- 2010: $O(n^{2.374})$.
- 2011: $O(n^{2.3728642})$.
- 2014: $O(n^{2.3728639})$.

Best known. $O(n^{2.3728639})$ [François Le Gall, 2014.]

Conjecture. $O(n^{2+\varepsilon})$ for any $\varepsilon > 0$.

Caveat. Theoretical improvements to Strassen are progressively less practical.

5.6 Convolution and FFT

Fast Fourier Transform: Applications

Applications.

- Optics, acoustics, quantum physics, telecommunications, control systems, signal processing, speech recognition, data compression, image processing.
- DVD, JPEG, MP3, MRI, CAT scan.
- Numerical solutions to Poisson's equation.

The FFT is one of the truly great computational developments of this [20th] century. It has changed the face of science and engineering so much that it is not an exaggeration to say that life as we know it would be very different without the FFT. *-Charles van Loan*

Polynomials: Coefficient Representation

Polynomial. [coefficient representation]

$$A(x) = a_0 + a_1x + a_2x^2 + \cdots + a_{n-1}x^{n-1}$$

$$B(x) = b_0 + b_1x + b_2x^2 + \cdots + b_{n-1}x^{n-1}$$

Add: $O(n)$ arithmetic operations.

$$A(x) + B(x) = (a_0 + b_0) + (a_1 + b_1)x + \cdots + (a_{n-1} + b_{n-1})x^{n-1}$$

Evaluate: $O(n)$ using Horner's method.


$$A(x) = a_0 + (x(a_1 + x(a_2 + \cdots + x(a_{n-2} + x(a_{n-1}))) \cdots))$$

Multiply (convolve): $O(n^2)$ using brute force.

$$A(x) \times B(x) = \sum_{i=0}^{2n-2} c_i x^i, \text{ where } c_i = \sum_{j=0}^i a_j b_{i-j}$$

Polynomials: Point-Value Representation

A degree $n-1$ polynomial $A(x)$ is uniquely specified by its evaluation at n distinct values of x .



Polynomials: Point-Value Representation

Polynomial. [point-value representation]

$$A(x): (x_0, y_0), \dots, (x_{n-1}, y_{n-1})$$

$$B(x): (x_0, z_0), \dots, (x_{n-1}, z_{n-1})$$

Add: $O(n)$ arithmetic operations.

$$A(x) + B(x): (x_0, y_0 + z_0), \dots, (x_{n-1}, y_{n-1} + z_{n-1})$$

Multiply: $O(n)$, but need $2n-1$ points.

$$A(x) \times B(x): (x_0, y_0 \times z_0), \dots, (x_{2n-1}, y_{2n-1} \times z_{2n-1})$$

Evaluate: $O(n^2)$ using Lagrange's formula.


$$A(x) = \sum_{k=0}^{n-1} y_k \frac{\prod_{j \neq k} (x - x_j)}{\prod_{j \neq k} (x_k - x_j)}$$

Converting Between Two Polynomial Representations

Tradeoff. Fast evaluation or fast multiplication. We want both!

Representation	Multiply	Evaluate
Coefficient	$O(n^2)$	$O(n)$
Point-value	$O(n)$	$O(n^2)$

Goal. Make all ops fast by efficiently converting between two representations.



Converting Between Two Polynomial Representations: Brute Force

Coefficient \rightarrow point-value. Given a polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$, evaluate it at n distinct points x_0, \dots, x_{n-1} .

$$\begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ \vdots \\ y_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & x_0 & x_0^2 & \cdots & x_0^{n-1} \\ 1 & x_1 & x_1^2 & \cdots & x_1^{n-1} \\ 1 & x_2 & x_2^2 & \cdots & x_2^{n-1} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_{n-1} & x_{n-1}^2 & \cdots & x_{n-1}^{n-1} \end{bmatrix} \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ \vdots \\ a_{n-1} \end{bmatrix}$$

Running time. $O(n^2)$ for matrix-vector multiplication or n times Horner's method

Converting Between Two Polynomial Representations: Brute Force

Point-value \rightarrow coefficient. Given n distinct points x_0, \dots, x_{n-1} and values y_0, \dots, y_{n-1} , find unique polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$ that has given values at given points.

$$\begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ \vdots \\ y_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & x_0 & x_0^2 & \cdots & x_0^{n-1} \\ 1 & x_1 & x_1^2 & \cdots & x_1^{n-1} \\ 1 & x_2 & x_2^2 & \cdots & x_2^{n-1} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_{n-1} & x_{n-1}^2 & \cdots & x_{n-1}^{n-1} \end{bmatrix} \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ \vdots \\ a_{n-1} \end{bmatrix}$$

Running time. $O(n^3)$ for Gaussian elimination.

Coefficient to Point-Value Representation: Intuition

Coefficient to point-value. Given a polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$, evaluate it at n distinct points x_0, \dots, x_{n-1} .

We can choose which points!

Divide. Break polynomial up into even and odd powers.

- $A(x) = a_0 + a_1 x + a_2 x^2 + a_3 x^3 + a_4 x^4 + a_5 x^5 + a_6 x^6 + a_7 x^7.$
- $A_{\text{even}}(x) = a_0 + a_2 x + a_4 x^2 + a_6 x^3.$
- $A_{\text{odd}}(x) = a_1 + a_3 x + a_5 x^2 + a_7 x^3.$
- $A(x) = A_{\text{even}}(x^2) + x A_{\text{odd}}(x^2).$
- $A(-x) = A_{\text{even}}(x^2) - x A_{\text{odd}}(x^2).$

Intuition. Choose two points to be ± 1 .

- $A(1) = A_{\text{even}}(1) + 1 A_{\text{odd}}(1).$
- $A(-1) = A_{\text{even}}(1) - 1 A_{\text{odd}}(1).$

Can evaluate polynomial of degree $\leq n$ at 2 points by evaluating two polynomials of degree $\leq \frac{1}{2}n$ at 1 point.

Coefficient to Point-Value Representation: Intuition

Coefficient to point-value. Given a polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$, evaluate it at n distinct points x_0, \dots, x_{n-1} .

We can choose which points!

Divide. Break polynomial up into even and odd powers.

- $A(x) = a_0 + a_1 x + a_2 x^2 + a_3 x^3 + a_4 x^4 + a_5 x^5 + a_6 x^6 + a_7 x^7.$
- $A_{\text{even}}(x) = a_0 + a_2 x + a_4 x^2 + a_6 x^3.$
- $A_{\text{odd}}(x) = a_1 + a_3 x + a_5 x^2 + a_7 x^3.$
- $A(x) = A_{\text{even}}(x^2) + x A_{\text{odd}}(x^2).$
- $A(-x) = A_{\text{even}}(x^2) - x A_{\text{odd}}(x^2).$

Intuition. Choose four **complex** points to be $\pm 1, \pm i$.

- $A(1) = A_{\text{even}}(1) + 1 A_{\text{odd}}(1).$
- $A(-1) = A_{\text{even}}(1) - 1 A_{\text{odd}}(1).$
- $A(i) = A_{\text{even}}(-1) + i A_{\text{odd}}(-1).$
- $A(-i) = A_{\text{even}}(-1) - i A_{\text{odd}}(-1).$

Can evaluate polynomial of degree $\leq n$ at 4 points by evaluating two polynomials of degree $\leq \frac{1}{2}n$ at 2 point.

Coefficient to Point-Value Representation: Intuition

Coefficient to point-value. Given a polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$, evaluate it at n distinct points x_0, \dots, x_{n-1} .

We can choose which points!

Divide. Break polynomial up into even and odd powers.

- $A(x) = a_0 + a_1 x + a_2 x^2 + a_3 x^3 + a_4 x^4 + a_5 x^5 + a_6 x^6 + a_7 x^7.$
- $A_{\text{even}}(x) = a_0 + a_2 x + a_4 x^2 + a_6 x^3.$
- $A_{\text{odd}}(x) = a_1 + a_3 x + a_5 x^2 + a_7 x^3.$
- $A(x) = A_{\text{even}}(x^2) + x A_{\text{odd}}(x^2).$
- $A(-x) = A_{\text{even}}(x^2) - x A_{\text{odd}}(x^2).$

Goal. Choose n points s.t.

- Can evaluate polynomial of degree $\leq n$ at n points by evaluating two polynomials of degree $\leq \frac{1}{2}n$ at $\frac{1}{2}n$ point.
- But also: can evaluate polynomial of degree $\leq \frac{1}{2}n$ at $\frac{1}{2}n$ points by evaluating two polynomials of degree $\leq \frac{1}{4}n$ at $\frac{1}{4}n$ point, and so on.

Roots of Unity


Def. An n^{th} root of unity is a complex number x such that $x^n = 1$.

Fact. The n^{th} roots of unity are: $\omega^0, \omega^1, \dots, \omega^{n-1}$ where $\omega = e^{2\pi i / n}$.

Pf. $(\omega^k)^n = (e^{2\pi i k / n})^n = (e^{2\pi i})^k = 1^k = 1$.

Fact. The $\frac{1}{2}n^{\text{th}}$ roots of unity are: $v^0, v^1, \dots, v^{n/2-1}$ where $v = e^{4\pi i / n}$.

Fact. $\omega^2 = v$ and $(\omega^2)^k = v^k$.



Discrete Fourier Transform

Coefficient to point-value. Given a polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$, evaluate it at n distinct points x_0, \dots, x_{n-1} .

Key idea: choose $x_k = \omega^k$ where ω is principal n^{th} root of unity.

$$\begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ y_3 \\ \vdots \\ y_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 & 1 & 1 & \dots & 1 \\ 1 & \omega^1 & \omega^2 & \omega^3 & \dots & \omega^{n-1} \\ 1 & \omega^2 & \omega^4 & \omega^6 & \dots & \omega^{2(n-1)} \\ 1 & \omega^3 & \omega^6 & \omega^9 & \dots & \omega^{3(n-1)} \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & \omega^{n-1} & \omega^{2(n-1)} & \omega^{3(n-1)} & \dots & \omega^{(n-1)(n-1)} \end{bmatrix} \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ a_3 \\ \vdots \\ a_{n-1} \end{bmatrix}$$

\uparrow \uparrow
Discrete Fourier transform Fourier matrix F_n

Fast Fourier Transform

Goal. Evaluate a degree $n-1$ polynomial $A(x) = a_0 + \dots + a_{n-1} x^{n-1}$ at its n^{th} roots of unity: $\omega^0, \omega^1, \dots, \omega^{n-1}$.

Divide. Break polynomial up into even and odd powers.

- $A_{\text{even}}(x) = a_0 + a_2x + a_4x^2 + \dots + a_{n/2-2} x^{(n-1)/2}.$
- $A_{\text{odd}}(x) = a_1 + a_3x + a_5x^2 + \dots + a_{n/2-1} x^{(n-1)/2}.$
- $A(x) = A_{\text{even}}(x^2) + x A_{\text{odd}}(x^2).$

Conquer. Evaluate degree $A_{\text{even}}(x)$ and $A_{\text{odd}}(x)$ at the $\frac{1}{2}n^{\text{th}}$ roots of unity: $v^0, v^1, \dots, v^{n/2-1}$.

Combine.

- $A(\omega^k) = A_{\text{even}}(v^k) + \omega^k A_{\text{odd}}(v^k), \quad 0 \leq k < n/2$
- $A(\omega^{k+n/2}) = A_{\text{even}}(v^k) - \omega^k A_{\text{odd}}(v^k), \quad 0 \leq k < n/2$

$$\begin{array}{c} \uparrow \\ \omega^{k+n/2} = -\omega^k \end{array}$$

$$v^k = (\omega^k)^2 = (\omega^{k+n/2})^2$$


FFT Algorithm

```
FFT(n, a0, a1, ..., an-1) {  
    if (n == 1) return a0  
  
    (e0, e1, ..., en/2-1) ← FFT(n/2, a0, a2, a4, ..., an-2)  
    (d0, d1, ..., dn/2-1) ← FFT(n/2, a1, a3, a5, ..., an-1)  
  
    for k = 0 to n/2 - 1 {  
        ωk ← e2πik/n  
        yk ← ek + ωk dk  
        yk+n/2 ← ek - ωk dk  
    }  
  
    return (y0, y1, ..., yn-1)  
}
```

FFT Summary

Theorem. FFT algorithm evaluates a degree $n-1$ polynomial at each of the n^{th} roots of unity in $O(n \log n)$ steps. \uparrow
assumes n is a power of 2

Pf. $T(2n) = 2T(n) + O(n) \Rightarrow T(n) = O(n \log n)$.



Point-Value to Coefficient Representation: Inverse DFT

Goal. Given the values y_0, \dots, y_{n-1} of a degree $n-1$ polynomial at the n points $\omega^0, \omega^1, \dots, \omega^{n-1}$, find unique polynomial $a_0 + a_1 x + \dots + a_{n-1} x^{n-1}$ that has given values at given points.

$$\begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ a_3 \\ \vdots \\ a_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 & 1 & 1 & \dots & 1 \\ 1 & \omega^1 & \omega^2 & \omega^3 & \dots & \omega^{n-1} \\ 1 & \omega^2 & \omega^4 & \omega^6 & \dots & \omega^{2(n-1)} \\ 1 & \omega^3 & \omega^6 & \omega^9 & \dots & \omega^{3(n-1)} \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & \omega^{n-1} & \omega^{2(n-1)} & \omega^{3(n-1)} & \dots & \omega^{(n-1)(n-1)} \end{bmatrix}^{-1} \begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ y_3 \\ \vdots \\ y_{n-1} \end{bmatrix}$$

\uparrow Inverse DFT \uparrow Fourier matrix inverse $(F_n)^{-1}$

Inverse FFT

Claim. Inverse of Fourier matrix is given by following formula.

$$G_n = \frac{1}{n} \begin{bmatrix} 1 & 1 & 1 & 1 & \dots & 1 \\ 1 & \omega^{-1} & \omega^{-2} & \omega^{-3} & \dots & \omega^{-(n-1)} \\ 1 & \omega^{-2} & \omega^{-4} & \omega^{-6} & \dots & \omega^{-2(n-1)} \\ 1 & \omega^{-3} & \omega^{-6} & \omega^{-9} & \dots & \omega^{-3(n-1)} \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & \omega^{-(n-1)} & \omega^{-2(n-1)} & \omega^{-3(n-1)} & \dots & \omega^{-(n-1)(n-1)} \end{bmatrix}$$

Consequence. To compute inverse FFT, apply same algorithm but use $\omega^{-1} = e^{-2\pi i / n}$ as principal n^{th} root of unity (and divide by n).

Inverse FFT: Proof of Correctness

Claim. F_n and G_n are inverses.

Pf.

$$(F_n G_n)_{kk'} = \frac{1}{n} \sum_{j=0}^{n-1} \omega^{kj} \omega^{-jk'} = \frac{1}{n} \sum_{j=0}^{n-1} \omega^{(k-k')j} = \begin{cases} 1 & \text{if } k = k' \\ 0 & \text{otherwise} \end{cases}$$

↑
summation lemma

Summation lemma. Let ω be a principal n^{th} root of unity. Then

$$\sum_{j=0}^{n-1} \omega^{kj} = \begin{cases} n & \text{if } k \equiv 0 \pmod{n} \\ 0 & \text{otherwise} \end{cases}$$

Pf.

- If k is a multiple of n then $\omega^k = 1 \Rightarrow$ sums to n .
- Else: $\omega^k \neq 1$
 - $x^n - 1 = (x - 1)(1 + x + x^2 + \dots + x^{n-1})$
 - Let $x = \omega^k$, we have $0 = \omega^{kn} - 1 = (\omega^k - 1)(1 + \omega^k + \omega^{k(2)} + \dots + \omega^{k(n-1)})$
 - Therefore, $1 + \omega^k + \omega^{k(2)} + \dots + \omega^{k(n-1)} = 0 \Rightarrow$ sums to 0. ▪

Inverse FFT: Algorithm


```
IFFT(n, a0, a1, ..., an-1) {  
    if (n == 1) return a0  
  
    (e0, e1, ..., en/2-1) ← IFFT(n/2, a0, a2, a4, ..., an-2)  
    (d0, d1, ..., dn/2-1) ← IFFT(n/2, a1, a3, a5, ..., an-1)  
  
    for k = 0 to n/2 - 1 {  
        ωk ← e-2πik/n  
        yk ← (ek + ωk dk)  
        yk+n/2 ← (ek - ωk dk)  
    }  
  
    return (y0, y1, ..., yn-1)  
}
```

Note. Need to divide the final result by n .

Inverse FFT Summary


Theorem. Inverse FFT algorithm interpolates a degree $n-1$ polynomial given values at each of the n^{th} roots of unity in $O(n \log n)$ steps.

↑
assumes n is a power of 2



Polynomial Multiplication

Theorem. Can multiply two degree $n-1$ polynomials in $O(n \log n)$ steps.



Integer Multiplication

Integer multiplication. Given two n bit integers $a = a_{n-1} \dots a_1 a_0$ and $b = b_{n-1} \dots b_1 b_0$, compute their product $c = a \times b$.

Convolution algorithm.

- Form two polynomials.
- Note: $a = A(2)$, $b = B(2)$.
- Compute $C(x) = A(x) \times B(x)$.
- Evaluate $C(2) = a \times b$.
- Running time: $O(n \log n)$ complex arithmetic steps.

$$A(x) = a_0 + a_1x + a_2x^2 + \dots + a_{n-1}x^{n-1}$$

$$B(x) = b_0 + b_1x + b_2x^2 + \dots + b_{n-1}x^{n-1}$$

Practice. [GNU Multiple Precision Arithmetic Library] *GMP* proclaims to be "the fastest bignum library on the planet." It uses brute force, Karatsuba, and FFT, depending on the size of n .

Divide-and-Conquer: Chapter Summary

Divide-and-Conquer

Basic idea

- Break up problem into several parts.
- Solve each part recursively.
- Combine solutions to sub-problems into overall solution.

Algorithms

- Mergesort
 - Divide a sequence into two of same size
- Counting inversions
 - Extension of mergesort
- Closest Pair of Points
 - Vertically divide the space

Divide-and-Conquer

Basic idea

- Break up problem into several parts.
- Solve each part recursively.
- Combine solutions to sub-problems into overall solution.

Algorithms

- Integer Multiplication
 - Divide each n -digit integer into two $\frac{1}{2}n$ -digit integers
- Matrix Multiplication
 - Divide each n -by- n matrix into four $\frac{1}{2}n$ -by- $\frac{1}{2}n$ blocks
- Fast Fourier Transform
 - Divide a polynomial into two with even and odd powers