Mnemonic	Format	Opcode	Effect	Notes
ADD m	3/4	18	A ← (A) + (m..m+2)	
ADDF m	3/4	58	F ← (F) + (m..m+5)	X F
ADDR r1,r2	2	90	r2 ← (r2) + (r1)	X
AND m	3/4	40	A ← (A) & (m..m+2)	
CLEAR r1	2	B4	r1 ← 0	X
COMP m	3/4	28	(A) : (m..m+2)	C
COMPF m	3/4	88	(F) : (m..m+5)	X F C
COMPR r1,r2	2	A0	(r1) : (r2)	X C
DIV m	3/4	24	A ← (A) / (m..m+2)	
DIVF m	3/4	64	F ← (F) / (m..m+5)	X F
DIVR r1,r2	2	9C	r2 ← (r2) / (r1)	X
FIX	1	C4	A ← (F) [convert to integer]	X F
FLOAT	1	C0	F ← (A) [convert to floating]	X F
HIO	1	F4	Halt I/O channel number (A)	P X
J m	3/4	3C	PC ← m	
JEQ m	3/4	30	PC ← m if CC set to =	
JGT m	3/4	34	PC ← m if CC set to >	
JLT m	3/4	38	PC ← m if CC set to <	
JSUB m	3/4	48	L ← (PC); PC ← m	
LDA m	3/4	00	A ← (m..m+2)	
LDB m	3/4	68	B ← (m..m+2)	X
LDCH m	3/4	50	A [rightmost byte] ← (m)	
LDF m	3/4	70	F ← (m..m+5)	X F
LDL m	3/4	08	L ← (m..m+2)	
LDS m	3/4	6C	S ← (m..m+2)	X
LDT m	3/4	74	T ← (m..m+2)	X
LDX m	3/4	04	X ← (m..m+2)	
LPS m	3/4	D0	Load processor status from information beginning at address m (see Section 6.2.1)	P X
MUL m	3/4	20	A ← (A) * (m..m+2)	

Mnemonic	Format	Opcode	Effect	Notes
MULF m	3/4	60	F ← (F) * (m..m+5)	X F
MULR r1, r2	2	98	r2 ← (r2) * (r1)	X
NORM	1	C8	F ← (F) [normalized]	X F
OR m	3/4	44	A ← (A) | (m..m+2)	
RD m	3/4	D8	A [rightmost byte] ← data from device specified by (m)	P
RMO r1,r2	2	AC	r2 ← (r1)	X
RSUB	3/4	4C	PC ← (L)	
SHIFTL r1,n	2	A4	r1 ← (r1); left circular shift n bits. {In assembled instruction, r2 = n–1}	X
SHIFTR r1,n	2	A8	r1 ← (r1); right shift n bits, with vacated bit positions set equal to leftmost bit of (r1). {In assembled instruction, r2 = n-1}	X
SIO	1	F0	Start I/O channel number (A); address of channel program is given by (S)	P X
SSK m	3/4	EC	Protection key for address m ← (A) (see Section 6.2.4)	P X
STA m	3/4	0C	m..m+2 ← (A)	
STB m	3/4	78	m..m+2 ← (B)	X
STCH m	3/4	54	m ← (A) [rightmost byte]	
STF m	3/4	80	m..m+5 ← (F)	X F
STI m	3/4	D4	Interval timer value ← (m..m+2) (see Section 6.2.1)	P X
STL m	3/4	14	m..m+2 ← (L)	
STS m	3/4	7C	m..m+2 ← (S)	X
STSW m	3/4	E8	m..m+2 ← (SW)	P
STT m	3/4	84	m..m+2 ← (T)	X
STX m	3/4	10	m..m+2 ← (X)	
SUB m	3/4	1C	A ← (A) – (m..m+2)	
SUBF m	3/4	5C	F ← (F) – (m..m+5)	X F

Mnemonic	Format	Opcode	Effect	Notes
SUBR r1,r2	2	94	r2 ← (r2) – (r1)	X
SVC n	2	B0	Generate SVC interrupt. {In assembled instruction, r1 = n}	X
TD m	3/4	E0	Test device specified by (m)	P C
TIO	1	F8	Test I/O channel number (A)	P X C
TIX m	3/4	2C	X ← (X) + 1; (X): (m..m+2)	C
TIXR r1	2	B8	X ← (X) + 1; (X): (r1)	X C
WD m	3/4	DC	Device specified by (m) ← (A) [rightmost byte]	P