

SMOTE- Gini

Synthetic Minority Oversampling Technique (SMOTE) with 'gini' as criterion for best split.

Importing important libraries and modules.

```
In [1]: import pandas as pd
from sklearn.ensemble import RandomForestClassifier
from imblearn.over_sampling import SMOTE
from sklearn.model_selection import train_test_split # to split the data
from sklearn.metrics import confusion_matrix
import matplotlib.pyplot as plt
import numpy as np
import itertools
from sklearn import tree
```

Loading the data into dataframe. Extracting the features and class variables as well as fraud data.

```
In [2]: data = pd.read_csv('https://people.rit.edu/~hvp4259/project/data/creditcard.csv')
print(data.shape)
X = data.ix[:, data.columns != 'Class']
y = data.ix[:, data.columns == 'Class']
fraud_record = data[data.Class == 1]
y_fraud_record = fraud_record.ix[:, fraud_record.columns == 'Class']
x_fraud_record = fraud_record.ix[:, fraud_record.columns != 'Class']
number_records_fraud = len(data[data.Class == 1])
```

(284807, 31)

Defining the utility function called plot_confusion_matrix for displaying the confusion matrix in a nice UI.

```
In [3]: def plot_confusion_matrix(cm, classes, normalize=False, title='Confusion matrix',
plt.imshow(cm, interpolation='nearest', cmap=cmap)
plt.title(title)
plt.colorbar()
tick_marks = np.arange(len(classes))
plt.xticks(tick_marks, classes, rotation=45)
plt.yticks(tick_marks, classes)
thresh = cm.max() / 2.
for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
    plt.text(j, i, cm[i, j], horizontalalignment="center", color="white" if cm[i, j] > thresh else "black")
plt.tight_layout()
plt.ylabel('True label')
plt.xlabel('Predicted label')
plt.show()
```

Defining the utility function called show_data for displaying precision, recall and accuracy from the confusion matrix.

```
In [4]: def show_data(cm, print_res = 0):
        tp = cm[1,1]
        fn = cm[1,0]
        fp = cm[0,1]
        tn = cm[0,0]
        if print_res == 1:
            print('Precision = {:.5f}'.format(tp/(tp+fp)))
            print('Recall (TPR) = {:.5f}'.format(tp/(tp+fn)))
            print('Accuracy = {:.5f}'.format((tp+tn)/(tp+tn+fp+fn)))
        return tp/(tp+fp), tp/(tp+fn)
```

Definign the utility function called data_preparation for splitting the data into test and trainign datasets.

```
In [5]: def data_prepration(x):
        x_features= x.ix[:,x.columns != "Class"]
        x_labels=x.ix[:,x.columns=="Class"]
        x_features_train,x_features_test,x_labels_train,x_labels_test = train_test_sp
        print("length of training data")
        print(len(x_features_train))
        print("length of test data")
        print(len(x_features_test))
        return(x_features_train,x_features_test,x_labels_train,x_labels_test)
```

Preparing the data, splitting it into test and training dataset.

```
In [6]: data_train_X,data_test_X,data_train_y,data_test_y=data_prepration(data)
        columns = data_train_X.columns
        print("Proportion of Normal data in training data is ",len(data_train_y[data_train_
        print("Proportion of fraud data in training data is ",len(data_train_y[data_train_
```

length of training data

199364

length of test data

85443

Proportion of Normal data in training data is 0.998294576754078

Proportion of fraud data in training data is 0.001705423245922032

Oversampling the highly disbalanced prepared data and balancing the training dataset with the normal : fraud data ratio 0.5 : 0.5.

```
In [7]: os = SMOTE(random_state = 0)
os_data_X, os_data_y = os.fit_sample(data_train_X, data_train_y.values.ravel())
os_data_X = pd.DataFrame(data = os_data_X, columns = columns )
os_data_y = pd.DataFrame(data = os_data_y, columns = ["Class"])
print("length of oversampled data is ",len(os_data_X))
print("Number of normal transcation in oversampled data",len(os_data_y[os_data_y[
print("Number of fraud transcation",len(os_data_y[os_data_y["Class"]==1]))
print("Proportion of Normal data in oversampled data is ",len(os_data_y[os_data_y[
print("Proportion of fraud data in oversampled data is ",len(os_data_y[os_data_y[
```

```
length of oversampled data is 398048
Number of normal transcation in oversampled data 199024
Number of fraud transcation 199024
Proportion of Normal data in oversampled data is 0.5
Proportion of fraud data in oversampled data is 0.5
```

Training the model with RandomForestClassifier having 100 trees in the forest with criterion for best split as 'gini'.

```
In [8]: clf= RandomForestClassifier(n_estimators = 100, criterion = 'gini')
clf.fit(os_data_X, os_data_y.values.ravel())
```

```
Out[8]: RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
max_depth=None, max_features='auto', max_leaf_nodes=None,
min_impurity_split=1e-07, min_samples_leaf=1,
min_samples_split=2, min_weight_fraction_leaf=0.0,
n_estimators=100, n_jobs=1, oob_score=False, random_state=None,
verbose=0, warm_start=False)
```


Saving all 100 trees to the local drive in .dot format.

```
In [10]: #i_tree = 0
#for tree_in_forest in clf.estimators_:
#    with open('F:/RIT/Sem 2/AT/random_forest_gini/tree_' + str(i_tree) + '.dot',
#            my_file = tree.export_graphviz(tree_in_forest, out_file = my_file)
#    i_tree = i_tree + 1'''
```

Applying the model on test data.

```
In [11]: pred = clf.predict(data_test_X)
cm = confusion_matrix(data_test_y.values.ravel(), pred)
print(cm)
plot_confusion_matrix(cm, ['0', '1'], title = 'Confusion Matrix- Test Data')
pr, tpr = show_data(cm, print_res = 1);
```

```
[[85266   25]
 [   34  118]]
```




Precision = 0.82517
Recall (TPR) = 0.77632
Accuracy = 0.99931

Applying the model on the entire dataset.

```
In [12]: pred = clf.predict(X)
cm = confusion_matrix(y, pred)
print(cm)
plot_confusion_matrix(cm, ['0', '1'], title = 'Confusion Matrix- Entire Dataset')
pr, tpr = show_data(cm, print_res = 1);
```

```
[[284290    25]
 [    34   458]]
```



Precision = 0.94824
Recall (TPR) = 0.93089
Accuracy = 0.99979

Applying the model on only the fraud data instances.

```
In [13]: pred = clf.predict(x_fraud_record)
cm = confusion_matrix(y_fraud_record, pred)
print(cm)
plot_confusion_matrix(cm, ['0', '1'], title = 'Confusion Matrix- Only fraud records',
pr, tpr = show_data(cm, print_res = 1);
```

```
[[ 0  0]
 [34 458]]
```



Precision = 1.00000
Recall (TPR) = 0.93089
Accuracy = 0.93089