Deployment guide: overview

This sample guide describes a small deployment. Step one is to build the container image. Step two is to push the image to a registry. Step three is to apply the Kubernetes manifests. Always verify the rollout status before sending traffic to the new version. This sample guide describes a small deployment. Step one is to build the container image. Step two is to push the image to a registry. Step three is to apply the Kubernetes manifests. Always verify the rollout status before sending traffic to the new version. This sample guide describes a small deployment. Step one is to build the container image. Step two is to push the image to a registry. Step three is to apply the Kubernetes manifests. Always verify the rollout status before sending traffic to the new version. This sample guide describes a small deployment. Step one is to build the container image. Step two is to push the image to a registry. Step three is to apply the Kubernetes manifests. Always verify the rollout status before sending traffic to the new version. This sample guide describes a small deployment. Step one is to build the container image. Step two is to push the image to a registry. Step three is to apply the Kubernetes manifests. Always verify the rollout status before sending traffic to the new version.

Authentication process

Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one. Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one. Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one. Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one. Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one. Users authenticate with a short lived token issued by the identity provider. The API gateway validates the token signature and expiry on every request. Expired tokens are rejected and the client must request a new one.

Troubleshooting

If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods. If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods. If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods. If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods. If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods. If a pod stays in Pending, check node resources and scheduling events. If a pod restarts repeatedly, read the previous container logs. If a service is unreachable, confirm the selector labels match the pods.