

Hierarchical_2

Janice Hsu

2023-09-15

```
# Required Libraries
```

```
library(zoo)
```

```
##
```

```
## Attaching package: 'zoo'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      as.Date, as.Date.numeric
```

```
library(ggplot2)
```

```
library(lubridate)
```

```
##
```

```
## Attaching package: 'lubridate'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      date, intersect, setdiff, union
```

```
library(tsibble)
```

```
##
```

```
## Attaching package: 'tsibble'
```

```
## The following object is masked from 'package:lubridate':
```

```
##
```

```
##      interval
```

```
## The following object is masked from 'package:zoo':
```

```
##
```

```
##      index
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      intersect, setdiff, union
```

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr 1.1.2 v stringr 1.5.0
## v forcats 1.0.0 v tibble 3.2.1
## v purrr 1.0.1 v tidyr 1.3.0
## v readr 2.1.4

## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x tsibble::interval() masks lubridate::interval()
## x dplyr::lag() masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(fpp3)
```

```
## -- Attaching packages ----- fpp3 0.5 --
## v tsibbledata 0.4.1 v fable 0.3.3
## v feasts 0.3.1 v fabletools 0.3.3
## -- Conflicts ----- fpp3_conflicts --
## x lubridate::date() masks base::date()
## x dplyr::filter() masks stats::filter()
## x tsibble::index() masks zoo::index()
## x tsibble::intersect() masks base::intersect()
## x tsibble::interval() masks lubridate::interval()
## x dplyr::lag() masks stats::lag()
## x tsibble::setdiff() masks base::setdiff()
## x tsibble::union() masks base::union()
```

```
library(hts)
```

```
## Loading required package: forecast
## Registered S3 method overwritten by 'quantmod':
## method from
## as.zoo.data.frame zoo
##
## Attaching package: 'forecast'
##
## The following object is masked from 'package:fabletools':
##
## accuracy
```

```
library(dplyr)
library(tidyr)
library(forecast)
```

```
data <- read.csv("HLTH0037_ts_cleaned.csv")
```


```
data1 <- data %>%
  mutate(YearMonth = yearmonth(YearMonth)) %>%
  as_tsibble(index = YearMonth, key = c(Age_Code, Sex_ItemName_ENG, Hospital_Code, Hospital_ItemName_ENG))

data1 <- data1 %>%
  mutate(Number = 1)
```

#Number of patients entering ED under different hospital hierarchy

```
data1_hts <- data1 %>%
  aggregate_key(Organisation/Hospital_ItemName_ENG, Number = sum(Number))

data1_hts |>
  filter(is_aggregated(Hospital_ItemName_ENG)) |>
  autoplot(Number) +
  labs(y = "Number of patients",
       title = "Number of patients who enter ED") +
  facet_wrap(vars(Organisation), scales = "free_y", ncol = 3) +
  theme(legend.position = "none") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```



- A couple of Local Health Boards (LHBs) were redefined from the 1st of April 2019 onwards: Cwm Taf (27)→ Cwm Taf Morgannwg (30)// Abertawe Bro Morgannwg (26) → Swansea Bay (31). Therefore, if you decide to forecast at LHB resolution, you might want to consider these 4 as a unique one.
- A the Princess of Wales Hospital changed its Local Health Boards
- So we analyse these 4 as one organisation

Group the changed Local Health Board together

```
data1_grouped <- data1 %>%  
  mutate(Grouped_Organisation = case_when(  
    Organisation %in% c("Cwm Taf", "Cwm Taf Morgannwg", "Abertawe Bro Morgannwg", "Swansea Bay") ~ "Gronfa  
    TRUE ~ Organisation  
  ))
```

There are 6 Local Health Boards

```
unique(data1_grouped$Grouped_Organisation)
```


```
## [1] "Betsi Cadwaladr"      "Hywel Dda"           "Grouped_organisation"  
## [4] "Cardiff & Vale"       "Aneurin Bevan"       "Powys Teaching"
```

```
data2_hts <- data1_grouped %>%  
  group_by(Grouped_Organisation) %>%  
  summarise(Number = sum(Number))
```

Number of patients who enter ED under 6 different local health boards

```
data2_hts |>  
  ggplot(aes(x = YearMonth, y = Number)) +  
  geom_line(stat = "identity") +  
  labs(y = "Number of patients",  
       title = "Number of patients who enter ED") +  
  facet_wrap(vars(Grouped_Organisation), scales = "free_y", ncol = 3) +  
  theme(legend.position = "none") +  
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

Number of patients who enter ED



Change the Age_Code structure into different groups

```
unique(data1_grouped$Age_Code)
```


```
## [1] "0 to 4" "18 to 24" "25 to 29" "30 to 34" "35 to 39" "40 to 44"
## [7] "45 to 49" "5 to 17" "50 to 54" "55 to 59" "60 to 64" "65 to 69"
## [13] "70 to 74" "75 to 79" "80 to 84" "85" "Unknown"
```

Age group: “0-4”, “5-17”, “18-69”, “70^”

```
data1_grouped_age <- data1_grouped %>%
  filter(Age_Code != "Unknown") %>%
  mutate(Grouped_Age = case_when(
    Age_Code == "0 to 4" ~ "0-4",
    Age_Code == "5 to 17" ~ "5-17",
    Age_Code %in% c("18 to 24", "25 to 29", "30 to 34", "35 to 39",
                  "40 to 44", "45 to 49", "50 to 54", "55 to 59",
                  "60 to 64", "65 to 69") ~ "18-69",
    Age_Code %in% c("70 to 74", "75 to 79", "80 to 84", "85") ~ "70 and over",
    TRUE ~ "Other"
  ))
```

Plot Number of Patients in different age groups

```
data1_gts <- data1_grouped_age %>%  
  filter(Sex_ItemName_ENG != "Not Specified or invalid") %>%  
  group_by(Grouped_Age, Sex_ItemName_ENG) %>%  
  summarize(Number = sum(Number, na.rm = TRUE))  
  
ggplot(data1_gts, aes(x = Grouped_Age, y = Number)) +  
  geom_bar(stat = "identity") +  
  labs(y = "Number of patients") +  
  theme(axis.text.x = element_text(angle = 45, hjust = 1)) +  
  facet_wrap(~ Sex_ItemName_ENG, scales = "free")
```



#Change the data into wide format

```
data2_wide <- data1_grouped %>%  
  group_by(Grouped_Organisation) %>%  
  index_by(YearMonth) %>%  
  summarise(Number = sum(Number)) %>%  
  pivot_wider(names_from = Grouped_Organisation, values_from = Number)
```

Forecast under Total (hierarchy 1) and Local Health Board (Hierarchy 2)


```
# Create the hierarchical time series object
hts_data <- hts(data2_wide[, -1]) # exclude the YearMonth column
```

```
## Since argument characters are not specified, the default labelling system is used.
```


```
# Forecast using the hierarchical model
forecasts_hts <- forecast(hts_data)
```

```
# Plot the forecasts
plot(forecasts_hts)
```

Level 0



Level 1



```
# If you want to inspect the forecasts for the aggregated level:
aggregated_forecast <- forecasts_hts$allcasts$Total
```

```
# If you want to inspect the forecasts for an individual health board, say "Aneurin Bevan":
aneurin_bevan_forecast <- forecasts_hts$allcasts$`Aneurin Bevan`
```

```
str(forecasts_hts)
```

```
## List of 6
## $ bts : Time-Series [1:10, 1:6] from 136 to 145: 161 161 161 161 161 ...
## ..- attr(*, "dimnames")=List of 2
## .. ..$ : NULL
## .. ..$ : chr [1:6] "Aneurin Bevan" "Betsi Cadwaladr" "Cardiff & Vale" "Grouped_organisation" ...
## $ histy : Time-Series [1:135, 1:6] from 1 to 135: 130 130 132 131 130 137 130 132 131 131 ...
## ..- attr(*, "dimnames")=List of 2
## .. ..$ : NULL
## .. ..$ : chr [1:6] "Aneurin Bevan" "Betsi Cadwaladr" "Cardiff & Vale" "Grouped_organisation" ...
## $ labels :List of 2
## ..$ Level 0: chr "Total"
## ..$ Level 1: chr [1:6] "Aneurin Bevan" "Betsi Cadwaladr" "Cardiff & Vale" "Grouped_organisation" .
## $ method : chr "comb"
## $ fmethod: chr "ets"
## $ nodes :List of 1
## ..$ Level 1: int 6
## - attr(*, "class")= chr [1:2] "hts" "gts"
```

- bts: This contains the forecasts for the different series. It's a time-series matrix.
- histy: This represents the historical data for the different series.
- labels: This list contains labels for the different levels in the hierarchy.
- method, fmethod: These are metadata about the forecasting process, indicating the method used for forecasting and combination.
- nodes: Information about the nodes at different levels in the hierarchy.

```
# Dates for Historical Data
start_date <- yearmonth("2012 Apr")
end_date <- yearmonth("2023 Jun")
hist_dates <- seq(as.Date(start_date), as.Date(end_date), by = "1 month") %>% yearmonth()

# Extract historical time series data from the hts object
historical_data <- zoo(forecasts_hts$histy, order.by = hist_dates)

# Adjusting the forecast start date
forecast_start_date <- as.Date(end_date) %>%
  add_with_rollback(months(1)) %>%
  yearmonth()

forecast_dates <- seq(as.Date(forecast_start_date), by = "1 month", length.out = 10) %>% yearmonth()

# Extract forecast data from the hts object
forecast_data <- zoo(forecasts_hts$bts, order.by = forecast_dates)

# Combine historical and forecast data for plotting
combined_data <- rbind(historical_data, forecast_data)

# Convert the combined data to a long data frame for ggplot
df <- as.data.frame(fortify(combined_data, melt = TRUE))
names(df) <- c("Date", "Health_Board", "Number")

# Plot
ggplot(df, aes(x = Date, y = Number, color = Health_Board)) +
  geom_line() +
  labs(title = "Hierarchical Time Series Forecast",
```



```

x = "YearMonth",
y = "Number",
color = "Health Board") +
scale_x_yearmonth(name = "YearMonth",
                  labels = function(x) format(x, "%b %Y"),
                  breaks = yearmonth(seq(as.Date(start_date), by = "1 year", length.out = 12))) +
theme_minimal() +
theme(axis.text.x = element_text(angle = 45, hjust = 1))

```

Hierarchical Time Series Forecast

