

# forecasting ED

Janice Hsu

2023-08-28

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.2      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr      1.0.1
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(fpp3)
```

```
## -- Attaching packages ----- fpp3 0.5 --
## v tsibble     1.1.3      v fable      0.3.3
## v tsibbledata 0.4.1      v fabletools 0.3.3
## v feasts      0.3.1
## -- Conflicts ----- fpp3_conflicts --
## x lubridate::date() masks base::date()
## x dplyr::filter()   masks stats::filter()
## x tsibble::intersect() masks base::intersect()
## x tsibble::interval() masks lubridate::interval()
## x dplyr::lag()       masks stats::lag()
## x tsibble::setdiff() masks base::setdiff()
## x tsibble::union()   masks base::union()
```

```
library(hts)
```

```
## Loading required package: forecast
## Registered S3 method overwritten by 'quantmod':
##   method                from
## as.zoo.data.frame zoo
##
## Attaching package: 'forecast'
##
## The following object is masked from 'package:fabletools':
##
##   accuracy
```

```
data <- read.csv("HLTH0037_ts_cleaned.csv")
```

```
data %>%  
  select(Hospital_Hierarchy, Organisation) %>%  
  unique()
```

```
##      Hospital_Hierarchy      Organisation  
## 1      W11000023      Betsi Cadwaladr  
## 1171     W11000025      Hywel Dda  
## 1931     W11000031      Swansea Bay  
## 2033     W11000026      Abertawe Bro Morgannwg  
## 2364     W11000029      Cardiff & Vale  
## 2628     W11000030      Cwm Taf Morgannwg  
## 2868     W11000027      Cwm Taf  
## 3203     W11000028      Aneurin Bevan  
## 3775     W11000024      Powys Teaching
```

```
data1 <- data %>%  
  mutate(YearMonth = yearmonth(YearMonth)) %>%  
  as_tsibble(index = YearMonth, key = c(Age_Code, Sex_ItemName_ENG, Hospital_Code, Hospital_ItemName_ENG))  
  
data1 <- data1 %>%  
  mutate(Number = 1)
```

*#Produce a table or plot to show the hierarchy between the organisation and hospital hierarchy*

```
data2 <- data1 %>%  
  select(YearMonth, Hospital_ItemName_ENG, Hospital_Hierarchy, Organisation, Number)
```

```
# Convert to data.table  
library(data.table)
```

```
##  
## Attaching package: 'data.table'  
  
## The following object is masked from 'package:tsibble':  
##  
##      key  
  
## The following objects are masked from 'package:lubridate':  
##  
##      hour, isoweek, mday, minute, month, quarter, second, wday, week,  
##      yday, year  
  
## The following objects are masked from 'package:dplyr':  
##  
##      between, first, last  
  
## The following object is masked from 'package:purrr':  
##  
##      transpose
```

```

setDT(data2)

# Create a hierarchical table using data.table operations
hierarchical_table <- data2[, .(Total = sum(Number)), by = .( Organisation, Hospital_ItemName_ENG)]

knitr::kable(hierarchical_table)

```


Organisation	Hospital_ItemName_ENG	Total
Betsi Cadwaladr	Ysbyty Glan Clwyd	4437
Betsi Cadwaladr	Wrexham Maelor Hospital	4478
Betsi Cadwaladr	Colwyn Bay Community Hospital	340
Betsi Cadwaladr	Holywell Community Hospital	394
Betsi Cadwaladr	Mold Community Hospital	682
Betsi Cadwaladr	Ysbyty Gwynedd	4381
Betsi Cadwaladr	Llandudno General Hospital	4342
Betsi Cadwaladr	Bryn Beryl Hospital	4058
Betsi Cadwaladr	Dolgellau And Barmouth District Hospital	3066
Betsi Cadwaladr	Ffestiniog Memorial Hospital	65
Betsi Cadwaladr	Tywyn & District War Memorial Hospital	2897
Betsi Cadwaladr	Ysbyty Alltwen	4315
Betsi Cadwaladr	Ysbyty Penrhos Stanley	4320
Hywel Dda	Glangwili General Hospital	4353
Hywel Dda	Llandovery Hospital	1320
Hywel Dda	Bronglais General Hospital	4339
Hywel Dda	Cardigan And District Memorial Hospital	921
Hywel Dda	Prince Philip Hospital	4339
Hywel Dda	Withybush General Hospital	4349
Hywel Dda	S. Pembs Hosp. Health & Social Care Res Centre	607
Hywel Dda	New Tenby Cottage Hospital Outpatients	2977
Hywel Dda	Cardigan Integrated Care Centre	1368
Swansea Bay	Morriston Hospital	1653
Swansea Bay	Neath Port Talbot Hospital	1646
Abertawe Bro Morgannwg	Princess Of Wales Hospital	2764
Abertawe Bro Morgannwg	Singleton Hospital	2558
Abertawe Bro Morgannwg	Morriston Hospital	2716
Abertawe Bro Morgannwg	Neath Port Talbot Hospital	2706
Cardiff & Vale	University Hospital Of Wales	4633
Cardiff & Vale	The Barry Hospital	4158
Cwm Taf Morgannwg	Princess Of Wales Hospital	1686
Cwm Taf Morgannwg	The Royal Glamorgan Hospital	1717
Cwm Taf Morgannwg	Prince Charles Hospital	1680
Cwm Taf Morgannwg	Ysbyty Cwm Rhondda	1602
Cwm Taf Morgannwg	Ysbyty Cwm Cynon	1250
Cwm Taf	The Royal Glamorgan Hospital	2712
Cwm Taf	Prince Charles Hospital	2718
Cwm Taf	Aberdare General Hospital	32
Cwm Taf	Ysbyty Cwm Rhondda	2610
Cwm Taf	Ysbyty Cwm Cynon	2652
Aneurin Bevan	Nevill Hall Hospital	4402
Aneurin Bevan	Royal Gwent Hospital	4465
Aneurin Bevan	Ysbyty Aneurin Bevan	4328
Aneurin Bevan	Ysbyty Ystrad Fawr	4387

Organisation	Hospital_ItemName_ENG	Total
Aneurin Bevan	The Grange Hospital	1055
Powys Teaching	Llandrindod Wells Hospital	4319
Powys Teaching	Victoria Memorial Hospital	4294
Powys Teaching	Breconshire War Memorial Hospital	4323
Powys Teaching	Ystradgynlais Community Hospital	3951

*#Number of patients entering ED under different hospital hierarchy*

```
data1_hts <- data1 %>%
  aggregate_key(Organisation/Hospital_ItemName_ENG, Number = sum(Number))

data1_hts |>
  filter(is_aggregated(Hospital_ItemName_ENG)) |>
  autoplot(Number) +
  labs(y = "Number of patients",
       title = "Number of patients who enter ED") +
  facet_wrap(vars(Organisation), scales = "free_y", ncol = 3) +
  theme(legend.position = "none")+
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```



- A couple of Local Health Boards (LHBs) were redefined from the 1st of April 2019 onwards: Cwm Taf (27)→ Cwm Taf Morgannwg (30)// Abertawe Bro Morgannwg (26) → Swansea Bay (31). Therefore, if you decide to forecast at LHB resolution, you might want to consider these 4 as a unique one.
- At the Princess of Wales Hospital changed its Local Health Boards
- So we analyse these 4 as one organisation

```
data1_grouped <- data1 %>%
  mutate(Grouped_Organisation = case_when(
    Organisation %in% c("Cwm Taf", "Cwm Taf Morgannwg", "Abertawe Bro Morgannwg", "Swansea Bay") ~ "Gronfa",
    TRUE ~ Organisation
  ))
```


```
unique(data1_grouped$Grouped_Organisation)
```

```
## [1] "Betsi Cadwaladr"      "Hywel Dda"            "Grouped_organisation"
## [4] "Cardiff & Vale"       "Aneurin Bevan"        "Powys Teaching"
```

```
data2_hts <- data1_grouped %>%
  group_by(Grouped_Organisation) %>%
  summarise(Number = sum(Number))
```

```
data2_hts |>
  ggplot(aes(x = YearMonth, y = Number)) +
  geom_line(stat = "identity") +
  labs(y = "Number of patients",
       title = "Number of patients who enter ED") +
  facet_wrap(vars(Grouped_Organisation), scales = "free_y", ncol = 3) +
  theme(legend.position = "none") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

## Number of patients who enter ED



```
#library(gt)

#data2_hts %>%
#gt() %>%
#tab_header(title = "Number of patients who enter ED") %>%
#cols_label(
#  YearMonth = "Year/Month",
#  Number = "Number of Patients",
#  Grouped_Organisation = "Organisation Group"
#)
```

```
unique(data1_grouped$Age_Code)
```


```
## [1] "0 to 4" "18 to 24" "25 to 29" "30 to 34" "35 to 39" "40 to 44"
## [7] "45 to 49" "5 to 17" "50 to 54" "55 to 59" "60 to 64" "65 to 69"
## [13] "70 to 74" "75 to 79" "80 to 84" "85" "Unknown"
```

Age group: "0-4", "5-17", "18-69", "70^"

```
data1_grouped_age <- data1_grouped %>%
  filter(Age_Code != "Unknown") %>%
  mutate(Grouped_Age = case_when(
    Age_Code == "0 to 4" ~ "0-4",
    Age_Code == "5 to 17" ~ "5-17",
    Age_Code %in% c("18 to 24", "25 to 29", "30 to 34", "35 to 39",
                  "40 to 44", "45 to 49", "50 to 54", "55 to 59",
                  "60 to 64", "65 to 69") ~ "18-69",
    Age_Code %in% c("70 to 74", "75 to 79", "80 to 84", "85") ~ "70 and over",
    TRUE ~ "Other"
  ))
```

```
data1_gts <- data1_grouped_age %>%
  filter(!Sex_ItemName_ENG == "Not Specified or invalid") %>%
  aggregate_key(Grouped_Age* Sex_ItemName_ENG , Number = sum(Number))

data1_gts |>
  filter(!is_aggregated(Sex_ItemName_ENG), !is_aggregated(Grouped_Age)) |>
  autoplot(Number) +
  labs(y = "Number of patients")+
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```




```
# Number of patients entering ED, facet by sex

data3_ghts <- data1_grouped_age %>%
  aggregate_key((Grouped_Organisation/Hospital_Hierarchy)* Sex_ItemName_ENG , Number = sum(Number))

data3_ghts |>
  filter(!is_aggregated(Hospital_Hierarchy)) |>
  autoplot(Number) +
  labs(y = "Number of patients",
       title = "Number of patients who enter ED") +
  facet_wrap(vars(Sex_ItemName_ENG), scales = "free_y", ncol = 3) +
  theme(legend.position = "none")+
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

## Number of patients who enter ED



```
data1_full <- data1_grouped_age |>
  aggregate_key(Grouped_Organisation/Hospital_ItemName_ENG, Number = sum(Number))

data1_full$key_combined <- paste(data1_full$Grouped_Organisation, data1_full$Hospital_ItemName_ENG, sep = "_")

library(lubridate)

data1_wide <- data1_full %>%
  pivot_wider(names_from = key_combined, values_from = Number)

library(hts)

reconcile_data1_wide_paths <- function(data1_full) {

  # Convert to regular data frame to bypass tsibble constraints
  data1_full <- as.data.frame(data1_full)

  # Convert YearMonth to date
  data1_wide <- data1_full %>%
    unite("key_column", Grouped_Organisation, Hospital_ItemName_ENG, sep = "_") %>%
    pivot_wider(names_from = key_column, values_from = Number, values_fill = list(Number = 0))
}
```



```

# Convert the data to a gts object
ts_data <- ts(data1_wide[, -1], frequency = 12, start = c(year(min(ymd(paste0(data1_wide$YearMonth, "-"))), 12), 1))
gts_obj <- hts(ts_data)

return(gts_obj)
}

```

```

# Calling the function
gts_obj = reconcile_data1_wide_paths(data1_full)

```

## Since argument characters are not specified, the default labelling system is used.

```

# First, forecast each individual series with ets
individual_forecasts <- lapply(1:ncol(gts_obj[[1]]), function(i) {
  ets_forecast <- forecast(ets(gts_obj[[1]][,i]), h = 6)
  return(ets_forecast$mean)
})

# Combine the forecasts into a matrix
forecast_matrix <- do.call(cbind, individual_forecasts)

# Now, reconcile the forecasts using hts
gts_forecast_matrix <- ts(forecast_matrix, frequency = 12)
gts_forecasts <- hts(gts_forecast_matrix)

```

## Since argument characters are not specified, the default labelling system is used.

```

reconciled_forecasts <- forecast(gts_forecasts, method = "bu")

# Print the reconciled forecasts
print(reconciled_forecasts)

```

```

## Hierarchical Time Series
## 2 Levels
## Number of nodes at each level: 1 50
## Total number of series: 51
## Number of observations in each historical series: 6
## Number of forecasts per series: 24
## Top level series of forecasts:
##      Jan      Feb      Mar      Apr      May      Jun      Jul      Aug
## 1                                81.52277 81.59813
## 2 81.97494 82.05030 82.12566 82.20102 82.27639 82.35175 82.42711 82.50247
## 3 82.87928 82.95464 83.03000 83.10536 83.18072 83.25609
##      Sep      Oct      Nov      Dec
## 1 81.67349 81.74885 81.82422 81.89958
## 2 82.57783 82.65319 82.72856 82.80392
## 3

```

Forecasting Each Series with ets:

```
individual_forecasts <- lapply(1:ncol(gts_obj[[1]]), function(i) {
  ets_forecast <- forecast(ets(gts_obj[[1]][,i]), h = 6)
  return(ets_forecast$mean)
})
```

Combine the Forecasts into a Matrix

```
forecast_matrix <- do.call(cbind, individual_forecasts)
```

Convert to HTS Structure:

```
gts_forecast_matrix <- ts(forecast_matrix, frequency = 12)
gts_forecasts <- hts(gts_forecast_matrix)
```

## Since argument characters are not specified, the default labelling system is used.

Reconcile the Forecasts:

```
reconciled_forecasts <- forecast(gts_forecasts, method = "bu", h = 6)
```

```
print(reconciled_forecasts)
```

```
## Hierarchical Time Series
## 2 Levels
## Number of nodes at each level: 1 50
## Total number of series: 51
## Number of observations in each historical series: 6
## Number of forecasts per series: 6
## Top level series of forecasts:
##      Jul      Aug      Sep      Oct      Nov      Dec
## 1 81.52277 81.59813 81.67349 81.74885 81.82422 81.89958
```