



CRICOS PROVIDER 00123M

School of Computer Science

COMP SCI 1103/2103 Algorithm Design & Data Structure

Searching + more complexity examples

adelaide.edu.au

seek LIGHT

Overview

- Binary search
- Analysis of recursive algorithms: simple methods in this course
- Examples for finding Complexity
 - Binary Search
 - GCD
 - Fibonacci
 - Maximum Subsequence Sum Problem

Complexity Analysis

- How to prove things:
 - If we want to prove Big-oh (and other) notation, the only thing we can rely on is the formal definition.
 - Sometimes, if we want to disprove some statement, at least one counterexample will work.
- We will see examples later.

Searching an array

- Array access is $O(1)$
- But if we search for an element in an array, what's the worst case? What's the best case?
- What are your assumptions?
- Do these assumptions matter?
- What's the big-O for searching an array, if we can't make any assumptions about its contents?

Searching an array

- If we know that the data is sorted then we can make assumptions about where the thing that we're searching for is.
- I have an integer array of unique integers 1,2,3,4,...,10, inserted into locations 0..9 in order.
- What can I say about all of the elements from location 0 to location 4?
- What if they weren't in order?

Binary Search

- In binary search we locate the middle element in our structure, or nearest to middle element, and look at it.
- Is it what we're looking for? Stop.
- Is it less than what we're looking for? Look at the elements larger than this one.
- Is it greater? Look at the smaller elements?
- Have we run out of elements? Stop!

Binary Search

```
bool binarySearch(int arr[], int obj, int start, int end){  
    while (start <= end){  
        int middle = (start+end)/2;  
        if(arr[middle] == obj)  
            return true;  
        else if(arr[middle] > obj)  
            end = middle-1;  
        else  
            start = middle +1;  
    }  
    return false  
}
```

Binary Search

- Benefits:
 - We halve the search space each time. Locating the middle element in an array is an $O(1)$ operation, so it doesn't add complexity.
 - We know if the element isn't there without having to search everything.
- What complexity is binary search?

Binary Search

- In binary search we:
 - halve the search space every time
 - don't have to search every element
- Intuitively, this is better than $O(n)$. But what is it?
- We keep halving the search space - so it's better than $O(n/2)$... $O(\log_2 n) = O(\log n)$, usually we drop the 2
- This is for worst case! Let's have a look at the average case as well.

Searching

- Sorted data can be searched faster
- So if we can search sorted data in $O(\log n)$, this is a strong motivation to sort it in the first place.
- You've already seen selection sort and insertion sort in CS1102.
- What are their complexities?
- Why would we take the effort to sort, given that sorting effort is $\geq O(n)$?

Sorting and Searching

- Sort once, search a lot
- We assume that, most of the time, we will search data far more frequently than we will sort it.
- Thus, a once-off sorting cost of $O(n^2)$ is acceptable, if we can then search at $O(\log n)$ thereafter.

Complexity Analysis Example

```
int gcdIter(int a, int b){  
    int minV = min(a,b);  
  
    for(int gcd = minV; gcd >=1; gcd --){  
        // upper bound to the lower bound  
        if((a % gcd ==0) && (b % gcd ==0)) {  
            return gcd;  
        }  
    }  
    return 1;  
}
```

Complexity Analysis

- Procedure for computing the running time:
 - Determine the bounds on the running times of the statements
 - Proceed up the program structure tree
 - Analyze compound statements only after their constituent parts have been analyzed
- Analysing programs is not always trivial

Example

- Euclid's Algorithm for computing the greatest common divisor.

```
int gcd(int a, int b){
    if(a == b){
        return a;
    }

    if(a < b){
        int tmp = a;
        a = b;
        b = tmp;
    }

    // a > b is for sure from this point

    int c = a % b;
    if(c == 0){
        return b;
    }else{
        return gcd(b,c);
    }
}
```

```
int gcd(int a, int b){
    while(b != 0){
        int remainder = a % b;
        a = b;
        b = remainder;
    }

    return a;
}
```

Try with 100 and 94
94 and 6
6 and 4
Try with 100 and 65
65 and 35
35 and 30

Example

```
int gcd(int a, int b){  
    while(b != 0){  
        int remainder = a % b;  
        a = b;  
        b = remainder;  
    }  
    return a;  
}
```

- The size of the while loop depends on how long the sequence of remainders is.
- What is the relationship between the input size and the length of the remainder sequence?
- We can prove that after two iterations, the remainder is at most half of its original value.
 - Therefore, the complexity is $O(2\log n) = O(\log n)$

Complexity Analysis

- How to analyze recursive functions
- It can be quite complicated.
- If the recursion is really just a thinly veiled loop, the analysis is usually trivial

```
int fac(int n){  
    if(n <= 1){  
        return 1;  
    }else{  
        return n*fac(n-1);  
    }  
}
```

$$T(1)=c'$$

$$T(n)=c+T(n-1)$$

$$\text{Gives us } nc+c' = O(n)$$

Example

- However, when more than one recursive call is done in the function, it is difficult to convert the recursion into a simple loop structure.
- Recursive Fibonacci has a growth rate of:
- $1/\sqrt{5} \left(\left(\frac{1+\sqrt{5}}{2} \right)^n - \left(\frac{1-\sqrt{5}}{2} \right)^n \right)$
 - complicated for this course!
- We can show that it is in $\Omega((3/2)^n)$

```
int fib(int n){  
    if(n<=1)  
        return 1;  
    else  
        return fib(n-1)+fib(n-2);  
}
```



THE UNIVERSITY
of ADELAIDE