



THE UNIVERSITY
of ADELAIDE



CRICOS PROVIDER 00123M

School of Computer Science

COMP SCI 1103/2103 Algorithm Design & Data Structure

Review of Pointers

adelaide.edu.au

seek LIGHT

Review of Pointers

In this lecture, we are going to give more details and see more examples on:

- The concepts of pointers
- Talk about pointer arithmetic
- Discuss arrays and strings

Review of Pointers

- Pointer: the memory address of a variable.
- How to define and use them?

```
double d;  
double * ptr=&d;  
cout << ptr <<endl << *ptr << endl;
```

Review of Pointers

- Pointers are variables of the same size as integers
- But are they exactly the same thing?

```
int p;  
int *ptr;
```

- Abstraction
- Compile time: the compiler knows some more information about a pointer variable

`ptr=ptr+1;` (increments ptr by `sizeof(*ptr)`)

Pointer Arithmetic

```
1  #include <iostream>
2  using namespace std;
3
4  main() {
5      int x, *xp;
6      double y, *yp;
7      char z, *zp;
8      class {
9          int temp[1000];
10     } c, *cp;
11
12     cout << sizeof(x) << endl;
13     cout << sizeof(y) << endl;
14     cout << sizeof(z) << endl;
15     cout << sizeof(c) << endl;
16
17     cout << sizeof(xp) << endl;
18     cout << sizeof(yp) << endl;
19     cout << sizeof(zp) << endl;
20     cout << sizeof(cp) << endl;
21 }
22
```

```
cout<< sizeof(*xp)<<endl;
cout<< sizeof(*yp)<<endl;
cout<< sizeof(*zp)<<endl;
cout<< sizeof(*cp)<<endl;
```

Pointer Arithmetic

Operation	Result
Address + number	Address
Address - number	Address
Address - Address	Number
Address + Address	Illegal

Example

```
int *ptr1, *ptr2;  
  
ptr1 = 100;  
ptr2 = 108;  
  
cout << ptr2 - ptr1 << endl;
```

Output: 2

What about 'cout << *ptr2 - *ptr1 << endl;' ?

Example

```
int *xp=&p;  
double *yp=&d;  
class {  
    int temp[1000];  
} c1, *cp=&c1;
```

```
cout<< xp<<endl;  
cout<< yp<<endl;  
cout<< cp<<endl;
```

```
cout<< xp+1<<endl;  
cout<< yp+1<<endl;  
cout<< cp+1<<endl;
```

```
0x7fff5fbff598  
0x7fff5fbff5a8  
0x7fff5fbfe5d8
```

```
0x7fff5fbff59c  
0x7fff5fbff5b0  
0x7fff5fbff578
```


Remember this example?

```
int *ptr;  
int a[10];  
int i;  
  
for(i = 0; i<10; i++){  
    a[i] = i*2;  
}  
  
ptr = a;  
  
for(i = 0; i<10; i++){  
    cout << ptr[i] << " ";  
}  
cout << endl;  
  
ptr[5] = 5;  
  
for(i = 0; i<10; i++){  
    cout << a[i] << " ";  
}  
cout << endl;
```

0 2 4 6 8 10 12 14 16 18

Iterating through ptr is the same
as iterating through array a.

0 2 4 6 8 5 12 14 16 18

Pointers and Arrays

- We said that we can define a pointer and assign the (address of the) array to it, and work with it just like we work with an array
- What happens here:
- `int b[10];`
- `b=ptr;`
- `Cout<<b[o];`

You cannot change the pointer value in an array variable.

Example

```
1 main()  
2 {int a[3]={2012,2,14};  
3 int* p1=&a[0];  
4 int* p2=a;  
5 }
```

a=?

a+1 = ?

*(a+2) = ?

*(a+2) = 3; What happened?

*(a+3) = ?

*(a+3) = 0xbffff37c;

What happened?

Addr	Name	Value
0xbffff374	a[0]	2012
0xbffff375		
0xbffff376		
0xbffff377		
0xbffff378	a[1]	2
0xbffff379		
0xbffff37a		
0xbffff37b		
0xbffff37c	a[2]	14
0xbffff37d		
0xbffff37e		
0xbffff37f		
0xbffff380	p1	0xbffff374
0xbffff381		
0xbffff382		
0xbffff383		
0xbffff384	p2	0xbffff374
0xbffff385		
0xbffff386		
0xbffff387		

Example

```
1 main()  
2 { char s1[] = "abc";  
3 char* s2 = "def";  
4 char* p1 = s1;  
5 }
```

s1 is a constant address,
and its value is not stored
in the memory.

Address slots
0x8048484-7 are
read-only.

What will happen if ...
s1[0] = 'z';
s2 += 1;
p1 += 1;

Addr	Name	Value
0x8048484	*s2	'd'
0x8048485	*(s2+1)	'e'
0x8048486	*(s2+2)	'f'
0x8048487	*(s2+3)	'\0'

⋮

0xbffff38c	s1[0]	'a'
0xbffff38d	s1[1]	'b'
0xbffff38e	s1[2]	'c'
0xbffff38f	s1[3]	'\0'
0xbffff390 0xbffff391 0xbffff392 0xbffff393	s2	0x8048484
0xbffff394 0xbffff395 0xbffff396 0xbffff397	p1	0xbffff38c

Summary

- Pointers allow you to access storage but it's extremely manual. Misjudging your pointer arithmetic will have strange results.
- Space is finite - management is important.
- C++ arrays and pointers are very easy to cause problems!



THE UNIVERSITY
of ADELAIDE

Questions?