

No.	Time	Source	Destination	Protocol	Length	Info
217	12.787188	10.170.56.60	128.119.245.12	HTTP	453	GET /wireshark-labs/HTTP-wireshark-file4.html

HTTP/1.1  
Frame 217: 453 bytes on wire (3624 bits), 453 bytes captured (3624 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24), Dst: 48:80:02:83:58:3f (48:80:02:83:58:3f)  
Internet Protocol Version 4, Src: 10.170.56.60, Dst: 128.119.245.12  
Transmission Control Protocol, Src Port: 59068, Dst Port: 80, Seq: 1, Ack: 1, Len: 399  
Hypertext Transfer Protocol

No.	Time	Source	Destination	Protocol	Length	Info
225	13.027521	128.119.245.12	10.170.56.60	HTTP	1355	HTTP/1.1 200 OK (text/html)

Frame 225: 1355 bytes on wire (10840 bits), 1355 bytes captured (10840 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 48:80:02:83:58:3f (48:80:02:83:58:3f), Dst: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24)  
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 10.170.56.60  
Transmission Control Protocol, Src Port: 80, Dst Port: 59068, Seq: 1, Ack: 400, Len: 1301  
Hypertext Transfer Protocol  
Line-based text data: text/html (23 lines)

No.	Time	Source	Destination	Protocol	Length	Info
233	13.055396	10.170.56.60	128.119.245.12	HTTP	476	GET /pearson.png HTTP/1.1

Frame 233: 476 bytes on wire (3808 bits), 476 bytes captured (3808 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24), Dst: 48:80:02:83:58:3f (48:80:02:83:58:3f)  
Internet Protocol Version 4, Src: 10.170.56.60, Dst: 128.119.245.12  
Transmission Control Protocol, Src Port: 59068, Dst Port: 80, Seq: 400, Ack: 1302, Len: 422  
Hypertext Transfer Protocol

No.	Time	Source	Destination	Protocol	Length	Info
255	13.294767	128.119.245.12	10.170.56.60	HTTP	745	HTTP/1.1 200 OK (PNG)

Frame 255: 745 bytes on wire (5960 bits), 745 bytes captured (5960 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 48:80:02:83:58:3f (48:80:02:83:58:3f), Dst: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24)  
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 10.170.56.60  
Transmission Control Protocol, Src Port: 80, Dst Port: 59068, Seq: 4222, Ack: 822, Len: 691  
[3 Reassembled TCP Segments (3611 bytes): #253(1460), #254(1460), #255(691)]  
Hypertext Transfer Protocol  
Portable Network Graphics

No.	Time	Source	Destination	Protocol	Length	Info
752	45.127287	10.170.56.60	10.91.50.90	HTTP	530	CCM_POST /ccm_system/request HTTP/1.1 (text/plain)

Frame 752: 530 bytes on wire (4240 bits), 530 bytes captured (4240 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24), Dst: 48:80:02:83:58:3f (48:80:02:83:58:3f)  
Internet Protocol Version 4, Src: 10.170.56.60, Dst: 10.91.50.90  
Transmission Control Protocol, Src Port: 59080, Dst Port: 80, Seq: 4359, Ack: 1, Len: 476  
[3 Reassembled TCP Segments (4834 bytes): #750(358), #751(4000), #752(476)]  
Hypertext Transfer Protocol  
MIME Multipart Media Encapsulation, Type: multipart/mixed, Boundary: "aAbBcCdDv1234567890VxXyYzZ"

No.	Time	Source	Destination	Protocol	Length	Info
833	51.475832	10.91.50.90	10.170.56.60	HTTP	545	HTTP/1.1 200 OK (text/plain)

Frame 833: 545 bytes on wire (4360 bits), 545 bytes captured (4360 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 48:80:02:83:58:3f (48:80:02:83:58:3f), Dst: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24)  
Internet Protocol Version 4, Src: 10.91.50.90, Dst: 10.170.56.60  
Transmission Control Protocol, Src Port: 80, Dst Port: 59080, Seq: 1, Ack: 4835, Len: 491  
Hypertext Transfer Protocol  
MIME Multipart Media Encapsulation, Type: multipart/mixed, Boundary: "aAbBcCdDv1234567890VxXyYzZ"

No.	Time	Source	Destination	Protocol	Length	Info
2202	141.639523	10.170.56.60	23.46.32.10	HTTP	466	GET /

DigiCertTrustedG4CodeSigningRSA4096SHA3842021CA1.crl HTTP/1.1  
Frame 2202: 466 bytes on wire (3728 bits), 466 bytes captured (3728 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24), Dst: 48:80:02:83:58:3f (48:80:02:83:58:3f)  
Internet Protocol Version 4, Src: 10.170.56.60, Dst: 23.46.32.10  
Transmission Control Protocol, Src Port: 59094, Dst Port: 80, Seq: 1, Ack: 1, Len: 412  
Hypertext Transfer Protocol

No.	Time	Source	Destination	Protocol	Length	Info
2204	141.641437	23.46.32.10	10.170.56.60	HTTP	371	HTTP/1.1 304 Not Modified

Frame 2204: 371 bytes on wire (2968 bits), 371 bytes captured (2968 bits) on interface \Device\NPF\_{4E350C0C-95E7-4BE3-ABEC-D2C46E3F3B43}, id 0  
Ethernet II, Src: 48:80:02:83:58:3f (48:80:02:83:58:3f), Dst: 6c:0b:5e:59:9b:24 (6c:0b:5e:59:9b:24)  
Internet Protocol Version 4, Src: 23.46.32.10, Dst: 10.170.56.60  
Transmission Control Protocol, Src Port: 80, Dst Port: 59094, Seq: 1, Ack: 413, Len: 317  
Hypertext Transfer Protocol