

FIT2014 Theory of Computation

Lecture 27 NP-completeness

slides by Graham Farr

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Warning

This material has been reproduced and communicated to you by or on behalf of Monash University
in accordance with s113P of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.


Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Overview

- ▶ Definition of NP-completeness
- ▶ Basic properties
- ▶ Existence of an NP-complete language
- ▶ Statement of the Cook-Levin Theorem

If $P \neq NP$:




In NP, not known to be in P:
SATISFIABILITY, 3-SAT,
HAMILTONIAN CIRCUIT,
3-COLOURABILITY,
VERTEX COVER,
INDEPENDENT SET, ...

GRAPH ISOMORPHISM,
INTEGER FACTORISATION, ...

In P:
2-SAT,
EULERIAN CIRCUIT,
2-COLOURABILITY,
CONNECTED GRAPHS,
SHORTEST PATH,
PRIMES,
Invertible matrices,
...,
All Context-Free Languages,
All Regular Languages.

If $P = NP$:

If $P = NP$



SATISFIABILITY, 3-SAT,
HAMILTONIAN CIRCUIT,
3-COLOURABILITY,
VERTEX COVER,
INDEPENDENT SET, ...

GRAPH ISOMORPHISM,
INTEGER FACTORISATION, ...

2-SAT,
EULERIAN CIRCUIT,
2-COLOURABILITY,
CONNECTED GRAPHS,
SHORTEST PATH,
PRIMES,
Invertible matrices,
...,
All Context-Free Languages,
All Regular Languages.

P and NP

Languages in P are “easy” ... or, at least, they have “efficient” (polynomial time) deciders.

Languages outside P are “hard”.

They don't have “efficient” (polynomial time) deciders.

Languages in NP: membership is “easy” (polynomial time) to verify.

NP contains many languages of great practical importance.

What are the “hardest” languages in NP?

Use polynomial-time reduction ...

NP-completeness


Definition

A language L is **NP-complete** if

- (a) L is in NP, and
- (b) every language in NP is polynomial-time reducible to L .
i.e.,

$$\forall K \in \text{NP} : K \leq_P L.$$

NP-completeness




L is **NP-complete** because ...

L is in NP,

and

everything in NP ...
is polynomial-time reducible to L

NP-completeness




L is not NP-complete because ...

L is not in NP.

It doesn't matter if
everything in NP
is polynomial-time reducible to L

NP-completeness

NP



L is not NP-complete because ...

not everything in NP
is polynomial-time reducible to L

NP-completeness

Theorem.

Let L be any NP-complete language.

There is a polynomial-time decider for L if and only if $P = NP$.

Proof.

(\Leftarrow)

If $P = NP$, then every language in NP has a polynomial-time decider.

Since L is NP-complete, it must be in NP
(using the first part of the definition of NP-completeness).

Therefore L has a polynomial-time decider.

(\implies)

We know $P \subseteq NP$.

It remains to show that, under our assumptions, $NP \subseteq P$.

Then we'll know that $P = NP$.

Let K be any language in NP . We will show it is also in P .

Since L is NP -complete, any language in NP is polynomial-time reducible to L .

Therefore $K \leq_P L$.

But we know that, if $K \leq_P L$ and L is in P , then K is in P too. (See Lecture 26.)

So K is in P .

We have shown that $NP \subseteq P$, which completes the proof.



Exercises

Prove:

Theorem.

Let L be any NP-complete language.

For every language K ,

K is in NP if and only if $K \leq_P L$.

Theorem.

Let L be any NP-complete language.

For every language K ,

K is in NP-complete if and only if $K \leq_P L$ and $L \leq_P K$.

Cook-Levin Theorem

Our first NP-complete language:

SATISFIABILITY $:=$ { satisfiable Boolean expressions in CNF }

Cook-Levin Theorem

SATISFIABILITY is NP-complete.

History: S. Cook (1971), L. Levin (1972)

Cook-Levin Theorem

To prove the Cook-Levin Theorem, we must show:

(a) SATISFIABILITY is in NP

- ▶ the easy part
- ▶ Given Boolean expression φ in CNF:
- ▶ Certificate = truth assignment to variables of φ .
- ▶ Verification: check that each clause is satisfied ...
- ▶ Prove verification works and takes polynomial time.

(b) For every L in NP, $L \leq_P$ SATISFIABILITY.

- ▶ much harder.

Reduction to SATISFIABILITY

Let's begin by looking at:

PARTITION INTO TRIANGLES:

the set of graphs G such that the vertex set of G can be partitioned into 3-sets (i.e., sets of size 3) so that each of these 3-sets induces a triangle in G .

How to do a polynomial-time reduction from
PARTITION INTO TRIANGLES to SATISFIABILITY?

Revision

Things to think about:

- ▶ If $P = NP$, which languages would be NP-complete?
- ▶ How to do a polynomial-time reduction from PARTITION INTO TRIANGLES to SATISFIABILITY?

Reading:

- ▶ Sipser, section 7.4, pp. 299–304.
- ▶ M. R. Garey and D. S. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*, W. H. Freeman & Co., San Francisco, 1979: §2.5.