FIT9137 Applied Session Week 11

Topics

Firewall

Covered Learning Outcomes:

• identify and describe fundamental concepts of network security mechanisms against common threats and countermeasures.

Instructions

- One of the main purposes of an applied session is to build the learning community, create connections and include the learners. The other goal is to give and receive feedback from your peers and or your tutors.
- Form groups of 2 students (online) or more face-to-face to work through the exercises. If met a problem, try to solve it by asking direct questions to your peers. If the issue was not solved within peers, ask your tutor. If you did not get a chance to solve the problem during your applied session with your peer or tutor, jump into one of many consultation hours and ask any of the tutors to help you. Please visit the "Teaching Team and Unit Resources" tile in the FIT9137 Moodle site.

ACTIVITY: Firewall

In this exercise we will configure the firewall service on a gateway router in a sample core configuration file. Find the file FIT9137_Week-11_Activity_Firewall.imn inside the workshop_files folder that you downloaded in Week 4. Open core and from the file menu open this core configuration .imn file in the VM.

The node phoenix is the gateway router with its eth0 connected to the Internal network of the organization, the eth1 interface to the Demilitarized Zone (DMZ), and the eth2 connected to the Internet. The firewall will protect the two networks: Internal, and DMZ against unauthorized traffic by inspecting the packets that pass through the router (or firewall).

The DMZ network is part of the organization's network where servers that provide services to the Internet will be located. The DMZ network is separated from the Internal network (or intranet) since it is possible for these servers to be compromised by an attacker and then be used to attack the rest of the network hence the firewall protects the Internal network against both the Internet and DMZ. Check out the content here for more information - https://en.wikipedia.org/wiki/DMZ_(computing). The diagram of a typical three-legged network model employing a DMZ using a single firewall is used in our workshop activity.




Figure 1: A company network with a DMZ

Firewall Policy

Open the Services configuration for the firewall router (node phoenix) and click the tool icon next to the Firewall setting (in the Security column). This will open a dialogue that lets you enter firewall rules based on the iptables tool (man iptables).

Enter the following as the basis for your firewall rules:

STEP 1: Default Policy

```
#!/bin/sh
# Set default policy: drop all packets
# This means that the firewall blocks all traffic for the identified chain iptables -P INPUT DROP iptables -P OUTPUT DROP iptables -P FORWARD DROP
```

After setting up this firewall, you should not be able to reach any computer inside the DMZ or the Internal network. In fact no traffic will be allowed to pass through, be sent from, or be delivered to the firewall.

The iptables commands use different chains for different tasks. The INPUT chain is for packets that have the firewall router as its destination. The OUTPUT chain is for packets that software on the firewall router wants to send somewhere else. The FORWARD chain controls the packets for which the firewall router performs routing. When a packet is passing through the firewall, entering from one interface, routed by the firewall, and then exiting from another interface, then the packet is checked against the FORWARD chain rules.

STEP 2: External to DMZ.

Now that the system is secure (all traffic is blocked), we can start allowing traffic for individual services to pass through. We will start by allowing the servers in DMZ to be accessible to external hosts.

For the configuration to persist in core we need to use the GUI however as we are learning the iptables rules it would be better to try the commands while the core configuration is running. This way we can test the rules and make sure the rules correctly match the intended traffic and then we can add the rules to the configuration via GUI.

Note: Keep a copy of the tested and correct rules in a text file so that you can add them to the Firewall service through GUI.

To test the policy, we just configured start the emulation and open a terminal on helios and try to visit the web server in DMZ:

```
lynx 10.1.1.71
```

STEP 3: Incoming Rule.

Now we add a rule that allows TCP packets for port 80 to pass from outside to the web server in DMZ. Open a terminal on phoenix and enter the following command:

```
iptables -A FORWARD -i eth2 -o eth1 -d 10.1.1.71 -p tcp --dport 80 -j ACCEPT
```

The command line arguments specify the criteria for a packet to match against and the policy to apply if the packet matches the criteria:

- -A FORWARD append the rule to the FORWARD chain
- -i eth2 input interface must match eth2 (the interface the packet came in) when omitted will match any interface
- -o eth1 output interface must match eth1 (the interface the packet is going out) when omitted will match any interface
- -d 10.1.1.70 destination IP address must match the specified address or address range (with subnet mask)
- -p tcp the protocol must match TCP
- --dport 80 the destination port must match 80, only if TCP or UDP is specified as protocol
- -j ACCEPT jump to ACCEPT target, the target policy to apply to the matched packet

With this rule, a client can now send a HTTP request to the web server. However, the server response will not pass through the firewall as all traffic from within the DMZ to the outside is still blocked. You can observe this by opening a Wireshark on the firewall (node phoenix) interface eth1 and another on the node Internet interface eth0. Then in the terminal on node helios enter:

lynx 10.1.1.71

Note: You can use tcpdump as a command line alternative to Wireshark. To do so in a separate terminal on phoenix issue tcpdump -1 -i eth1 and in a terminal on Internet issue tcpdump -1 -i eth0 which will print a summary of captured packets in the terminal.

STEP 4: Outgoing Rule

To allow the response from the server to pass through we use the following command (on phoenix):

```
iptables -A FORWARD -i eth1 -o eth2 -s 10.1.1.71 -p tcp --sport 80 -j ACCEPT
```

Notice the changes in the input and output interfaces and -s instead of -d to specify the source IP address that must be matched and the --sport instead of --dport indicating that the source

port must be 80.

Try to visit the web server from helios using the web server IP address.

Note: Observe that the iptables option -P is for policy and -p to identify the protocol. If you mistake one for the other, in terminal you will get an error, however in firewall service configuration of a node you will not see the errors.

To check if the rules that you have added to the Firewall service of a node have taken effect, run the emulation and execute the following command on that node:

```
iptables -L
```

If the policy is not changed or a rule does not appear then check the command to see if there are any syntax or option errors.

STEP 5:Other Services - DNS(Name resolution) & SMTP(Email)

Now add necessary rules that allow DNS and SMTP services by the nodes ns-argos and mail-argos respectively. For each service you need to add an incoming and an outgoing rules to the forward chain.

```
For DNS & SMTP services

iptables -A FORWARD -i eth2 -o eth1 -d 10.1.1.70 -p udp --dport 53 -j ACCEPT iptables -A FORWARD -i eth1 -o eth2 -s 10.1.1.70 -p udp --sport 53 -j ACCEPT

iptables -A FORWARD -i eth2 -o eth1 -d 10.1.1.72 -p tcp --dport 25 -j ACCEPT iptables -A FORWARD -i eth1 -o eth2 -s 10.1.1.72 -p tcp --sport 25 -j ACCEPT
```

STEP 6: Internal to DMZ.

Write rules that allow traffic from the Internal network to reach servers in DMZ: web, mail, and DNS.

```
iptables -A FORWARD -i eth0 -o eth1 -d 10.1.1.70 -p udp --dport 53 -j ACCEPT iptables -A FORWARD -i eth1 -o eth0 -s 10.1.1.70 -p udp --sport 53 -j ACCEPT iptables -A FORWARD -i eth0 -o eth1 -d 10.1.1.71 -p tcp --dport 80 -j ACCEPT iptables -A FORWARD -i eth1 -o eth0 -s 10.1.1.71 -p tcp --sport 80 -j ACCEPT iptables -A FORWARD -i eth0 -o eth1 -d 10.1.1.72 -p tcp --dport 25 -j ACCEPT iptables -A FORWARD -i eth1 -o eth0 -s 10.1.1.72 -p tcp --sport 25 -j ACCEPT
```

STEP 7: Internal to External.

Now that we have opened up the DMZ, we configure the firewall to allow the clients in the Internal network to access web servers outside. Try to find the correct iptables rules that would implement the following:

- Any packet from Internal network is allowed to pass to outside network
- Any traffic from the outside toward the Internal network is only accepted and allowed to pass if it is a response to a request made by a local client.

This can be achieved using only ESTABLISHED and RELATED packets to pass through in the opposite direction (from outside to Internal). This is the iptables method of *Stateful Inspection*. Do a research on this topic to find out how to implement these rules (man iptables-extensions).

```
iptables -A FORWARD -i eth0 -o eth2 -s 10.1.1.0/26 -p tcp --dport 80 -m state --
state NEW,RELATED,ESTABLISHED -j ACCEPT

iptables -A FORWARD -i eth2 -o eth0 -d 10.1.1.0/26 -p tcp --sport 80 -m state --
state RELATED,ESTABLISHED -j ACCEPT

Note: Enter each command in one line, that is -- and what follows is the
continuation of the iptables command, all in one line.
```

STEP 8: DMZ to External

Certain services require connecting to external servers as part of their operation. For instance, a DNS server can be configured to perform the *forwarding* operation which is to ask a query on behalf of its clients from another DNS server. In the given configuration the node ns-argos will resolve any query for the domain argos.edu and forward any other query to the node Internet. For simplicity the DNS service is configured on the Internet node rather than a separate server. Similarly, the node sphinx resolves queries for delos.edu and forwards any other queries to the Internet node. The Internet node then forwards the relevant queries to the appropriate server. As the configuration is isolated the scenario is only simulating the real-life example where the DNS server of an organization forwards its Internet queries to its Internet Service Provider.

Add required rules that allows ns-argos to forward queries for other domains to the Internet node. In this case ns-argos will be the client and the Internet the DNS server.

```
iptables -A FORWARD -i eth1 -o eth2 -s 10.1.1.70 -d 10.1.1.130 -p udp --dport 53
-m state --state NEW,ESTABLISHED -j ACCEPT

iptables -A FORWARD -i eth2 -o eth1 -d 10.1.1.70 -s 10.1.1.130 -p udp --sport 53
-m state --state ESTABLISHED -j ACCEPT

Note: Enter each command in one line, that is -m and what follows is the continuation of the iptables command, all in one line.
```

To test the rules, the Internal client selene should be able to resolve the name www.delos.edu.

This will test the Internal to DMZ rules as well as DMZ to External rules. For this to succeed a DNS query from selene must reach ns-argos, then a DNS query from ns-argos must reach Internet, then the reply from Internet must reach ns-argos, and finally the reply from ns-argos must reach selene. So, in total 4 rules must be correct for this test to succeed.

When an SMTP server needs to send an email to another domain it will be the client and the mail server of the recipient of the email will be the server. This also requires a different pair of rules compared to the ones you have written for the External to DMZ. Add the necessary rules to allow mail-argos to send email to any external mail server. Although we cannot test the rule as there is no other mail server in the given scenario.

```
iptables -A FORWARD -i eth1 -o eth2 -s 10.1.1.72 -p tcp --dport 25 -m state --
state NEW,ESTABLISHED -j ACCEPT

iptables -A FORWARD -i eth2 -o eth1 -d 10.1.1.72 -p tcp --sport 25 -m state --
state ESTABLISHED -j ACCEPT

Note: Enter each command in one line, that is -- and what follows is the
continuation of the iptables command, all in one line.
```

STEP 9: Internal to Firewall

```
iptables -A INPUT -i eth0 -s 10.1.1.0/26 -p tcp --dport 22 -j ACCEPT iptables -A OUTPUT -o eth0 -d 10.1.1.0/26 -p tcp --sport 22 -j ACCEPT
```

Write rules that allow clients in the Internal network to connect to SSH service on phoenix.