



CS 225

Data Structures

March 12 – Disjoint Sets

G Carl Evans





Disjoint Sets ADT

- Maintain a collection $S = \{s_0, s_1, \dots, s_k\}$
- Each set has a representative member.
- API:

```
void makeSets(int number);  
void union(int k1, const int k2);  
int find(int k);
```

Implementation #1



0	1	2	3	4	5	6	7


Find(k):

Union(k1, k2):

YOU EXPECTED A NEW DATA STRUCTURE

BUT IT WAS ME, TREE ALL ALONG

Implementation #2




0	1	2	3	4	5	6	7

Find(k):





Union(k1, k2):

Implementation #2


- We will continue to use an array where the index is the key
- The value of the array is:
 - **-1**, if we have found the representative element
 - **The index of the parent**, if we haven't found the rep. element
- We will call theses **UpTrees**:



UpTrees



Disjoint Sets



0	1	2	3	4	5	6	7	8	9

Find(k):

Union(k1, k2):

Disjoint Sets Find


```
1 int DisjointSets::find(int i) {  
2     if ( s[i] < 0 ) { return i; }  
3     else { return find( s[i] ); }  
4 }
```

Running time?


What is the ideal UpTree?

Disjoint Sets Union

```
1 void DisjointSets::union(int r1, int r2) {  
2  
3  
4 }
```




Disjoint Sets – Union



0	1	2	3	4	5	6	7	8	9	10	11
6	6	6	8	-1	10	7	-1	7	7	4	5

Disjoint Sets – Smart Union




Union by height

0	1	2	3	4	5	6	7	8	9	10	11
6	6	6	8		10	7		7	7	4	5

Idea: Keep the height of the tree as small as possible.

Disjoint Sets – Smart Union




Union by size

0	1	2	3	4	5	6	7	8	9	10	11
6	6	6	8		10	7		7	7	4	5

Idea: Keep the height of the tree as small as possible.

Disjoint Sets – Smart Union



Union by height

0	1	2	3	4	5	6	7	8	9	10	11
6	6	6	8		10	7		7	7	4	5

Idea: Keep the height of the tree as small as possible.

Union by size

0	1	2	3	4	5	6	7	8	9	10	11
6	6	6	8		10	7		7	7	4	5

Idea: Minimize the number of nodes that increase in height

Both guarantee the height of the tree is: _____.

Disjoint Sets Find

```
1 int DisjointSets::find(int i) {  
2     if ( s[i] < 0 ) { return i; }  
3     else { return find( s[i] ); }  
4 }
```

```
1 void DisjointSets::unionBySize(int root1, int root2) {  
2     int newSize = arr_[root1] + arr_[root2];  
3  
4     // If arr_[root1] is less than (more negative), it is the larger set;  
5     // we union the smaller set, root2, with root1.  
6     if ( arr_[root1] < arr_[root2] ) {  
7         arr_[root2] = root1;  
8         arr_[root1] = newSize;  
9     }  
10  
11     // Otherwise, do the opposite:  
12     else {  
13         arr_[root1] = root2;  
14         arr_[root2] = newSize;  
15     }  
16 }
```



Union by Size (limit on height)

To show that every tree in a disjoint set data structure using union by size has a height of at most $O(\log n)$ we will show that the inverse.

Base Case

Inductive Hypothesis




Union by Size

Case 1



Union by Size

Case 2




Union by Height (limit on height)

Much like before we will show the min(nodes) in a tree with a root of height $k \geq 2^k$

Base Case

IH

Path Compression





Disjoint Sets Analysis

The **iterated log** function:

The number of times you can take a log of a number.

$\log^*(n) =$

0 , $n \leq 1$

$1 + \log^*(\log(n))$, $n > 1$

What is $\lg^*(2^{65536})$?



Disjoint Sets Analysis

In a Disjoint Sets implemented with smart **unions** and path compression on **find**:

Any sequence of **m union** and **find** operations result in the worse case running time of $O(\text{_____})$,
where **n** is the number of items in the Disjoint Sets.