

Constructive Formalization of Regular Languages

Jan-Oliver Kaiser

Advisors: Christian Doczkal, Gert Smolka

Supervisor: Gert Smolka

April 27, 2012

1 Goal

2 State Removal

3 Brzozowski Algebraic Method

4 Transitive Closure

5 Our Approach

Goal:

Find simple proofs for the decidability of regular expression equivalence and the Myhill-Nerode theorem.

Roadmap:

- 1 RE \Rightarrow FA (**DONE**)
- 2 Emptiness test on FA (**Easy**)
- 3 RE equivalence (**Follows from 1 and 2**)
- 4 FA \Rightarrow RE (**Work in progress**)
- 5 Myhill-Nerode

Definitions:

- We use extended regular Expressions (RE):

$$r, s ::= \emptyset \mid \varepsilon \mid a \mid rs \mid r + s \mid r \& s \mid r^* \mid \neg r$$

$$\text{Def.: } \bigoplus_{x \in X} r_x := r_{x_0} + \dots + r_{x_{|X|-1}}$$

- Our Finite Automata (FA) are

$$(\Sigma, Q, q_0, F, \delta)$$

(The transition relation δ of deterministic FA is total).

Finite automata to regular expressions

- Converting REs to FAs is straight-forward and there is really only one algorithm (with slight variations):
We mirror the constructors of RE in operations on FAs.

Finite automata to regular expressions

- Converting REs to FAs is straight-forward and there is really only one algorithm (with slight variations):
We mirror the constructors of RE in operations on FAs.
- Converting FAs to REs is complicated and there are at least three algorithms found in textbooks.

Finite automata to regular expressions

- Converting REs to FAs is straight-forward and there is really only one algorithm (with slight variations):
We mirror the constructors of RE in operations on FAs.
- Converting FAs to REs is complicated and there are at least three algorithms found in textbooks.

Why is that?

My intuition:

- Converting REs to FAs is done by structural recursion on a **tree**. The result is a **flat structure**.

My intuition:

- Converting REs to FAs is done by structural recursion on a **tree**. The result is a **flat structure**.
- Converting FAs to REs **can not be done** by structural recursion. There is **no recursive structure** in FAs. But somehow we need to construct a **tree** of REs.

Three methods (+ variations):

- 1 Transitive Closure
- 2 State Removal
- 3 Brzozowski Algebraic Method


State Removal

Given: NFA $A = (\Sigma, Q, q_0, F, \delta)$.


New concept: Automata that have transitions labeled by RE.

Idea: Remove states until there are two or less states remaining.
Update the remaining states' transitions by incorporating the
"lost" paths.


Remove q from




Remove q from



to get



Repeat until A is of this form:



$$\Rightarrow \mathcal{L}(A) = \mathcal{L}(r_1^* r_2 (r_4 + r_3 r_1^* r_2)^*)$$

Caveats


- It looks like we only need to update two edges.

Caveats

- It looks like we only need to update two edges.
In reality, there can be $|Q| - 1$ states connected to q .

Caveats

- It looks like we only need to update two edges.
In reality, there can be $|Q| - 1$ states connected to q .



Caveats

- It looks like we only need to update two edges.
In reality, there can be $|Q| - 1$ states connected to q .
- What about final states?

Caveats

- It looks like we only need to update two edges.
In reality, there can be $|Q| - 1$ states connected to q .
- What about final states?
 - 1 Introduce a new final state without any outgoing edges.
 - 2 Introduce ε transitions from all other final states to the final new state.
 - 3 Make all other states non-final.
 - 4 Never remove the new final state.

Formalization:

- Requires a new kind of finite automaton that has RE transitions.
- Lots of details to consider.
- Induction on the number of states.

Brzozowski Algebraic Method

Given: FA $A = (\Sigma, Q, q_0, F, \delta)$.

Idea: Retrieve a RE for FA by solving a system of equations determined by δ .

Construct system of equations:

$$\begin{aligned}
 r_0 &= \sum_{\substack{a \in \Sigma \\ 0 \leq i < |Q|}} \{ a r_i \mid (q_0, a, q_i) \in \delta \} \quad (+ \varepsilon \text{ if } r_0 \in F) \\
 &\vdots \\
 r_{|Q|-1} &= \sum_{\substack{a \in \Sigma \\ 0 \leq i < |Q|}} \{ a r_i \mid (q_{|Q|-1}, a, q_i) \in \delta \} \quad (+ \varepsilon \text{ if } r_{|Q|-1} \in F)
 \end{aligned}$$

$$\Rightarrow \mathcal{L}(A) = \mathcal{L}(r_0)$$

Solve the system by substitution and **Arden's Lemma** which states that for all regular languages X , Y and Z the equation

$$X = YX + Z \tag{1}$$

has the unique solution

$$X = Y^*Z \tag{2}$$

Formalization:

- Requires a formalization of these equations and operations on them.
- We would need to prove Arden's Lemma.
- We would also need to prove that Arden's Lemma (and substitution) is enough to solve these systems of equations.

Transitive Closure

Given: FA $A = (\Sigma, Q, q_0, F, \delta)$.

Idea: Construct regexps r_f for every final states $f \in F$ s.t.
 r_f matches all words which A accepts with final state f .

$$\Rightarrow \mathcal{L}(A) = \mathcal{L}\left(\bigoplus_{f \in F} r_f\right)$$

How do we construct r_f ?

We generalize the idea of r_f to R_{ij}^k which matches all words which lead from state i to j while passing only through states with index smaller than k .

- 1 Merge multiple edges between states to one unified edge.
- 2 Construct regexp R_{ij}^k recursively:

$$R_{ij}^0 := \begin{cases} r & \text{if } i \neq j \wedge i \text{ has edge } r \text{ to } j \\ \varepsilon + r & \text{if } i = j \wedge i \text{ has edge } r \text{ to } j \\ \emptyset & \text{otherwise} \end{cases}$$

$$R_{ij}^k := R_{ik}^{k-1} R_{kk}^{k-1} R_{kj}^{k-1} + R_{ij}^{k-1}$$

$$\Rightarrow \mathcal{L}(A) = \mathcal{L}\left(\bigoplus_{f \in F} r_f\right) = \mathcal{L}\left(\bigoplus_{f \in F} R_{0f}^{|Q|}\right)$$

Formalization:

- Easier than the other methods.
- The recursive definition translates quite well.
- The details are quite challenging.

Formalization:

- Easier than the other methods.
- The recursive definition translates quite well.
- The details are quite challenging.

This appears to be the simplest formalization.

Our Approach:

There are different ways of formalizing R_{ij}^k itself, especially its parameters. Most practical so far:

k is of type nat, i and j are ordinals from $[0..|Q| - 1]$.

Our Approach:

There are different ways of formalizing R_{ij}^k itself, especially its parameters. Most practical so far:

k is of type nat, i and j are ordinals from $[0..|Q| - 1]$.

This gives us easy recursion and matching on k .

Our Approach:

There are different ways of formalizing R_{ij}^k itself, especially its parameters. Most practical so far:

k is of type nat, i and j are ordinals from $[0..|Q| - 1]$.

This gives us easy recursion and matching on k .

But we have to use $\min k (|Q| - 1)$ to map k to the corresponding ordinal (and then to a state).

To get a FA counterpart to R_{ij}^k , we introduce A_{ij}^k s.t.

$$\mathcal{L}(A_{ij}^k) = \mathcal{L}(R_{ij}^k).$$

A_{ij}^k is similar to A . It has one additional state, which has all incoming edges of state j and no outgoing edges. It only leaves states that are i or $< k$. It only enters states less than $< k$ or the new state.

We can then show that

$$\mathcal{L}\left(\bigcup_{f \in F} A_{q_0 f}^{|Q|}\right) = \mathcal{L}(A).$$

Lemmas:

- 1 The language of an automaton is the union of the words with runs on A that end in any final state, i.e.

$\mathcal{L}(A) = \bigcup_{f \in F} \mathcal{L}(A_f)$, where A_f accepts only in f . (Not difficult)

- 2 A path in A_{ij}^{k+1} that is not in A_{ij}^k can be decomposed into:

- a sub path from index 0 to the first occurrence of k
- a sub path from the first to the last occurrence of k
- the remaining sub path from the last occurrence of k to the end.

(Complex; requires a new operations on lists)

More lemmas:

- 3 A path on A which passes through a final state more than once is in $\mathcal{L}(A)^*$ (Relies on the same operations we need for lemma 2)
- 4 Any path on A_{ij}^k that ends in the new accepting state can be mapped to an equivalent path that ends state j (and vice-versa).
- 5 Any path on A_{ij}^k that does not end in the new accepting state is also a path on A .

Goal
Recap
Finite automata to regular expressions
State Removal
Brzozowski Algebraic Method
Transitive Closure
Our Approach

Definitions
Lemmas

Thank you for your attention