




IndustryLUX FARO X3


HTS 1500-75 DALI | 5.000 K



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	75°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 83

PROPERTIES

through-wiring	5 x 1,5 mm²
connection	Terminal: 5-pole max. 1,5 mm²
module per circuit breaker B10A	32
module per circuit breaker B16A	51
module per circuit breaker C10A	32
module per circuit breaker C16A	51
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX FARO X3 HTS 1500-75 DALI 5.000 K	
product code	111550650067
EAN code	4260374015741
warranty	5 years

ACCESSORIES

Mounting plate for 2-3 luminaires
Cord suspension 2m
Top-Entry-Cap

PERFORMANCE

luminous efficiency	131 lm/W
system performance	65 W
luminous flux	8.500 lm
dimmmable	DALI

RESILIENCE

protection class	II
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–30 to +60 °C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes 2x mounting clip and cable gland M20

DIMENSION

L x W x H / Ø (H2)	1.500 x 104 x 57 (77) mm
weight	2,5 kg