IndustryLUX
RODALIS ECO
98

CE D IP 65 IK 08

LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING

169

287

LIGHT INFORMATION

beam angle	120°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

PROPERTIES

|	
through-wiring	No
connection	Cable: 3 x 1,0 mm², 1,5 m
module per circuit breaker B10A	3
module per circuit breaker B16A	4
module per circuit breaker C10A	5
module per circuit breaker C16A	8
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX RODALIS ECO 98	
product code	435012090045
EAN code	4260374015581
warranty	3 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	133 lm/W
system performance	98 W
luminous flux	13.000 lm
dimmable	No

RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistent	Yes
operating temperature	−30 to +45 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	Ø 287 (110) x 76 (169) mm
weight	3,4 kg