




ClickLUX ROCKET


90EM, mit Einzelbatterie 3h



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	90°
color temperature	4.000 5.000 6.500 K
color tolerance	< 5 SDCM
color rendering index	> 83

PROPERTIES

through-wiring	6 x 1,5 mm² + 1 x 2,5 mm²
connection	Plug: 7-pole max. 2,5 mm²
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

ClickLUX ROCKET 90EM, self
contained 3h

product code	722095220093
EAN code	4260374015024
warranty	5 years

ACCESSORIES

ClickLUX ROCKET blank module 1m

ClickLUX ROCKET blank module 2m

ClickLUX ROCKET blank module 1m (Plastic)

ClickLUX ROCKET blank module 2m (Plastic)

ClickLUX ROCKET Connector-Set

ClickLUX ROCKET chain suspension

Cord suspension 2m

Cord suspension 5m

PERFORMANCE

luminous efficiency	151 lm/W
system performance	76 W
luminous flux	11.500 lm
dimnable	Slide switch DALI

RESILIENCE

protection class	I
impact resistance	IK05
protection type	IP54
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	0 to +50°C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	Aluminium
housing color	Grey

SCOPE OF DELIVERY

includes 1x clip for ceiling- or cord mounting

DIMENSION

L x W x H / Ø (H2)	2.000 x 67 x 47 (84) mm
weight	3,3 kg