RoadLUX
PRO
140 | 50 x 150°

CE | D | IP 66 | IK 08

LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING

LIGHT INFORMATION

beam angle	50 x 150°
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 70

PROPERTIES

through-wiring	No
connection	Terminal: 3-pole max. 2,5 mm²
module per circuit breaker B10A	14
module per circuit breaker B16A	22
module per circuit breaker C10A	14
module per circuit breaker C16A	22
switching cycles	> 500.000
voltage range AC	200 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

RoadLUX PRO 140 | 50 x 150°	
product code	495040140126
EAN code	4260374016670
warranty	5 years

ACCESSORIES

Adapter 76mm for RoadLUX PRO
Adapter 34mm for RoadLUX PRO
Wall bracket for RoadLUX PRO
Corner bracket for RoadLUX PRO
Double post-top bracket for RoadLUX PRO

PERFORMANCE

luminous efficiency	146 lm/W
system performance	140 W
luminous flux	20.500 lm
dimmable	No

RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP66
lifespan	> 50.000 h [L80, B10]
UV resistent	Yes
operating temperature	–30 to +50 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Grey

SCOPE OF DELIVERY

reducing adaptor for 42 mm; screws

DIMENSION

L x W x H / Ø (H2)	617 (763) x 352 x 115 (167) mm
weight	8,2 kg