



Rettungszeichen L 49DMS003SL mit Einzelbatterie


















TECHNICAL DRAWING



LIGHT INFORMATION

PROPERTIES

through-wiring	No
connection	Terminal: 2-pole max. 2,5 mm²
module per circuit breaker B10A	_
module per circuit breaker B16A	_
module per circuit breaker C10A	_
module per circuit breaker C16A	_
switching cycles	> 500.000
voltage range AC	230 V AC, 50/60 Hz
voltage range DC	176 – 275 V DC

ORDER OVERVIEW

Escape sign luminaire SIGMA-L 49DMS003SL (self contained)

product code	- SL49DMS003SL
EAN code	4260374015420
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	117 lm/W
system performance	6 VA
luminous flux	.350 lm
dimmable	No

RESILIENCE

protection class	II
impact resistance	IK04
protection type	IP40
UV resistent	No
operating temperature	0 to +35 °C

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes mounting material and 3-pcs. pictogramset

DIMENSION

 lichtline GmbH · Weiherstraße 25 · D - 95448 Bayreuth
 L x W x H / Ø (H2)
 324 x 199 x 37 (10) mm www.lichtline.com

 fon +49(0)921 / 5 07 37 89 - 10 · fax +49(0)921 / 5 07 37 89 - 29 · vertrieb@lichtline.com
 weight
 1,2 kg