




Rettungszeichen **KAPPA** 46UT003SL mit Einzelbatterie



TECHNICAL DRAWING



LIGHT INFORMATION

PROPERTIES

through-wiring	No
connection	Terminal: 2-pole max. 2,5 mm ²
module per circuit breaker B10A	—
module per circuit breaker B16A	—
module per circuit breaker C10A	—
module per circuit breaker C16A	—
switching cycles	> 500.000
voltage range AC	230 V AC, 50/60 Hz
voltage range DC	176 – 275 V DC

ORDER OVERVIEW

Escape sign luminaire KAPPA 46UT003SL (self contained)	
product code	K46UT003SL
EAN code	4260374015406
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	130 lm/W
system performance	4,5 VA
luminous flux	.130 lm
dimnable	No

RESILIENCE

protection class	II
impact resistance	IK04
protection type	IP54
UV resistant	No
operating temperature	0 to +35 °C
foodready	Yes

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes mounting material and 3-pcs. pictogramset
--

DIMENSION

L x W x H / Ø (H2)	239 x 164 x 59 mm
weight	0,6 kg