




FloodLUX PRO


40 | 90 x 90° | 4.000K



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	90 x 90°
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm ² , 1,3 m
module per circuit breaker B10A	13
module per circuit breaker B16A	21
module per circuit breaker C10A	22
module per circuit breaker C16A	35
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

FloodLUX PRO 40 90 x 90° 4.000K	
product code	454004000024
EAN code	4260374018308
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	143 lm/W
system performance	40 W
luminous flux	5.700 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP66
lifespan	> 60.000 h [L80, B10]
UV resistant	Yes
operating temperature	–30 to +45 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	308 x 317 (360) x 83 (153) mm
weight	4,3 kg