


OfficeLUX RAYET 2.0


75 | doppelt asymmetrisch



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	double-asymmetric
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

PROPERTIES

through-wiring	5 x 2,5 mm ²
connection	Terminal: 5-pole max. 2,5 mm ²
module per circuit breaker B10A	18
module per circuit breaker B16A	29
module per circuit breaker C10A	28
module per circuit breaker C16A	44
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60Hz

ORDER OVERVIEW

OfficeLUX RAYET 2.0 75 double asymmetric	
product code	127526400148
EAN code	4260374018957
warranty	5 years

ACCESSORIES

PERFORMANCE

luminous efficiency	154 lm/W
system performance	74 W
luminous flux	11.400 lm
dimmmable	No

RESILIENCE

protection class	I
impact resistance	IK04
protection type	IP40
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–20 to +45 °C
foodready	No

MATERIAL

cover	diffuse cover
material (cover)	PMMA
material (housing)	Aluminium
housing color	Silvergrey

SCOPE OF DELIVERY

Module includes 1x clip for ceiling installation
--

DIMENSION

L x W x H / Ø (H2)	1450 x 64 x 95 (105) mm
weight	3,3 kg