IndustryLUX
TUBOLA
1500 RED

| | | EN 05 | EL | D | IP 65 | IK 08 | | SWITCH | |

LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING

Ø 48　80

1500

LIGHT INFORMATION

beam angle	130°
color temperature	Rot
color tolerance	< 5 SDCM

PROPERTIES

through-wiring	3 x 1,5 mm²
connection	Terminal: 3-pole max. 2,5 mm²
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz
voltage range DC	176 - 276 V DC

ORDER OVERVIEW

IndustryLUX TUBOLA 1500 RED	
product code	811515320017
EAN code	4260374013655
warranty	5 years

ACCESSORIES

Mounting plate for 2-3 luminaires
Cord suspension 2m
Stainless steel mounting clip (set of 2)
Cable gland for pressure equalization

PERFORMANCE

luminous efficiency	62 lm/W
system performance	30 W
luminous flux	1.850 lm
dimmable	No

RESILIENCE

protection class	II
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistent	Limited
operating temperature	–25 to +50 °C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes 2x mounting clip and cable gland M20

DIMENSION

L x W x H / Ø (H2)	1.500 x Ø 48 (80) mm
weight	1,0 kg