ClickLUX
2.0
4000-90 EM-EB

EM | EL | D | IP 40 | IK 05 | SWITCH

LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING

1528

LIGHT INFORMATION

beam angle	90°
color temperature	4.000 K
color tolerance	< 4 SDCM
color rendering index	> 80

PROPERTIES

through-wiring	4 x 1,5 mm² + 1 x 2,5 mm²
connection	Plug: 7-pole max. 2,5 mm²
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

ClickLUX 2.0 4000-90 EM-EB (self contained)	
product code	701540220094
EAN code	4260374019268
warranty	5 years

ACCESSORIES

ClickLUX connection plug
ClickLUX connector cable 1500mm
ClickLUX 2.0 blank module
ClickLUX 2.0 blank cover
ClickLUX 2.0 clip system 1
ClickLUX 2.0 clip system 3
ClickLUX 2.0 mounting clip for blank cover

PERFORMANCE

luminous efficiency	155 lm/W
system performance	56 W
luminous flux	8.700 lm
dimmable	Dip switch

RESILIENCE

protection class	I
impact resistance	IK05
protection type	IP40
lifespan	> 50.000 h [L80, B10]
UV resistent	Limited
operating temperature	0 to +50°C
foodready	Available on request

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	Aluminium
housing color	Grey

SCOPE OF DELIVERY

mounting clip system type 2 pre-installed

DIMENSION

L x W x H / Ø (H2)	1.528 x 67 x 65 mm
weight	2,2 kg