


# ClickLUX 2.0

4000-90 DALI



## LIGHT DISTRIBUTION CURVE



## TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	90°
color temperature	4.000 K
color tolerance	< 4 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	6 x 1,5 mm <sup>2</sup> + 1 x 2,5 mm <sup>2</sup>
connection	Plug: 7-pole max. 2,5 mm <sup>2</sup>
module per circuit breaker B10A	36
module per circuit breaker B16A	57
module per circuit breaker C10A	36
module per circuit breaker C16A	57
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz
voltage range DC	176 – 264 V DC

## ORDER OVERVIEW

ClickLUX 2.0 4000-90 DALI	
product code	701540560084
EAN code	4260374014874
warranty	5 years

## ACCESSORIES

ClickLUX connection plug
ClickLUX connector cable 1500mm
ClickLUX 2.0 blank module
ClickLUX 2.0 blank cover
ClickLUX 2.0 clip system 1
ClickLUX 2.0 clip system 3
ClickLUX 2.0 mounting clip for blank cover

## PERFORMANCE

luminous efficiency	155 lm/W
system performance	56 W
luminous flux	8.700 lm
dimnable	Slide switch   DALI

## RESILIENCE

protection class	I
impact resistance	IK05
protection type	IP40
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	–25 to +50 °C
foodready	Available on request

## MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	Aluminium
housing color	Grey

## SCOPE OF DELIVERY

mounting clip system type 2 pre-installed
---

## DIMENSION

L x W x H / Ø (H2)	1.528 x 67 x 28 (60) mm
weight	2,0 kg