



# Rettungszeichen SICMA L 48U003SL mit Einzelbatterie


















# **TECHNICAL DRAWING**



#### LIGHT INFORMATION

# **PROPERTIES**

through-wiring	No
connection	Terminal: 2-pole max. 2,5 mm²
module per circuit breaker B10A	_
module per circuit breaker B16A	_
module per circuit breaker C10A	_
module per circuit breaker C16A	_
switching cycles	> 500.000
voltage range AC	230 V AC, 50/60 Hz
voltage range DC	176 – 275 V DC

#### **ORDER OVERVIEW**

Escape sign luminaire SIGMA-L 48U003SL (self contained)

	_
product code	SL48U003SL
EAN code	4260374015413
warranty	5 years

# **ACCESSORIES**

No accessories available

#### **PERFORMANCE**

luminous efficiency	130 lm/W
system performance	5,5 VA
luminous flux	.260 lm
dimmable	No

# **RESILIENCE**

protection class	II
impact resistance	IK04
protection type	IP43
UV resistent	No
operating temperature	0 to +35 °C

# **MATERIAL**

cover	Transparent cover
material (cover)	PC
material (housing)	PC
housing color	White

#### **SCOPE OF DELIVERY**

includes mounting material and 3-pcs. pictogramset

#### **DIMENSION**

 $\label{lichtline} \begin{tabular}{lll} \textbf{lichtline} & GmbH \cdot Weiherstraße & 25 \cdot D - 95448 \ Bayreuth \\ fon & +49(0)921 / 5 07 37 89 - 10 \cdot fax & +49(0)921 / 5 07 37 89 - 29 \cdot vertrieb@\textbf{lichtline.com} \\ \end{tabular}$ 

265 x 191 x 37 (10) mm www.lichtline.com